



SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Important information *** This Safety Data Sheet is only authorised for use by HP for HP Original products. Any unauthorised use of this Safety Data Sheet is strictly prohibited and may result in legal action being taken by HP. ***

1.1. Product identifier

Trade name or designation of the mixture F0L63Series
Registration number -
Synonyms HP 2580 Black Solvent Ink
Issue date 26-May-2015
Version number 08
Revision date 14-Sep-2020
Supersedes date 27-Apr-2020

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Inkjet printing
Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

HP PPS Austria GmbH
Wienerbergstrasse 41, 3rd Floor
Wien, Austria 1120

Telephone +43 (1) 81118-0000

HP Inc. health effects line

(Toll-free within the US) 1-800-457-4209

(Direct) 1-760-710-0048

HP Inc. Customer Care Line

(Toll-free within the US) 1-800-474-6836

(Direct) 1-208-323-2551

Email: hpcustomer.inquiries@hp.com

1.4 Emergency telephone number +43 (1) 406 43 43

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids	Category 2	H225 - Highly flammable liquid and vapor.
-------------------	------------	---

Health hazards

Serious eye damage/eye irritation	Category 1	H318 - Causes serious eye damage.
-----------------------------------	------------	-----------------------------------

Environmental hazards

Hazardous to the aquatic environment, long-term aquatic hazard	Category 3	H412 - Harmful to aquatic life with long lasting effects.
--	------------	---

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Acetone, C.I. Solvent Orange 11, Chromium, 1-[2-[5-(1,1-dimethylpropyl)-2-hydroxy-3-nitrophenyl]diazonyl]-2-naphthalenol 1-[2-[2-hydroxy-4(or 5)-nitrophenyl]diazonyl]-2-naphthalenol Ammonium Sodium Complexes, Cyclohexanone, Ethyl Alcohol

Hazard pictograms



Signal word

Danger

Hazard statements

H225 Highly flammable liquid and vapor.
H318 Causes serious eye damage.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 Keep container tightly closed.
P240 Ground/Bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P273 Avoid release to the environment.

Response

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P310 Immediately call a POISON CENTER or doctor/physician.
P370 + P378 In case of fire: Use CO2 to extinguish.

Storage

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information

EUH208 - Contains tinting agent. May produce an allergic reaction.

2.3. Other hazards

Prolonged or repeated skin contact may cause drying, cracking, or irritation. May produce an allergic reaction. Potential routes of exposure to this product are skin and eye contact, ingestion, and inhalation.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Ethyl Alcohol	<80	64-17-5 200-578-6	-	603-002-00-5	
Classification:	Flam. Liq. 2;H225				
Cyclohexanone	<10	108-94-1 203-631-1	01-2119453616-35-XXXX	606-010-00-7	#
Classification:	Flam. Liq. 3;H226, Acute Tox. 4;H302, Acute Tox. 4;H312, Skin Irrit. 2;H315, Eye Dam. 1;H318, Acute Tox. 4;H332				
Acetone	<7.5	67-64-1 200-662-2	-	606-001-00-8	#
Classification:	Flam. Liq. 2;H225, Eye Irrit. 2;H319, STOT SE 3;H336				
Chromium, 1-[2-[5-(1,1-dimethylpropyl)-2-hydroxy-3-nitrophenyl]diazonyl]-2-naphthalenol 1-[2-[2-hydroxy-4(or 5)-nitrophenyl]diazonyl]-2-naphthalenol Ammonium Sodium Complexes	<5	1029600-34-7 700-174-4	-	-	
Classification:	Aquatic Chronic 2;H411				
C.I. Solvent Orange 11	<1	61725-76-6	-	-	
Classification:	Skin Sens. 1;H317, Aquatic Acute 1;H400, Aquatic Chronic 1;H410				

SECTION 4: First aid measures

General information	Not available.
4.1. Description of first aid measures	
Inhalation	Move person to fresh air immediately. If symptoms persist, get immediate medical attention.
Skin contact	In case of contact, immediately remove contaminated clothing and flush skin with copious amounts of water. Wash clothing separately before reuse. Get medical attention, if needed.
Eye contact	In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention immediately.
Ingestion	Rinse mouth out with water. If the material is swallowed, get immediate medical attention or advice -- Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.
4.2. Most important symptoms and effects, both acute and delayed	Not available.
4.3. Indication of any immediate medical attention and special treatment needed	Not available.

SECTION 5: Firefighting measures

General fire hazards	Not available.
5.1. Extinguishing media	
Suitable extinguishing media	Suitable extinguishing media: sand, carbon dioxide (CO ₂) or dry chemical.
Unsuitable extinguishing media	Not available.
5.2. Special hazards arising from the substance or mixture	Not available.
5.3. Advice for firefighters	
Special protective equipment for firefighters	Firefighters should wear full protective clothing including self contained breathing apparatus. Avoid runoff into storm sewers and ditches which lead to waterways.
Special fire fighting procedures	Move containers from fire area if you can do it without risk.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Avoid contact with skin. Avoid inhalation of vapors or mists. Do not touch or walk through spilled material. Ensure adequate ventilation. Remove all sources of ignition. Use personal protective equipment to minimize exposure to skin and eye. In the case of vapor formation use a respirator with an approved filter.
For emergency responders	Not available.
6.2. Environmental precautions	Do not flush into surface water or sanitary sewer system.
6.3. Methods and material for containment and cleaning up	Not available.
6.4. Reference to other sections	Not available.

SECTION 7: Handling and storage

7.1. Precautions for safe handling	Avoid contact with skin, eyes and clothing. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Wear personal protective equipment.
7.2. Conditions for safe storage, including any incompatibilities	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame.
7.3. Specific end use(s)	Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001

Components	Type	Value
Acetone (CAS 67-64-1)	MAK	1200 mg/m ³ 500 ppm
	STEL	4800 mg/m ³ 2000 ppm
Cyclohexanone (CAS 108-94-1)	MAK	20 mg/m ³ 5 ppm
	STEL	80 mg/m ³ 20 ppm
Ethyl Alcohol (CAS 64-17-5)	Ceiling	3800 mg/m ³ 2000 ppm
	MAK	1900 mg/m ³ 1000 ppm

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	1210 mg/m ³ 500 ppm
	STEL	81.6 mg/m ³ 20 ppm
Cyclohexanone (CAS 108-94-1)	TWA	40.8 mg/m ³ 10 ppm

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures Not available.

Derived no effect levels (DNELs)

Components	Type	Route	Value	Form
Cyclohexanone (CAS 108-94-1)	Workers	Dermal	4 mg/kg bw/d	Systemic Long Term
		Dermal	4 mg/kg bw/d	Systemic Short Term
		Inhalation	80 mg/m ³	Local short term
		Inhalation	80 mg/m ³	Systemic short term
		Inhalation	40 mg/m ³	Local long term
		Inhalation	40 mg/m ³	Systemic long term

Predicted no effect concentrations (PNECs)

Components	Type	Route	Value	Form
Cyclohexanone (CAS 108-94-1)	Not applicable	Intermittent	0.329 mg/l	Releases
		Marine water	0.00329 mg/l	
		Sediment	0.168 mg/kg	Freshwater
		Sediment	0.0168 mg/kg	Marine water
		Soil	0.0143 mg/kg	
		STP	10 mg/l	Sewage Treatment Plant

Exposure guidelines

Austria MAK: Skin designation

Cyclohexanone (CAS 108-94-1)

Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering controls Not available.

Individual protection measures, such as personal protective equipment

General information Not available.

Eye/face protection Wear safety glasses; chemical goggles (if splashing is possible).
Eye wash fountain and emergency showers are recommended.

Skin protection

- Hand protection	Recommended gloves: Nitrile 6 mil minimum thickness.
- Other	Wear appropriate chemical resistant clothing.
Respiratory protection	Provide adequate ventilation. In case of insufficient ventilation wear suitable respiratory equipment.
Thermal hazards	Not available.
Hygiene measures	Do not get this material in contact with skin. Avoid contact with skin, eyes and clothing. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Launder contaminated clothing before reuse.
Environmental exposure controls	Not available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state	Not available.
Form	Liquid.
Color	Black.
Odor	Solvent.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	41.0 °F (5.0 °C) Setafash Closed Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidizing properties	Not available.

9.2. Other information

VOC	743 g/l US EPA Method 24
-----	--------------------------

SECTION 10: Stability and reactivity

10.1. Reactivity	Not available.
10.2. Chemical stability	Stable at normal conditions.
10.3. Possibility of hazardous reactions	None known.
10.4. Conditions to avoid	Heat, flames and sparks.
10.5. Incompatible materials	Not available.
10.6. Hazardous decomposition products	Not available.

SECTION 11: Toxicological information

General information	Not available.
---------------------	----------------

Information on likely routes of exposure

Inhalation	Inhalation may result in mild irritation to the respiratory system.
Skin contact	Contact with skin may result in mild irritation.
Eye contact	Causes serious eye damage.
Ingestion	Ingestion is not a likely route of exposure.

Symptoms Not available.

11.1. Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

Components	Species	Test Results
-------------------	----------------	---------------------

Cyclohexanone (CAS 108-94-1)

Acute

Inhalation

Vapor

LC50

Rat

> 6.2 mg/l, 4 Hours

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Causes serious eye damage.

Respiratory sensitization Based on available data, the classification criteria are not met.

Skin sensitization Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

IARC Monographs. Overall Evaluation of Carcinogenicity

Cyclohexanone (CAS 108-94-1)

3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity Based on available data, the classification criteria are not met.

Specific target organ toxicity - single exposure Based on available data, the classification criteria are not met.

Specific target organ toxicity - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

Mixture versus substance information Not available.

Other information Complete toxicity data are not available for this specific formulation
Refer to Section 2 for potential health effects and Section 4 for first aid measures.

SECTION 12: Ecological information

12.1. Toxicity

Aquatic toxicity Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

LC50/96h/rainbow trout =<100 mg/l and >10 mg/l.

Components	Species	Test Results
-------------------	----------------	---------------------

Ethyl Alcohol (CAS 64-17-5)

Aquatic

Crustacea

EC50

Daphnia

9268, 48 Hours

Fish

LC50

Fish

12900, 96 Hours

12.2. Persistence and degradability Not available.

12.3. Bioaccumulative potential Not available.

Partition coefficient n-octanol/water (log Kow)

Acetone

-0.24

Cyclohexanone

0.81

Ethyl Alcohol

-0.31

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil Not available.

12.5. Results of PBT and vPvB assessment Not a PBT or vPvB substance or mixture.

12.6. Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste	Not available.
Contaminated packaging	Not available.
EU waste code	Not available.
Disposal methods/information	Do not dispose of together with general office waste. Do not allow this material to drain into sewers/water supplies. Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations. Ensure collection and disposal with an appropriately licensed waste contractor.

SECTION 14: Transport information

DOT

UN number	UN1210
UN proper shipping name	Printing ink
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Special precautions for user	Not available.
DOT Supplemental Information	DOT Classification only applies to shipments within the US and Puerto Rico.

IATA

UN number	UN1210
UN proper shipping name	Printing ink
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	No.
Special precautions for user	Not available.

IMDG

UN number	UN1210
UN proper shipping name	Printing ink
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Transport hazard class(es)	
Marine pollutant	No.
EmS	Not available.
Special precautions for user	Not available.

ADR

UN number	UN1210
UN proper shipping name	Printing ink
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Hazard No. (ADR)	Not available.
Tunnel restriction code	Not available.
Packing group	II
Environmental hazards	No.
Special precautions for user	Not available.

ADR; IATA; IMDG





SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorizations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Acetone (CAS 67-64-1)

Cyclohexanone (CAS 108-94-1)

Ethyl Alcohol (CAS 64-17-5)

Other information

This Safety Data Sheet complies with the requirements of Regulation (EU) 2015/830. Classification according to Regulation (EC) No 1272/2008 as amended.

Specific Provisions: Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (in the amended version OJ L 396 from 29.05.2007 page 3 with further rectifications and amendments).

Other regulations

All chemical substances in this HP product have been notified or are exempt from notification under chemical substances notification laws in the following countries: US (TSCA), EU (EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South Korea, New Zealand, and China.

National regulations

Not available.

15.2. Chemical safety assessment

See attached SUMI or GEIS document, if applicable.

SECTION 16: Other information

References

Regulation (EC) No. 1907/2006 of December 18, 2006 concerning the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH) and establishing a European Chemicals Agency (REACH).

Regulation (EU) 2015/830 of May 28, 2015 amending Regulation (EC) No. 1907/2006.

Regulation (EC) No. 1272/2008 of December 16, 2008 on classification, labeling and packaging of substances and mixtures, and amendments (CLP).

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any H-statements not written out in full under Sections 2 to 15

H225 Highly flammable liquid and vapor.
H226 Flammable liquid and vapor.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

Revision information

1. Product and Company Identification: Alternate Trade Names
Composition / Information on Ingredients: Ingredients
9. Physical & Chemical Properties: Multiple Properties

Training information

Follow training instructions when handling this material.

Disclaimer

This Safety Data Sheet document is provided without charge to customers of HP. Data is the most current known to HP at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and may not meet regulatory requirements in other countries.

Explanation of abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS	Chemical Abstracts Service
CERCLA	Comprehensive Environmental Response Compensation and Liability Act
CFR	Code of Federal Regulations
COC	Cleveland Open Cup
DOT	Department of Transportation
EPCRA	Emergency Planning and Community Right-to-Know Act (aka SARA)
IARC	International Agency for Research on Cancer
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
RCRA	Resource Conservation and Recovery Act
REC	Recommended
REL	Recommended Exposure Limit
SARA	Superfund Amendments and Reauthorization Act of 1986
STEL	Short-Term Exposure Limit
TCLP	Toxicity Characteristics Leaching Procedure
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
VOC	Volatile Organic Compounds

Safe Use of Mixture Information (SUMI)

--

Solvent based inks: SB01 *English*

Disclaimer

This SUMI is a generic document for communicating conditions of safe use of a product in response to the REACH obligation. This document relates only to conditions of safe use and is not specific to a product. By adding this SUMI to a specific product SDS, the importer/formulator declares that the mixture can safely be used following the instructions below. Following occupational health legislation, the employer of workers remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product. Derived No Effect Levels (DNEL) and Predicted No Effect Concentration (PNEC) values of substances derived from the Chemical Safety Assessment (CSA) will be given in section 8 of the SDS.

The REACH registration number(s), where applicable, completes an extended product SDS.

Operational conditions

Maximum duration Up to 8 hours per day

Frequency of exposure < 240 days per year

Process conditions

- Covers use at ambient temperatures.
- Use of an integrated local exhaust ventilation is required in drying zone.
- Adequate ventilation should be provide for the areas where printing is performed. ANSI/ASHRAE Standard 62.1-2013 provides guidelines to ensure acceptable air quality in the workspace.
- Use explosion proof electrical equipment.
- Keep emissions below the occupational exposure limits of the ingredients specified in section 8 of the SDS.
- Avoid direct contact.
- Regular cleaning of equipment and work area.
- Supervision in place to check that Risk Management Measures are in place are being correctly used and Operational Conditions followed.

Risk management measures

Conditions and measures related to Personal Protection Equipment, hygiene and health evaluation

- Wear safety glasses with side shields (or goggles), if splashing is possible.
- Wear appropriate chemical resistant gloves: see section 8 of the SDS.
- Wear appropriate chemical resistant clothing.
- In case of inadequate ventilation wear respiratory protection.
- Eye wash fountain and emergency showers are recommended.
- Avoid breathing mist/vapours.
- Avoid contact with skin, eyes and clothing.
- Training of workers in relation to proper use and maintenance of all Personal protection equipment (PPE) must be ensured.



Good practice advice

- Use personal protective equipment as required.
- Wash hands before breaks and after work.
- Keep good industrial hygiene and safety practice.
- Use only with adequate ventilation.
- Do no eat, drink or smoke when using this product.
- Wash contaminated clothing before reuse.
- Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
- Store in a well-ventilated place.
- Keep container tightly closed.
- Store at room temperature.



Environmental measures

- Do not allow this material to drain into sewers/water supplies.
- Dispose of waste material according to Local, State, Federal and Provincial Environmental Regulations.
- Ensure collection and disposal with appropriately licenced waste contractor.

Use descriptors

IS-Use at industrial sites

PW-Widespread use by professional workers

SU7-Printing and reproduction media

PC18-Inks and Toners

PROC1-Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2-Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC3- Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition

PROC8a-Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC8b-Transfer of substance or mixture (charging and discharging) at dedicated facilities

ERC5-Use at industrial site leading to inclusion into/onto article

ERC8c-Widespread use leading to inclusion into/onto article (indoor)

Additional information on product composition

In section 2 of the SDS as well as on the label, the classification of the mixture is provided.

The classification of the mixture is based on the individual ingredients and their concentration within the mixture.

All ingredients contributing to the classification are stated in Section 3 of the SDS.

Relevant limit values of ingredients on which the exposure assessment is based, are listed in section 8 of the SDS.

The product may contain sensitizing ingredients that may cause allergic reaction to certain people.

Section 2 of the SDS states these ingredients where applicable.