



MATERIAL SAFETY DATA SHEET

SECTION 1 PRODUCT IDENTIFICATION				
• Product Identification				
Polymer Lithium-Ion Rechargeable Battery	Nominal PACK Capacity:2200mAh			
Nominal Voltage:3.7V	PACK P/N: DAP574868PA			
Cell P/N:PP574868AB	Customer P/N-1:			
Nominal Cell Capacity:2200mAh				
Cell UL NO:				
PACK UL NO: _____	Nominal PACK Capacity:2200mAh	Customer Model Name:		
• Manufacture Identification				
Tianjin Lishen Battery Joint-Stock CO. LTD.	86 - 22 - 83710366			
6 Lanyuan Road, Huayuan Hi-Tech	Phone Number (For Information)			
Industry Park, Tianjin 300384, China	86 - 22 - 83710366			
Http://www.lishen.com.cn	Emergency Phone Number Telex			
	86 - 22 - 83710366			
Note: Blank spaces are not permitted. If any item is not applicable or no information is available, the space must be marked to indicate that.				
SECTION 2 COMPOSITION & INFORMATION ON INGREDIENTS				
Equivalent lithium content per cell		0.66g		
COMPONENTS-Chemical Name and Common Names				
(Hazardous Components 1% or greater, Carcinogens 0.1% or greater)		%	OSHA PEL	ACGIH TLV
Lithium Cobaltite		41%		CAS Number 12190-79-3
Graphite Carbon		21%		OTHER LIMITS RECOMMENDED 7782-42-5
Lithium Hexafluorophosphate		4%		CAS Number 21324-40-3
Organic solvent		14%		
Non-Hazardous Ingredients(tabs,pouch,separator,etc.)		20%		
Total		100%		
SECTION 3 HAZARDS IDENTIFICATION				
Primary Routes of Entry		<input type="checkbox"/> Inhalation <input type="checkbox"/> Ingestion <input type="checkbox"/> Skin Absorption <input type="checkbox"/> Eye contact		CARCINOGEN LISTED IN <input type="checkbox"/> NTP <input type="checkbox"/> OSHA <input type="checkbox"/> IARC Monograph <input type="checkbox"/> NOT Listed
Health Hazards		harmful and irritant All chemicals are contained in a sealed can. Risk of exposure occurs only,if the battery is mechanically or electrically abused(mechanical, thermal, electrical), which leads to the rupture of the battery container. Electrolyte leakage, electrode materials reaction with moisture/water or battery vent/fire may follow, depending upon the circumstances.		
Medical Conditions Generally Aggravated By Exposure				
An acute exposure will not generally aggravate any medical condition.				
Symptoms of Exposure		Skin contact, no effect under routine handling and use.		
Eye Contact		No effect under routine handling and use		
Skin Contact		No effect under routine handling and use		
Ingestion		No effect under routine handling and use		
Inhalation		No		
Reported as carcinogen		Not applicable		
SECTION 4 FIRST-AID MEASURES				
If exposure to internal materials in cell due to damaged outer casing, the following actions are recommended.				
Eye Contact		In case of eye contact, flush with lot of water for 15 minutes, and get medical help.		
Skin Contact		In case of skin contact with contents of battery, flush immediately with water.		
Inhalation		In case of light inhalation ,move to an area with flash air immediately, if irritation persists, get medical help.		
Ingestion		In case of ingestion, drink milk/water to induce vomitting and wash out,get medical help.		
SECTION 5 FIREFIGHTING MEASURES				
Extinguisher Media:				
CO ₂ or dry chemical power				
Special Fire-Fighting Procedures:				
In case of fire in cell original containers, use CO2 or dry chemical extinguisher; For fire in an adjacent area, water can be used.				
SECTION 6 ACCIDENTAL RELEASE MEASURES				
On Land:				
Place material into suitable containers, If the skin has come into contact with the electrolyte, it should be washed thoroughly with water,Sand or earth should be used to absorb any exuded material.Seal leaking battery and contaminated absorbent material should be treated by local regulation,and call local fire/police department to ask for help.				
In Water:				
If possible, remove from water far from body in special fixture, and call local fire/police department to ask for help.				



SECTION 13 DISPOSAL CONSIDERATIONS

There is no contamination during normal operation and use. Lithium batteries should have their terminals insulated prior to disposal, do not throw away a used battery and provide them for recycling company.

Open cells should be treated as hazardous waste. If the leakage or other material is Released, we should take actions as follows:
 Leave the area, allow the batteries to cool down, let the vapors to dissipate .
 Avoid skin and eye contact or inhalation of vapors. Remove spiller liquid with absorbent and incinerate after.

Waste Disposal method Opened cells should be treated as hazardous waste.
 Incineration: incineration should never be performed by battery users but eventually by trained professionals in authorized facilities with proper gas and fumes treatment.
 Landfilling: According to the proper laws and regulations in different countries or areas, the battery should be buried deeply in the specified place;
 Recycling: Send to authorized recycling facilities to get Co,Cu and Al, eventually through licensed waste carrier;

SECTION 14 Transportation

Lishen's DAP574868PA Lithium-Ion Polymer batteries are considered to be "Rechargeable Lithium Ion Polymer Batteries" and meet the requirements of transportation by the United States Department of Transportation (DOT), International Civil Aviation Administration (ICAO), International Air Transportation Association (IATA) special provision UN3480 as "non-dangerous goods" or "non-hazardous materials". These lithium batteries can be transported in nonrestrictive material and as Non-Dangerous Goods as they meet all the requirements in below:

1	Lithium content requirement	
1.1	For the bar cells, the lithium content can not overpass 20Wt/h;	
1.2	For the batteries, the lithium content can not overpass 100Wt/h;	
2	15. Transport information	
2.1	<ul style="list-style-type: none"> When large amount of batteries are transported by ship, vehicle and railroad, avoid high temperature and dew condensation. Avoid transportation which may cause damage of package. For Lithium ion batteries, the Watt-hour rating is no more than 20Wh/cell and 100Wh/battery pack can be treated as "non-dangerous goods" by the United Nations Recommendations on the Transport of Dangerous Goods/Special Provision 188, provided that the products are prevented from being short-circuited each other and are packaged in an appropriate condition which satisfies Packing Group II performance level. The shipment complies with the Packing Instruction 965 under IATA and so the cargo can be exempted from Dangerous Goods regulations. 	requirements in Part 3 -38.3 item us Goods, Manual of Tests and
3		
1.1		put into hard outer package to equipments (such as mobile
1.2	The cell quantity is more than 24pcs or the battery quantity is more than 12pcs, they must be asked to meet with the requirements in blow besides they are assembled in finished equipment.	
a	Every package must be marked in the content that the packages are loaded in lithium cells or batteries, also add new lithium iron operation label , also need point out the corrective actions when the packages are damaged.	
b	Every batch shipment must be appended document which should contain the content that the packages are loaded in lithium cells or batteries, also need point out the corrective actions when the packages are damaged.	
c	Every package must pass 1.2mm fall test in any direction. No damage for the cells and batteries, no move and touch together, no cells or batteries escape from the package.	
d	Every package weight can not overpass 10kg if the batteries can not be assembled in finished equipment.	

SECTION 15 REGULATORY INFORMATION

OSHA Hazard Communication Standard (29 CFR 1910.1200)
 Hazardous Non-hazardous

SECTION 16 OTHER INFORMATION

There is no hazards in accordance with the UN recommendations test.(UN manual of tested and criteria 38.3)

Pack Part Number	DAP574868PA
Nominal Voltage	3.7V
Nominal Pack Capacity	2200mAh
Pack Mass	40g
Equivalent Lithium Content	0.66g

Test NO	Test Item	Criteria	Result	Remark
38.3.4.1	Altitude Test	No mass loss,leakage,venting,disassembly,rupture,and fire.OCV should not be less than 90% before testing	Passed	Test 1 to 5 must be conducted in sequence on the same cell or battery
38.3.4.2	Thermal Test	No mass loss,leakage,venting,disassembly,rupture,and fire.OCV should not be less than 90% before testing	Passed	
38.3.4.3	Vibration	No mass loss,leakage,venting,disassembly,rupture,and fire.OCV should not be less than 90% before testing	Passed	
38.3.4.4	Shock	No mass loss,leakage,venting,disassembly,rupture,and fire.OCV should not be less than 90% before testing	Passed	
38.3.4.5	External Short Circuit	External temperature should not exceed 170degC. No disassembly, and fire within six hours of this test.	Passed	
38.3.4.6	Impact	External temperature should not exceed 170degC. No disassembly, and fire within six hours of this test.	-----	Only for cell
38.3.4.7	Overcharge	No disassembly, and fire within seven days of this test.	Passed	Only for battery
38.3.4.8	Forced Discharge	No disassembly, and fire within seven days of this test.	-----	Only for cell