

## MATERIAL SAFETY DATA SHEET

<b>SECTION 1 PRODUCT IDENTIFICATION</b>																									
<ul style="list-style-type: none"> <li>• Product Identification               <table style="width: 100%; border: none;"> <tr> <td style="border: none; width: 50%;">Polymer Lithium-Ion Rechargeable Battery</td> <td style="border: none; width: 50%;">Nominal PACK Capacity:2960mAh</td> </tr> <tr> <td style="border: none;">Nominal Voltage:3.7V</td> <td style="border: none;">PACK P/N: CSP289791PA</td> </tr> <tr> <td style="border: none;">Cell P/N:PP289791AB</td> <td style="border: none;">Customer P/N-1:</td> </tr> <tr> <td style="border: none;">Nominal Cell Capacity:2960mAh</td> <td style="border: none;"></td> </tr> <tr> <td style="border: none;">Cell UL NO:</td> <td style="border: none;"></td> </tr> <tr> <td style="border: none;">PACK UL NO: _____</td> <td style="border: none;">Nominal PACK Capacity:2960mAh</td> </tr> <tr> <td style="border: none;"></td> <td style="border: none;">Customer Model Name:</td> </tr> </table> </li> <li>• Manufacture Identification               <table style="width: 100%; border: none;"> <tr> <td style="border: none; width: 50%;">Tianjin Lishen Battery Joint-Stock CO. LTD.</td> <td style="border: none; width: 50%;">86 - 22 - 83710366</td> </tr> <tr> <td style="border: none;">6 Lanyuan Road, Huayuan Hi-Tech</td> <td style="border: none;">Phone Number (For Information)</td> </tr> <tr> <td style="border: none;">Industry Park, Tianjin 300384, China</td> <td style="border: none;">86 - 22 - 83710366</td> </tr> <tr> <td style="border: none;"><a href="http://www.lishen.com.cn">Http://www.lishen.com.cn</a></td> <td style="border: none;">Emergency Phone Number Telex</td> </tr> <tr> <td style="border: none;"></td> <td style="border: none;">86 - 22 - 83710366</td> </tr> </table> </li> </ul> <p style="font-size: small; margin-top: 10px;">Note: Blank spaces are not permitted. If any item is not applicable or no information is available, the space must be marked to indicate that.</p>		Polymer Lithium-Ion Rechargeable Battery	Nominal PACK Capacity:2960mAh	Nominal Voltage:3.7V	PACK P/N: CSP289791PA	Cell P/N:PP289791AB	Customer P/N-1:	Nominal Cell Capacity:2960mAh		Cell UL NO:		PACK UL NO: _____	Nominal PACK Capacity:2960mAh		Customer Model Name:	Tianjin Lishen Battery Joint-Stock CO. LTD.	86 - 22 - 83710366	6 Lanyuan Road, Huayuan Hi-Tech	Phone Number (For Information)	Industry Park, Tianjin 300384, China	86 - 22 - 83710366	<a href="http://www.lishen.com.cn">Http://www.lishen.com.cn</a>	Emergency Phone Number Telex		86 - 22 - 83710366
Polymer Lithium-Ion Rechargeable Battery	Nominal PACK Capacity:2960mAh																								
Nominal Voltage:3.7V	PACK P/N: CSP289791PA																								
Cell P/N:PP289791AB	Customer P/N-1:																								
Nominal Cell Capacity:2960mAh																									
Cell UL NO:																									
PACK UL NO: _____	Nominal PACK Capacity:2960mAh																								
	Customer Model Name:																								
Tianjin Lishen Battery Joint-Stock CO. LTD.	86 - 22 - 83710366																								
6 Lanyuan Road, Huayuan Hi-Tech	Phone Number (For Information)																								
Industry Park, Tianjin 300384, China	86 - 22 - 83710366																								
<a href="http://www.lishen.com.cn">Http://www.lishen.com.cn</a>	Emergency Phone Number Telex																								
	86 - 22 - 83710366																								

<b>SECTION 2 HAZARDS IDENTIFICATION</b>	
Primary Routes of Entry	<input type="checkbox"/> Inhalation <input type="checkbox"/> Ingestion <input type="checkbox"/> Skin Absorption <input type="checkbox"/> Eye contact
Health Hazards	acute and chronic All chemicals are contained in a sealed can. Risk of exposure occurs only,if the battery is mechanically or electrically abused(mechanical, thermal, electrical), which leads to the rupture of the battery container. Electrolyte leakage, electrode materials reaction with moisture/water or battery vent/fire may follow, depending upon the circumstances.
Medical Conditions Generally Aggravated By Exposure An acute exposure will not generally aggravate any medical condition.	
Symptoms of Exposure	Skin contact, no effect under routine handling and use.
Eye Contact	No effect under routine handling and use
Skin Contact	No effect under routine handling and use
Ingestion	No effect under routine handling and use
Inhalation	No
Reported as carcinogen	Not applicable

<b>SECTION 3 COMPOSITION &amp; INFORMATION ON INGREDIENTS</b>					
Equivalent lithium content per cell	0.888g				
COMPONENTS-Chemical Name and Common Names	%	OSHA PEL	ACGIH TLV	CAS Number	OTHER LIMITS RECOMMENDED
(Hazardous Components 1% or greater, Carcinogens 0.1% or greater)					
Lithium Cobaltite	41%			12190-79-3	
Graphite Carbon	21%			7782-42-5	
Lithium Hexafluorophosphate	4%			21324-40-3	
Organic solvent	14%				
Non-Hazardous Ingredients(tabs,pouch,separator,etc.)	20%				
Total	100%				

<b>SECTION 4 FIRST-AID MEASURES</b>	
If exposure to internal materials in cell due to damaged outer casing, the following actions are recommended.	
Eye Contact	In case of eye contact, flush with lot of water for 15 minutes, and get medical help.
Skin Contact	In case of skin contact with contents of battery, flush immediately with water.
Inhalation	In case of light inhalation ,move to an area with flash air immediately, if irritation persists, get medical help.
Ingestion	In case of ingestion, drink milk/water to induce vomitting and wash out,get medical help.

<b>SECTION 5 FIREFIGHTING MEASURES</b>	
Extinguisher Media:	CO <sub>2</sub> or dry chemical power
Special Fire-Fighting Procedures:	
In case of fire in cell original containers, use CO2 or dry chemical extinguisher; For fire in an adjacent area, water can be used.	

<b>SECTION 6 ACCIDENTAL RELEASE MEASURES</b>	
On Land: Place material into suitable containers, If the skin has come into contact with the electrolyte, it should be washed thoroughly with water,Sand or earth should be used to absorb any exuded material.Seal leaking battery and contaminated absorbent material should be treated by local regulation,and call local fire/police department to ask for help.	
In Water: If possible, remove from water far from body in special fixture, and call local fire/police department to ask for help	





**SECTION 13 DISPOSAL CONSIDERATIONS**

There is no contamination during normal operation and use. Lithium batteries should have their terminals insulated prior to disposal, do not throw away a used battery and provide them for recycling company.

Open cells should be treated as hazardous waste. If the leakage or other material is Released, we should take actions as follows:

Leave the area, allow the batteries to cool down, let the vapors to dissipate .  
Avoid skin and eye contact or inhalation of vapors. Remove spiller liquid with absorbent and incinerate after.

Waste Disposal method Opened cells should be treated as hazardous waste.

Incineration: incineration should never be performed by battery users but eventually by trained professionals in authorized facilities with proper gas and fumes treatment.

Landfilling:According to the proper laws and regulations in different countries or areas, the battery should be buried deeply in the specified place;

Recycling: Send to authorized recycling facilities to get Co,Cu and Al,eventually through licensed waste carrier;

**SECTION 14 Transportation**

Lishen's DAP574868PA Lithium-Ion Polymer batteries are considered to be "Rechargeable Lithium Ion Polymer Batteries" and meet the requirements of transportation by the United States Department of Transportation (DOT), International Civil Aviation Administration (ICAO), International Air Transportation Association (IATA) special provision UN3480 as "non-dangerous goods" or "non-hazardous materials".These lithium batteries can be transported in nonrestrictive material and as Non-Dangerous Goods as they meet all the requirements in below:

1	Lithium content requirement
1.1	For the bar cells,the lithium content can not overpass 20Wt/h;
1.2	For the batteries, the lithium content can not overpass 100Wt/h;
2	Meet with UN Test Requirement
2.1	All the cell and battery must be verified to meet with all the requirements in Part 3 -38.3 item (UN38.3 tests) for "Recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria" .
3	Package Requirement
1.1	The cell and battery must be packaged specially and singly, and put into hard outer package to prevent short-circuit if they do not be assembled in finished equipments (such as mobile phone,camera,NBPC.and so on)
1.2	The cell quantity is more than 24pcs or the battery quantity is more than 12pcs, they must be asked to meet with the requirements in blow besides they are assembled in finished equipment.
a	Every package must be marked in the content that the packages are loaded in lithium cells or batteries,also add new lithium iron operation label , also need point out the corrective actions when the packages are damaged.
b	Every batch shipment must be appendix document which should contain the content that the packages are loaded in lithium cells or batteries, also need point out the corrective actions when the packages are damaged.
c	Every package must pass 1.2mm fall test in any direction. No damage for the cells and batteries, no move and touch together, no cells or batteries escape from the package.
d	Every package weight can not overpass 10kg if the batteries can not be assembled in finished equipment.

**SECTION 15 REGULATORY INFORMATION**

OSHA Hazard Communication Standard ( 29 CFR 1910.1200)

Hazardous  Non-hazardous

**SECTION 16 OTHER INFORMATION**

There is no hazards in accordance with the UN recommendations test.(UN manual of tested and criteria 38.3)

Pack Part Number	CHP289791PA
Nominal Voltage	3.7V
Nominal Pack Capacity	2960mAh
Pack Mass	56g
Equivalent Lithium Content	0.888g

Test NO	Test Item	Criteria	Result	Remark
38. 3. 4. 1	Altitude Test	No mass loss,leakage,venting,disassembly,rupture,and fire.OCV should not be less than 90% before testing	Passed	
38. 3. 4. 2	Thermal Test	No mass loss,leakage,venting,disassembly,rupture,and fire.OCV should not be less than 90% before testing	Passed	
38. 3. 4. 3	Vibration	No mass loss,leakage,venting,disassembly,rupture,and fire.OCV should not be less than 90% before testing	Passed	
38. 3. 4. 4	Shock	No mass loss,leakage,venting,disassembly,rupture,and fire.OCV should not be less than 90% before testing	Passed	
38. 3. 4. 5	External Short Circuit	External temperature should not exceed 170degC. No disassembly, and fire within six hours of this test.	Passed	
38. 3. 4. 6	Impact	External temperature should not exceed 170degC. No disassembly, and fire within six hours of this test.	Passed	
38. 3. 4. 7	Overcharge	No disassembly, and fire within seven days of this test.	-----	Only for battery
38. 3. 4. 8	Forced Discharge	No disassembly, and fire within seven days of this test.	Passed	