



SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture CD406 Series
Registration number -
Synonyms HP DS100 Specialty Textile Light Black Scitex Ink
Issue date 13-Aug-2016
Version number 01

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Inkjet printing
Uses advised against None known.

Company identification

HP Belgium BVBA
Hermeslaan 1B, Floor B1
Diegem, Belgium 1831
Telephone 32 2 729 71 11

HP Inc. health effects line
(Toll-free within the US) 1-800-457-4209
(Direct) 1-760-710-0048
HP Inc. Customer Care Line
(Toll-free within the US) 1-800-474-6836
(Direct) 1-208-323-2551
Email: hpcustomer.inquiries@hp.com
Emergency numbe +32 (0) 70245245

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: 1,4-diaminoanthraquinone, Ethylacetate, Ethylene Glycol, Monobutyl Ether Acetate

Hazard pictograms



Signal word Warning

Hazard statements

H312 Harmful in contact with skin.
H317 May cause an allergic skin reaction.

Precautionary statements

Prevention

P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

Response

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.
P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention.
P312 - Call a POISON CENTER/doctor/physician if you feel unwell.
P363 - Wash contaminated clothing before reuse.

Storage

Not available.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information

None.

2.3. Other hazards

Potential routes of exposure to this product are skin and eye contact, ingestion, and inhalation.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Ethylene Glycol, Monobutyl Ether Acetate	<90	112-07-2 203-933-3	01-2119475112-47-XXXX	607-038-00-2	#
Classification:	Acute Tox. 4;H302, Acute Tox. 4;H312				
1,4-diaminoanthraquinone	<2.5	128-95-0 204-922-6	-	-	
Classification:	Skin Sens. 1;H317				
Ethylacetate	<2.5	141-78-6 205-500-4	-	607-022-00-5	
Classification:	Flam. Liq. 2;H225, Eye Irrit. 2;H319, STOT SE 3;H336				

SECTION 4: First aid measures

General information Not available.

4.1. Description of first aid measures

Inhalation Move to fresh air. If symptoms persist, get medical attention.

Skin contact In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If irritation persists get medical attention. Remove and isolate contaminated clothing and shoes. Thoroughly wash (or discard) clothing and shoes before reuse.

Eye contact In case of contact, immediately flush eyes with large amounts of water, continuing to flush for 15 minutes. If irritation persists get medical attention.

Ingestion If swallowed, seek medical advice immediately and show this container or label.

4.2. Most important symptoms and effects, both acute and delayed Not available.

4.3. Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

General fire hazards Not available.

5.1. Extinguishing media

Suitable extinguishing media CO₂, water, dry chemical, or foam

Unsuitable extinguishing media Water may be ineffective. Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture Not available.

5.3. Advice for firefighters

Special protective equipment for firefighters Not available.

Special fire fighting procedures Firefighters should wear full protective clothing including self contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Not available.

For emergency responders	Not available.
6.2. Environmental precautions	Not available.
6.3. Methods and material for containment and cleaning up	Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).
6.4. Reference to other sections	Not available.

SECTION 7: Handling and storage

7.1. Precautions for safe handling	Avoid contact with skin, eyes and clothing. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Wear personal protective equipment.
7.2. Conditions for safe storage, including any incompatibilities	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame.
7.3. Specific end use(s)	Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Belgium. Exposure Limit Values.

Components	Type	Value
Ethylacetate (CAS 141-78-6)	TWA	1461 mg/m3 400 ppm
Ethylene Glycol, Monobutyl Ether Acetate (CAS 112-07-2)	STEL	333 mg/m3
	TWA	50 ppm 133 mg/m3 20 ppm

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU

Components	Type	Value
Ethylene Glycol, Monobutyl Ether Acetate (CAS 112-07-2)	STEL	333 mg/m3
	TWA	50 ppm 133 mg/m3 20 ppm

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures Not available.

Derived no-effect level (DNEL)

Components	Type	Route	Value	Form
Ethylacetate (CAS 141-78-6)	Workers	Dermal	63 mg/kg	Systemic long term
		Inhalation	734 mg/m3	Local long term
		Inhalation	734 mg/m3	Systemic long term
		Inhalation	1468 mg/m3	Local short term
		Inhalation	1468 mg/m3	Systemic short term
Ethylene Glycol, Monobutyl Ether Acetate (CAS 112-07-2)	Consumers	Dermal	72 mg/kg bw/d	Systemic acute short term
		Dermal	102 mg/kg bw/d	Systemic long term
		Inhalation	80 mg/m3	Systemic long term
		Inhalation	200 mg/m3	Local acute short term
		Oral	8.6 mg/kg bw/d	Systemic long term
	Workers	Oral	36 mg/kg bw/d	Systemic acute short term
		Dermal	169 mg/kg bw/d	Systemic long term
		Dermal	120 mg/kg bw/d	Systemic acute short term
		Inhalation	333 mg/m3	Local acute short term
		Inhalation	133 mg/m3	Systemic long term

Predicted no effect concentrations (PNECs)

Components	Type	Route	Value	Form
Ethylacetate (CAS 141-78-6)	Not applicable	Freshwater	0.24 mg/l	
		Intermittant	1.65 mg/l	Releases
		Marine water	0.024 mg/l	
		Sediment	1.15 mg/kg	Freshwater
		Sediment	0.115 mg/kg	Marine water
		Soil	0.148 mg/kg	
		STP	650 mg/l	Sewage Treatment Plant
Ethylene Glycol, Monobutyl Ether Acetate (CAS 112-07-2)	Not applicable	Freshwater	0.304 mg/l	
		Intermittant	0.56 mg/l	Releases
		Marine water	0.0304 mg/l	
		Secondary	0.06 g/kg	Food poisoning
		Sediment	2.03 mg/kg	Freshwater
		Sediment	0.203 mg/kg	Marine water
		Soil	0.42 mg/kg	
		STP	90 mg/l	Sewage Treatment Plant

8.2. Exposure controls

Appropriate engineering controls

Use in a well ventilated area.
Ensure adequate ventilation, especially in confined areas. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Additional area ventilation or local exhaust may be required to maintain air concentrations below recommended exposure limits.

Individual protection measures, such as personal protective equipment

General information

Not available.

Eye/face protection

Avoid contact with eyes
Wear safety glasses; chemical goggles (if splashing is possible).

Skin protection

- Hand protection

Recommended gloves: Nitrile 6 mil minimum thickness.

- Other

Use personal protective equipment to minimize exposure to skin and eye.

Respiratory protection

Not available.

Thermal hazards

Not available.

Hygiene measures

Not available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state

Not available.

Color

Black.

Odor

Not available.

Odor threshold

Not available.

pH

Not applicable.

Melting point/freezing point

Not determined.

Initial boiling point and boiling range

Not determined.

Flash point

> 145.0 °F (> 62.8 °C) (Closed Cup)

Evaporation rate

Not determined.

Flammability (solid, gas)

Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)

Not available.

Flammability limit - upper (%)

Not available.

Vapor pressure

Not determined.

Relative density

0.94 g/cm³ @ 20 Degrees C

Solubility(ies)

Not available.

Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not applicable.
Explosive properties	Not available.
Oxidizing properties	Not available.
9.2. Other information	No relevant additional information available.
Specific gravity	0.94 @ 20 Degrees C
VOC (Weight %)	< 850 g/L

SECTION 10: Stability and reactivity

10.1. Reactivity	Not available.
10.2. Chemical stability	Stable at normal conditions
10.3. Possibility of hazardous reactions	Will not occur.
10.4. Conditions to avoid	Not available.
10.5. Incompatible materials	strong oxidizing agents Strong acids and strong alkalis. oxidizing agents
10.6. Hazardous decomposition products	None known.

SECTION 11: Toxicological information

General information	Not available.
11.1. Information on toxicological effects	
Acute toxicity	Harmful in contact with skin.
Skin corrosion/irritation	Based on available data, the classification criteria are not met.
Serious eye damage/eye irritation	Based on available data, the classification criteria are not met.
Respiratory sensitization	Based on available data, the classification criteria are not met.
Skin sensitization	May cause sensitization by skin contact.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Based on available data, the classification criteria are not met.
Reproductive toxicity	Based on available data, the classification criteria are not met.
Specific target organ toxicity - single exposure	Based on available data, the classification criteria are not met.
Specific target organ toxicity - repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met.

Product	Species	Test Results
CD406 Series		
Acute		
<i>Oral</i>		
LD50	Rat	2400 mg/kg
Components		
Ethylacetate (CAS 141-78-6)		
Acute		
<i>Inhalation</i>		
LC50	Rat	16000 ppm, 6 Hours
LD50	Mouse	1500 ppm, 4 Hours
	Rabbit	2500 ppm, 4 Hours
	Rat	4000 ppm, 4 Hours
<i>Oral</i>		
LD50	Mouse	0.44 g/kg
	Rabbit	4.9 g/kg
	Rat	11.3 ml/kg

Components	Species	Test Results
		5.6 g/kg
<i>Other</i>		
LD50	Cat	3 g/kg
	Guinea pig	3 g/kg
Ethylene Glycol, Monobutyl Ether Acetate (CAS 112-07-2)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	1500 mg/kg
<i>Oral</i>		
LD50	Rat	2400 mg/kg
<i>Other</i>		
LD50	Mouse	754 mg/kg
Mixture versus substance information	Not available.	
Other information	Complete toxicity data are not available for this specific formulation	

SECTION 12: Ecological information

12.1. Toxicity

Components	Species	Test Results
Ethylacetate (CAS 141-78-6)		
Aquatic		
Fish	LC50	Indian catfish (<i>Heteropneustes fossilis</i>) 200.32 - 225.42 mg/l, 96 hours
12.2. Persistence and degradability	Not available.	
12.3. Bioaccumulative potential	Not available.	
Partition coefficient n-octanol/water (log Kow)		
Ethylacetate		0.73
Bioconcentration factor (BCF)	Not available.	
12.4. Mobility in soil	Not available.	
12.5. Results of PBT and vPvB assessment	Not a PBT or vPvB substance or mixture.	
12.6. Other adverse effects	Not available.	

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste	Not available.
Contaminated packaging	Not available.
EU waste code	Not available.
Disposal methods/information	Do not dispose of together with general office waste. Do not allow this material to drain into sewers/water supplies. Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations. Ensure collection and disposal with an appropriately licensed waste contractor.

SECTION 14: Transport information

DOT	
UN number	NA1993
UN proper shipping name	Combustible liquid n.o.s. (butyl cellosolve acetate) -Not regulated in quantities less than 119 gallons
Transport hazard class(es)	
Class	Combustible
Subsidiary risk	-
Packaging group	III

Special precautions for user Not available.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

ADR

Not regulated as dangerous goods.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I

Not listed.

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex II

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 1 as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 2 as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 3 as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(1) Candidate List as currently published by ECHA

Not listed.

Authorizations

Regulation (EC) No. 143/2011 Annex XIV Substances Subject to Authorization

Not listed.

Other EU regulations

Directive 96/82/EC (Seveso II) on the control of major-accident hazards involving dangerous substances

Not regulated.

Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Ethylacetate (CAS 141-78-6)

Ethylene Glycol, Monobutyl Ether Acetate (CAS 112-07-2)

Directive 94/33/EC on the protection of young people at work

Not regulated.

National regulations

Not available.

15.2. Chemical safety assessment

See attached SUMI or GEIS document, if applicable.

SECTION 16: Other information

References

Not available.

Information on evaluation method leading to the classification of mixture

Not available.

Revision information

Product and Company Identification: Synonyms
Composition/Information on Ingredients
Fire Fighting Measures: Fire & Explosion Properties
8. Exposure Controls / Personal Protection: OELs
Physical & Chemical Properties: Physical & Chemical Properties
14. Transport Information: Material Transportation Information
Regulatory Information: Safety Phrases
HazReg Data: Pacific Rim

Training information

Not available.

Disclaimer

This Safety Data Sheet document is provided without charge to customers of HP. Data is the most current known to HP at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and may not meet regulatory requirements in other countries.

Issue date

13-Aug-2016

Explanation of abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS	Chemical Abstracts Service
CERCLA	Comprehensive Environmental Response Compensation and Liability Act
CFR	Code of Federal Regulations
COC	Cleveland Open Cup
DOT	Department of Transportation
EPCRA	Emergency Planning and Community Right-to-Know Act (aka SARA)
IARC	International Agency for Research on Cancer
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
RCRA	Resource Conservation and Recovery Act
REC	Recommended
REL	Recommended Exposure Limit
SARA	Superfund Amendments and Reauthorization Act of 1986
STEL	Short-Term Exposure Limit
TCLP	Toxicity Characteristics Leaching Procedure
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
VOC	Volatile Organic Compounds

Manufacturer information

HP Inc.
1501 Page Mill Road
Palo Alto, CA 94304-1112 US
(Direct) +972 (9) 892-4628

Safe Use of Mixture Information (SUMI)

--

Solvent based inks: SB01 *English*

Disclaimer

This SUMI is a generic document for communicating conditions of safe use of a product in response to the REACH obligation. This document relates only to conditions of safe use and is not specific to a product. By adding this SUMI to a specific product SDS, the importer/formulator declares that the mixture can safely be used following the instructions below. Following occupational health legislation, the employer of workers remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product. Derived No Effect Levels (DNEL) and Predicted No Effect Concentration (PNEC) values of substances derived from the Chemical Safety Assessment (CSA) will be given in section 8 of the SDS.

The REACH registration number(s), where applicable, completes an extended product SDS.

Operational conditions

Maximum duration Up to 8 hours per day

Frequency of exposure < 240 days per year

Process conditions

- Covers use at ambient temperatures.
- Use of an integrated local exhaust ventilation is required in drying zone.
- Adequate ventilation should be provide for the areas where printing is performed. ANSI/ASHRAE Standard 62.1-2013 provides guidelines to ensure acceptable air quality in the workspace.
- Use explosion proof electrical equipment.
- Keep emissions below the occupational exposure limits of the ingredients specified in section 8 of the SDS.
- Avoid direct contact.
- Regular cleaning of equipment and work area.
- Supervision in place to check that Risk Management Measures are in place are being correctly used and Operational Conditions followed.

Risk management measures

Conditions and measures related to Personal Protection Equipment, hygiene and health evaluation

- Wear safety glasses with side shields (or goggles), if splashing is possible.
- Wear appropriate chemical resistant gloves: see section 8 of the SDS.
- Wear appropriate chemical resistant clothing.
- In case of inadequate ventilation wear respiratory protection.
- Eye wash fountain and emergency showers are recommended.
- Avoid breathing mist/vapours.
- Avoid contact with skin, eyes and clothing.
- Training of workers in relation to proper use and maintenance of all Personal protection equipment (PPE) must be ensured.



Good practice advice

- Use personal protective equipment as required.
- Wash hands before breaks and after work.
- Keep good industrial hygiene and safety practice.
- Use only with adequate ventilation.
- Do no eat, drink or smoke when using this product.
- Wash contaminated clothing before reuse.
- Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
- Store in a well-ventilated place.
- Keep container tightly closed.
- Store at room temperature.



Environmental measures

- Do not allow this material to drain into sewers/water supplies.
- Dispose of waste material according to Local, State, Federal and Provincial Environmental Regulations.
- Ensure collection and disposal with appropriately licenced waste contractor.

Use descriptors

IS-Use at industrial sites

PW-Widespread use by professional workers

SU7-Printing and reproduction media

PC18-Inks and Toners

PROC1-Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2-Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC3- Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition

PROC8a-Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC8b-Transfer of substance or mixture (charging and discharging) at dedicated facilities

ERC5-Use at industrial site leading to inclusion into/onto article

ERC8c-Widespread use leading to inclusion into/onto article (indoor)

Additional information on product composition

In section 2 of the SDS as well as on the label, the classification of the mixture is provided.

The classification of the mixture is based on the individual ingredients and their concentration within the mixture.

All ingredients contributing to the classification are stated in Section 3 of the SDS.

Relevant limit values of ingredients on which the exposure assessment is based, are listed in section 8 of the SDS.

The product may contain sensitizing ingredients that may cause allergic reaction to certain people.

Section 2 of the SDS states these ingredients where applicable.