

1. PRODUCT AND COMPANY IDENTIFICATION

Material name CH138A

Product use Inkjet printing.

Synonym(s) ColorSpan 0901147-004

Chemical family Acrylate/Polymer/Pigment Blend

CAS # Mixture

Company identification Hewlett-Packard Colombia

Carrera 7 No 99-21/53 Edificio Capita Torre 2 Bogota, Colombia

Telephone (57) 1 639 0000

Hewlett-Packard health effects line (Toll-free within the US) 1-800-457-4209

(Direct) 1-503-494-7199 HP Customer Care Line

(Toll-free within the US) 1-800-474-6836

(Direct) 1-208-323-2551

Email: hpcustomerinquiries@hp.com

2. HAZARDS IDENTIFICATION

Classification (EU) Xi, R36/38, R52/53

Acute health effects

Skin contact Avoid contact with skin.

Contact causes skin irritation.

Eye contact Irritating to eyes.

Inhalation Avoid breathing vapours or mists of this product. Inhalation of vapours or mists of the product

may be irritating to the respiratory system.

Ingestion Ingestion is not expected to be a primary route of exposure for this product under normal use

conditions. Harmful if swallowed.

Potential health effects

Routes of exposure Potential routes of exposure under normal use conditions are skin, eye contact and inhalation.

Physical hazards Not classified as a physical hazard.

Health hazards Irritating to eyes and skin.

Environmental hazards Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component/substance	CAS number	% by weight	EU classification
Acrylic Acid, Monoalkyl, Alkylaryl Ester	3076-04-8	10-30	Xi, N, R36/37/38, 51/53
Multifunctional Acrylate	84170-74-1	10-30	Xi, R36/38
N-vinylcaprolactam	2235-00-9	10-30	Xi, Xn, R22, 36
Substituted Phosphine Oxide	75980-60-8	1-5	Xn, R52/53, 62
2-Benzoyl-2-Dimethylamino-4-Morpholinobut	119313-12-1	0-1	N, R50/53

4. FIRST AID MEASURES

Inhalation Move person to fresh air immediately. If the affected person is not breathing, apply artificial

respiration. If breathing is difficult, give oxygen.

Get medical attention immediately.

Skin contact In case of contact, immediately remove contaminated clothing and flush skin with copious

amounts of water. Wash clothing separately before reuse.

If irritation persists get medical attention.

Material nameCH138ASDS ColombiaCreation date20-Nov-2008Version number1



Eye contact In case of eye contact, remove contact lens and rinse immediately with plenty of water, also

under the eyelids, for at least 15 minutes.

Get medical attention immediately.

Rinse mouth out with water. Give several glasses of water. If swallowed, do NOT induce Ingestion

vomiting. Never give anything by mouth to an unconscious person.

Do not use a solid water stream as it may scatter and spread fire.

Get medical attention immediately.

5. FIRE-FIGHTING MEASURES

> 95 °C (> 203 °F) closed cup; Flash point and method

Fire fighting Move containers from fire area if you can do it without risk.

Avoid runoff into storm sewers and ditches which lead to waterways. equipment/instructions

Dry chemical, foam, carbon dioxide. Do not use water. Use water to cool fire-exposed Suitable extinguishing media

containers and to protect personnel.

Extinguishing media which must not be used for safety

reasons

Unusual fire & explosion hazards

Hazardous combustion

products

Carbon monoxide and carbon dioxide.

Burning may produce thick, irritating smoke.

Specific methods Use a water spray to cool fully closed containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Avoid contact with skin Avoid inhalation of vapors or mists. Do not touch or walk through

spilled material.

Ensure adequate ventilation.

Use personal protective equipment to minimize exposure to skin and eye. In the case of

vapour formation use a respirator with an approved filter.

Environmental precautions

Do not flush into surface water or sanitary sewer system.

Methods for cleaning up Absorb with earth, sand or other non-combustible material and transfer to containers for later

disposal.

7. HANDLING AND STORAGE

Handling Avoid contact with skin, eyes and clothing. Avoid breathing vapours or mists of this product.

Use with adequate ventilation.

Wear personal protective equipment.

Keep containers tightly closed in a cool, well-ventilated place. Store away from strong Storage

oxidizers. Do not store near acids. Keep away from heat, sparks, and flame. Keep away from

direct sunlight.

Keep out of the reach of children.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Personal protective equipment

Respiratory protection Provide adequate ventilation. In case of insufficient ventilation wear suitable respiratory

Wear safety glasses; chemical goggles (if splashing is possible). Eye protection

Provide an emergency eye wash fountain and quick drench shower in the immediate work

Do not get this material in contact with skin. Avoid contact with skin, eyes and clothing. Hygiene measures

When using, do not eat, drink or smoke. Wash hands before breaks and immediately after

handling the product.

Launder contaminated clothing before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Not available. **Appearance**

Material name CH138A SDS Colombia Creation date 20-Nov-2008 Version number 1 2/5

Physical stateLiquid.FormLiquid.ColorBlack

Odor Characteristic.
Odour threshold Not available.
pH Not available.

Boiling point $> 100 \,^{\circ}\text{C} \, (> 212 \,^{\circ}\text{F}) \, (@ 760 \text{mmHg})$ **Flash point** $> 95 \,^{\circ}\text{C} \, (> 203 \,^{\circ}\text{F}) \, \text{closed cup};$

Flammability
Flammability limits in air,
upper, % by volume

Not available.

Flammability limits in air,

lower, % by volume

Not available.

Vapor pressureNot available.Relative densityNot available.Solubility (water)< 0.1 g/g</th>Partition coefficientNot available.

(n-octanol/water)

Viscosity 10 - 30 cP Vapor density > 1

Evaporation rate < 0.05 BuAc

Melting point Not available.

Freezing point Not available.

Auto-ignition temperature Not available.

Specific gravity 1.02 - 1.1

VOC < 95 g/l

10. STABILITY AND REACTIVITY

Stability Stable at normal conditions.

Conditions to avoid Heat, flames and sparks. Exposure to sunlight.

Materials to avoid Strong acids, alkalies and oxidizing agents.

Hazardous decomposition

products

Carbon monoxide and carbon dioxide.

Hazardous polymerization Hazardous polymerisation may occur.

11. TOXICOLOGICAL INFORMATION

Chronic toxicity Prolonged exposure causes local irritation of skin and mucous membranes, especially to the

eyes.

Teratogenicity None known.

Further information Complete toxicity data are not available for this specific formulation.

12. ECOLOGICAL INFORMATION

Aquatic toxicity Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

13. DISPOSAL CONSIDERATIONS

Disposal instructions Do not allow this material to drain into sewers/water supplies.

Dispose of in compliance with federal, state, and local regulations.

Material nameCH138ASDS ColombiaCreation date20-Nov-2008Version number1

14. TRANSPORT INFORMATION

ADR

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

General not regulated

15. REGULATORY INFORMATION

Labeling

Contains 2-Benzoyl-2-Dimethylamino-4-Morpholinobutyrophenone, Acrylic Acid, Monoalkyl, Alkylaryl

Ester, Multifunctional Acrylate, N-vinylcaprolactam, Substituted Phosphine Oxide

Symbol(s)



Irritant

R-phrase(s) R36/38 Irritating to eyes and skin.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

S-phrase(s) S24/25 Avoid contact with skin and eyes.

S61 Avoid release to the environment. Refer to special instructions/ Safety data sheets.

16. OTHER INFORMATION

Manufacturer information Hewlett-Packard

11311 K-Tel Drive

Minnetonka, MN 55343 US

Product Information 1-800-925-0563

List of relevant R phrases R22 Harmful if swallowed.

R36 Irritating to eyes.

R36/37/38 Irritating to eyes, respiratory system and skin.

R36/38 Irritating to eyes and skin.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R62 Possible risk of impaired fertility.

Disclaimer This Safety Data Sheet document is provided without charge to customers of Hewlett-Packard

Company. Data is the most current known to Hewlett-Packard Company at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in

Section 1 above and may not meet regulatory requirements in other countries.

Version number 1

Issue date 03-01-2009

Material name CH138A SDS Colombia



Explanation of abbreviations

ACGIH American Conference of Governmental Industrial Hygienists

CAS Chemical Abstracts Service

CERCLA Comprehensive Environmental Response Compensation and Liability Act

CFR Code of Federal Regulations

COC Cleveland Open Cup

DOT Department of Transportation

EPCRA Emergency Planning and Community Right-to-Know Act (aka SARA)

IARC International Agency for Research on Cancer

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

RCRA Resource Conservation and Recovery Act

REC Recommended

REL Recommended Exposure Limit

SARA Superfund Amendments and Reauthorization Act of 1986

STEL Short-term exposure limit

TCLP Toxicity Characteristics Leaching Procedure

TLV Threshold Limit Value

TSCA Toxic Substances Control Act
VOC Volatile Organic Compounds