



SAFETY DATA SHEET

1. Identification

Important information	*** This Safety Data Sheet is only authorised for use by HP for HP Original products. Any unauthorised use of this Safety Data Sheet is strictly prohibited and may result in legal action being taken by HP. ***	
Name of the substance or mixture (trade name)	G0Y96Series	
Synonyms	HP FB794 Black Scitex Ink Cartridge	
Major recommended uses for the substance or mixture	Inkjet printing	
Specific restrictions for use of the substance or mixture	Not available.	
Manufacturer/Importer/Distributor information		
Company identification	HP Colombia SAS Carrera 7 No 99-53 Torre B Pisos 7 Bogota, Colombia	
Telephone	(57) 1 639 0000	
HP Inc. health effects line		
(Toll-free within the US)	1-800-457-4209	
(Direct)	1-760-710-0048	
HP Inc. Customer Care Line		
(Toll-free within the US)	1-800-474-6836	
(Direct)	1-208-323-2551	
Email:	hpcustomer.inquiries@hp.com	

2. Hazards identification

Classification of the substance or mixture

Physical hazards	Not classified.	
Health hazards	Acute toxicity, oral	Not applicable
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Sensitization, skin	Category 1
	Reproductive toxicity	Category 1B
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity, repeated exposure	Category 1
Environmental hazards	Hazardous to the aquatic environment, long-term hazard	Category 2

GHS labeling elements, including precautionary statements

Hazard symbol(s)



Signal word

Danger

Hazard statement(s)

May damage fertility or the unborn child. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. May cause respiratory irritation. Causes damage to organs (liver, respiratory system) through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.

Precautionary statement(s)

Prevention Wear protective gloves/protective clothing/eye protection/face protection. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment.

Response IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical attention/advice. Call a poison center/doctor if you feel unwell. Take off contaminated clothing and wash before reuse. Collect spillage.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards which do not result in classification Potential routes of exposure to this product are skin and eye contact, ingestion, and inhalation.

Benzophenone is classified by the IARC as a Group 2B carcinogen (the substance is possibly carcinogenic to humans).

Supplemental information None.

3. Composition/information on ingredients

Mixture

Common chemical name or technical name	CAS number	Concentration or concentration range
2-phenoxyethyl acrylate	48145-04-6	<30
N-vinylcaprolactam	2235-00-9	<25
Carboxylic Acids, Esters	Proprietary	<15
Difunctional acrylic monomer	Proprietary	<10
Acrylate ester 5	Proprietary	<5
Alkyl Acrylate Ester	Proprietary	<5
Diphenyl (2,4,6-trimethylbenzoyl) phosphine oxide	Proprietary	<5
Black Pigment	Proprietary	<2.5
2,6-di-tert-butyl-.alpha.-dimethylamino-p-cresol	88-27-7	<1
Benzophenone	119-61-9	<1
Butylhydroxytoluene	128-37-0	<1
Aluminum, Tris(N-hydroxy-N-nitrosobenzenaminato-O,O')-	15305-07-4	<0.1

Composition comments Carbon black is present only in a bound form in this preparation.

4. First-aid measures

First-aid measures

Inhalation Move to fresh air. If symptoms persist, get medical attention.

Skin contact Wash affected areas thoroughly with mild soap and water. If irritation persists get medical attention.

Eye contact Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure) for at least 15 minutes or until particles are removed. If irritation persists get medical attention.

Ingestion If the material is swallowed, get immediate medical attention or advice -- Do not induce vomiting. Never give anything by mouth to an unconscious person.

Most important symptoms/effects, acute and delayed Not available.

Notes to physician Not available.

5. Fire-fighting measures

Means of fire extinguishing

Suitable extinguishing media Dry powder. Carbon dioxide (CO₂). Water may be ineffective.

Unsuitable extinguishing media Water may be ineffective. Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical Not available.

Special fire fighting procedures Avoid runoff into storm sewers and ditches which lead to waterways.

Protective measures taken by firefighting crews Not available.

6. Control measures for spills and leaks

Personal precautions, protective equipment and emergency procedures

To be taken by those who are not involved in rendering emergency services Wear appropriate personal protective equipment. Do not touch or walk through spilled material.

To be taken by those who are involved in rendering emergency services Not available.

Environmental precautions Do not let product enter drains. Do not flush into surface water or sanitary sewer system. See also section 13 Disposal considerations.

Methods and materials for containment and cleaning up Not available.

Other issues relating to spills and releases Soak up with inert absorbent material. Dispose of in compliance with federal, state, and local regulations.

7. Handling and storage

Precautions for safe handling Avoid contact with skin, eyes and clothing.

Conditions for safe storage, including any incompatibilities Keep away from excessive heat or cold. Do not store in direct sunlight. Do not handle or store near an open flame, heat or other sources of ignition. Opaque, high density polyethylene (HDPE) containers are recommended for shipping and storage.

8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Black Pigment	TWA	3 mg/m ³	Inhalable fraction.
Butylhydroxytoluene (CAS 128-37-0)	TWA	2 mg/m ³	Inhalable fraction and vapor.

Colombia. OELs. Resolution No. 02400: Norms Concerning Working Conditions, Health and Safety in the Workplace

Components	Type	Value	Form
Black Pigment	TWA	3 mg/m ³	Inhalable fraction.
Butylhydroxytoluene (CAS 128-37-0)	TWA	2 mg/m ³	Inhalable fraction and vapor.

Ecuador. OELs (INEN 2266:2013, 2013-01 2nd rev.: Transport, storage and handling of hazardous materials. Requirements. 1st ed., 1/29, 2013)

Components	Type	Value	Form
Black Pigment	TWA	3 mg/m ³	Inhalable fraction.
Butylhydroxytoluene (CAS 128-37-0)	TWA	2 mg/m ³	Inhalable fraction and vapor.

Paraguay. Decree No. 14.390/92 that approves the General Technical Regulation of Safety, Hygiene and Medicine in the Workplace

Components	Type	Value	Form
Black Pigment	TWA	3 mg/m ³	Inhalable fraction.

Paraguay. Decree No. 14.390/92 that approves the General Technical Regulation of Safety, Hygiene and Medicine in the Workplace

Components	Type	Value	Form
Butylhydroxytoluene (CAS 128-37-0)	TWA	2 mg/m3	Inhalable fraction and vapor.

Peru. OELs. Decreto Supremo 015-2005-SA (Reglamento sobre Valores Límites Permisibles para Agentes Químicos en el Ambiente de Trabajo)

Components	Type	Value
Black Pigment	TWA	3.5 mg/m3

Biological limit values	No biological exposure limits noted for the ingredient(s).
Exposure guidelines	Exposure limits have not been established for this product.
Appropriate engineering controls	Not available.
Personal protective measures	
Eyes and face protection	Wear safety glasses; chemical goggles (if splashing is possible). Eye wash fountain and emergency showers are recommended.
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves. Recommended gloves: Nitrile 6 mil minimum thickness.
Other	Wear appropriate chemical resistant clothing.
Respiratory protection	Provide adequate ventilation. In case of insufficient ventilation wear suitable respiratory equipment.
Thermal hazards	Not available.
Hygiene measures	Handle in accordance with good industrial hygiene and safety practice. Do not get this material in your eyes, on your skin, or on your clothing. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Launder contaminated clothing before reuse. Keep away from food and drink.

9. Physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Liquid.
Color	Black.
Odor	Characteristic.
Odor threshold	Not available.
pH	7.4 - 7.8 Metler Toledo pH Meter. Temperature 25°C
Melting point/freezing point	Not available.
Initial boiling point and boiling temperature range	Not available.
Flash point	> 199.9 °F (> 93.3 °C) Calculated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.

Decomposition temperature	Not available.
Viscosity	9.3 - 10.6 cP Brookfield Viscometer Temperature 50°C
Other physical and chemical parameters	
Chemical family	Acrylate/Polymer/Pigment Blend
VOC	0.2 g/L Calculated

10. Stability and reactivity

Reactivity	Not available.
Chemical stability	Stable under normal storage conditions.
Possibility of hazardous reactions	Hazardous polymerization can occur with decreased inhibitor content.
Conditions to avoid	Exposure to sunlight.
Incompatible materials	Incompatible with strong bases and oxidizing agents. alkaline metals
Hazardous decomposition products	Upon decomposition, this product may yield gaseous nitrogen oxides, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Inhalation may result in mild irritation to the respiratory system.
Skin contact	Causes skin irritation. May cause sensitization by skin contact.
Eye contact	Causes serious eye irritation.
Ingestion	Ingestion is not a likely route of exposure.

Symptoms Not available.

Acute toxicity May be harmful if swallowed.

Components	Species	Test Results
Black Pigment		
<u>Acute</u>		
Oral		
LD50	Rat	> 10000 mg/kg
N-vinylcaprolactam (CAS 2235-00-9)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	1700 mg/kg
Inhalation		
LC50	Rat	> 1.6 mg/l
Oral		
LD50	Rat	1114 mg/kg

Skin irritation and corrosion Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization	Based on available data, the classification criteria are not met.
Skin sensitization	May cause sensitization by skin contact.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Carbon black is classified as a carcinogen by the IARC (possibly carcinogenic to humans, Group 2B) and by the State of California under Proposition 65. In their evaluations of carbon black, both organizations indicate that exposure to carbon black, per se, does not occur when it remains bound within a product matrix, specifically, rubber, ink, or paint. Carbon black is present only in a bound form in this preparation.

ACGIH Carcinogens

Butylhydroxytoluene (CAS 128-37-0) A4 Not classifiable as a human carcinogen.

Colombia. OELs. Resolution No. 02400: Norms Concerning Working Conditions, Health and Safety in the Workplace

Black Pigment (CAS Proprietary) A3 Animal carcinogen.

Butylhydroxytoluene (CAS 128-37-0) A4 Not classifiable as a human carcinogen.

Ecuador. OELs (INEN 2266:2013, 2013-01 2nd rev.: Transport, storage and handling of hazardous materials. Requirements. 1st ed., 1/29, 2013)

Black Pigment (CAS Proprietary) Group A3 Confirmed animal carcinogen with unknown relevance to humans.
 Butylhydroxytoluene (CAS 128-37-0) Group A4 Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Benzophenone (CAS 119-61-9) 2B Possibly carcinogenic to humans.
 Butylhydroxytoluene (CAS 128-37-0) 3 Not classifiable as to carcinogenicity to humans.

Paraguay. Decree No. 14.390/92 that approves the General Technical Regulation of Safety, Hygiene and Medicine in the Workplace

Black Pigment (CAS Proprietary) A3 Confirmed animal carcinogen with unknown relevance to humans.
 Butylhydroxytoluene (CAS 128-37-0) A4 Not classifiable as a human carcinogen.

Toxic to reproduction Suspected of damaging the unborn child.
Specific target organ toxicity - single exposure May cause irritation to the respiratory system.
Specific target organ toxicity - repeated exposure Causes damage to organs (liver, respiratory system) through prolonged or repeated exposure.
Aspiration hazard Based on available data, the classification criteria are not met.
Other information Complete toxicity data are not available for this specific formulation

12. Ecological information

Aquatic toxicity Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. This product has not been tested for ecological effects.

Ecotoxicity

Components		Species	Test Results
2-phenoxyethyl acrylate (CAS 48145-04-6)			
<i>Acute</i>			
	EC10	Desmodesmus subcapitatus	0.71 mg/l, 72 h (DIN 38412 L9)
	EC50	Desmodesmus subcapitatus	4.44 mg/l, 72 h (DIN 38412 L9)
	LC50	Leuciscus idus	10 mg/l, 96 h (DIN 38 412)
	NOEC	Desmodesmus subcapitatus	0.71 mg/l, 72 h (DIN 38412 L9)
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Daphnia magna	1.21 mg/l, 48 h (Directive CE 79/831/CEE, Annex V, Part C)
Difunctional acrylic monomer			
<i>Acute</i>			
	EC10	Pseudokirchneriella subcapitata	2.3 mg/l, 72 h (OECD 201)
	EC50	Pseudokirchneriella subcapitata	11 mg/l, 72 h (OECD 201)
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Daphnia Magna	37 mg/l, 48 h (OECD 202)
Fish	LC50	Danio rerio	2.7 mg/l, 96 h (OECD 203)
Diphenyl (2,4,6-trimethylbenzoyl) phosphine oxide			
<i>Acute</i>			
	EC10	Pseudokirchneriella subcapitata	1.56 mg/l, 72 h (OECD 201)
	EC50	Pseudokirchneriella subcapitata	> 2.01 mg/l, 72 h (OECD 201)
	LC50	Cyprinus carpio	1.4 mg/l, 96 h (OECD 203)
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Daphnia magna	3.53 mg/l, 48 h (OECD 202)

Persistence and degradability Not available.

Bioaccumulative potential

**Partition coefficient
n-octanol / water (log Kow)** Not available.

**Bioconcentration factor
(BCF)**

Diphenyl (2,4,6-trimethylbenzoyl) phosphine oxide

72, (JIS K 0102-1986, 71 - Kanpogyo No .S, Yakuhatsu No .
615, 49-Kikyoku No . 392, MITI/MHW Chemical Substance
Control Law, Japan)

Mobility in soil Not available.

Other adverse effects Not available.

13. Considerations on final disposal

Recommended methods for final destination

Residual waste Not available.

Contaminated packaging Not available.

Local disposal regulations Do not dispose of together with general office waste.
Do not allow this material to drain into sewers/water supplies.
Dispose of waste material according to Local, State, Federal, and Provincial Environmental
Regulations.
Ensure collection and disposal with an appropriately licensed waste contractor.

14. Transport information

DOT

UN number Not available.

UN proper shipping name Not Regulated

Transport hazard class(es)

Class Not available.

Subsidiary risk -

Packing group Not available.

Environmental hazards

Marine pollutant No

Special precautions for user Not available.

DOT Supplemental Information DOT Classification only applies to shipments within the US and Puerto Rico.

IATA

UN number UN3082

UN proper shipping name Environmentally Hazardous Substance, Liquid, N.O.S. (Acrylates)

Transport hazard class(es)

Class 9

Subsidiary risk -

Packing group III

Environmental hazards Yes

Special precautions for user Not available.

IATA Supplemental Information When shipping ≤ 5L inner packaging, Special Provision A197 may apply.

IMDG

UN number UN3082

UN proper shipping name Environmentally Hazardous Substance, Liquid, N.O.S. (Acrylates), MARINE POLLUTANT

Transport hazard class(es)

Class 9

Subsidiary risk -

Packing group III

Transport hazard class(es)

Marine pollutant Yes

EmS F-A, S-F

Special precautions for user Not available.

IMDG Supplemental Information When shipping ≤ 5L containers, IMDG 2.10.2.7 may apply.

ADR

UN number UN3082

UN proper shipping name Environmentally Hazardous Substance, Liquid, N.O.S. (Acrylates)

Transport hazard class(es)


Class 9

Subsidiary risk -


Hazard No. (ADR) Not available.

Tunnel restriction code Not available.
Packing group III
Environmental hazards Yes
Special precautions for user Not available.
ADR Supplemental Information When shipping \leq 5L containers, ADR 375 may apply.

ADR; IATA; IMDG



Marine pollutant



Further information Transport in bulk according to Annex II of MARPOL73/78 and the IBC code: Not applicable.

15. Regulatory information

Federal regulations

Colombia. Controlled Substances (Resolution No. 009 of 1987 nationally regulating the transport & use of substances in subparag. f) of article 20 of Law 30 of 1986, as amended)

Not listed.

Venezuela. Chemical Precursors (Official Gazette No. 34.741, List I & II)

Not regulated.

International regulations

The components of this product are reported in the following inventories: USA, European Union, Canada, Japan, China, Australia, Korea.

Montreal Protocol

Not applicable.

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Basel Convention

Not applicable.

16. Other information

Significant information, yet not specifically related to the previous sections Not available.

Disclaimer

This Safety Data Sheet document is provided without charge to customers of HP. Data is the most current known to HP at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and may not meet regulatory requirements in other countries.

This safety data sheet is meant to convey information about HP inks (toners) provided in HP Original ink (toner) supplies. If our Safety Data Sheet has been provided to you with a refilled, remanufactured, compatible or other non-HP Original supply please be aware that the information contained herein was not meant to convey information about such products and there could be considerable differences from information in this document and the safety information for the product you purchased. Please contact the seller of the refilled, remanufactured or compatible supplies for applicable information, including information on personal protective equipment, exposure risks and safe handling guidance. HP does not accept refilled, remanufactured or compatible supplies in our recycling programs.

Explanation of abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS	Chemical Abstracts Service
CERCLA	Comprehensive Environmental Response Compensation and Liability Act
CFR	Code of Federal Regulations
COC	Cleveland Open Cup
DOT	Department of Transportation
EPCRA	Emergency Planning and Community Right-to-Know Act (aka SARA)
IARC	International Agency for Research on Cancer
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
RCRA	Resource Conservation and Recovery Act
REC	Recommended
REL	Recommended Exposure Limit
SARA	Superfund Amendments and Reauthorization Act of 1986
STEL	Short-Term Exposure Limit
TCLP	Toxicity Characteristics Leaching Procedure
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
VOC	Volatile Organic Compounds