

SAFETY DATA SHEET

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance/preparation CD403 Series

Use of the

Issue date

Inkjet printing

substance/preparation

29-Aug-2014 14-Mar-2017

Revision date Version #

02

Synonym(s)

HP DS100 Specialty Textile Light Cyan Scitex Ink

Company identification

PT. Hewlett-Packard Indonesia

9th Floor, Jl.Casablanca Kav.88 Prudential Centre

Jakarta, Indonesia 12870 Telephone +62-21 5799-1088

HP Inc. health effects line

(Toll-free within the US) 1-800-457-4209

(Direct) 1-760-710-0048 HP Inc. Customer Care Line

(Toll-free within the US) 1-800-474-6836

(Direct) 1-208-323-2551

Email: hpcustomer.inquiries@hp.com

2. HAZARDS IDENTIFICATION

GHS classification

Physical hazards Not classified.
Health hazards Not classified.
Environmental hazards Not classified.

GHS label elements

Signal word Warning



Hazard statement Combustible liquid. Harmful in contact with skin.

Precautionary statement

PreventionP210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Response P370 + P378 - In case of fire: Use sand, carbon dioxide (CO2) or dry chemical to extinguish.

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water. P312 - Call a POISON CENTER/doctor/physician if you feel unwell.

P363 - Wash contaminated clothing before reuse.

Storage P403 + P235 - Store in a well-ventilated place. Keep cool.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS #	Percent	
Ethylene Glycol, Monobutyl Ether Acetate	112-07-2	<100	
Ethylacetate	141-78-6	<2.5	

4. FIRST AID MEASURES

Inhalation Move to fresh air. If symptoms persist, get medical attention.

Material name: CD403 Series SDS INDONESIA

11291 Version #: 02 Revision date: 14-Mar-2017 Issue date: 29-Aug-2014

Skin contact In case of contact, immediately flush skin with plenty of water for at least 15 minutes while

> removing contaminated clothing and shoes. If irritation persists get medical attention. Remove and isolate contaminated clothing and shoes. Thoroughly wash (or discard) clothing and shoes before

Eye contact In case of contact, immediately flush eyes with large amounts of water, continuing to flush for 15

minutes. If irritation persists get medical attention.

Ingestion If swallowed, seek medical advice immediately and show this container or label.

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

> 145.0 °F (> 62.8 °C) Closed Cup Flash point Suitable extinguishing media CO2, water, dry chemical, or foam

Extinguishing media which must not be used for safety reasons

Water may be ineffective. Do not use a solid water stream as it may scatter and spread fire.

Unusual fire & explosion

hazards

None known.

Fire fighting

equipment/instructions

Firefighters should wear full protective clothing including self contained breathing apparatus.

Specific methods

Water mist may be used to cool closed containers.

Hazardous combustion

products

Carbon monoxide and carbon dioxide.

6. ACCIDENTAL RELEASE MEASURES

Methods for cleaning up Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous

earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

7. HANDLING AND STORAGE

Handling Avoid contact with skin, eyes and clothing. Avoid breathing vapors or mists of this product.

> Use with adequate ventilation. Wear personal protective equipment.

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks Storage

and flame.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Туре	Value	
Ethylacetate (CAS 141-78-6)	TWA	400 ppm	
Ethylene Glycol, Monobutyl Ether Acetate (CAS 112-07-2)	TWA	20 ppm	

Exposure limits

Indonesia. OELs (Minister of Manpower and Transmigration Regulation No. Per.13/MEN/X/2011 concerning

Threshold Limit Values, Annex II)

Components **Value** Type Ethylacetate (CAS 141-78-6) TWA 400 ppm

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures

Additional exposure data None established.

Engineering measures to

Use in a well ventilated area.

reduce exposure

Ensure adequate ventilation, especially in confined areas. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Additional area ventilation or local exhaust may be required to maintain air concentrations below recommended exposure limits.

Personal protective equipment

Hand protection Recommended gloves: Nitrile 6 mil minimum thickness.

Eye protection Avoid contact with eyes

Wear safety glasses; chemical goggles (if splashing is possible).

Use personal protective equipment to minimize exposure to skin and eye. Skin and body protection

Material name: CD403 Series SDS INDONESIA

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state Not available. Color Light Cyan Odor Not available. Not applicable. рH Melting point/Freezing point Not determined.

Boiling point, initial boiling point, and boiling range

Not determined.

Flash point

> 145.0 °F (> 62.8 °C) Closed Cup

Auto-ignition temperature Not available. Flammability limit - lower Not available.

(%)

Flammability limit - upper

(%)

Not available.

Vapor pressure Not determined. **Evaporation rate** Not determined. Specific gravity 0.94 @ 20 Degrees C

Solubility(ies)

Solubility (water) Not available. **Partition coefficient** Not available.

(n-octanol/water)

Decomposition temperature

Not available.

Other data

Relative density 0.94 g/cm3 @ 20 Degrees C

VOC (Weight %) < 850 g/L

10. STABILITY AND REACTIVITY

Conditions to avoid Not available. **Hazardous decomposition** None known.

products **Stability**

Stable at normal conditions

Materials to avoid strong oxidizing agents Strong acids and strong alkalis. oxidizing agents

Hazardous polymerization Will not occur.

11. TOXICOLOGICAL INFORMATION

Acute toxicity Harmful in contact with skin.

Skin corrosion/irritation Based on available data, the classification criteria are not met. Serious eye damage/eye Based on available data, the classification criteria are not met.

irritation

Respiratory or skin sensitization

Skin sensitization Based on available data, the classification criteria are not met. **Respiratory sensitization** Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met. Germ cell mutagenicity Based on available data, the classification criteria are not met. Toxic to reproduction Based on available data, the classification criteria are not met. Specific target organ toxicity Based on available data, the classification criteria are not met.

single exposure

Specific target organ toxicity

- repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met. **Further information** Complete toxicity data are not available for this specific formulation

Material name: CD403 Series SDS INDONESIA

11291 Version #: 02 Revision date: 14-Mar-2017 Issue date: 29-Aug-2014

Components	Species	Test Results
Ethylacetate (CAS 141-78-6	5)	
Acute		
Inhalation		
LC50	Rat	16000 ppm, 6 Hours
LD50	Mouse	1500 ppm, 4 Hours
	Rabbit	2500 ppm, 4 Hours
	Rat	4000 ppm, 4 Hours
Oral		
LD50	Mouse	0.44 g/kg
	Rabbit	4.9 g/kg
	Rat	11.3 ml/kg
		5.6 g/kg
Other		
LD50	Cat	3 g/kg
	Guinea pig	3 g/kg
Ethylene Glycol, Monobutyl	Ether Acetate (CAS 112-07-2)	
Acute		
Dermal		
LD50	Rabbit	1500 mg/kg
Inhalation		
LC50	Cat	> 460 ppm, 6 Hours
	Guinea pig	> 460 ppm, 6 Hours
	Mouse	> 460 ppm, 6 Hours
	Rabbit	> 460 ppm, 6 Hours
	Rat	> 460 ppm, 6 Hours
Oral		
LD100	Rabbit	987 mg/kg
LD50	Mouse	2820 mg/kg
	Rat	1600 mg/kg
		7.46 ml/kg
Other		
LD50	Mouse	754 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity This product has not been tested for ecological effects.

Environmental effectsNot available. **Persistence / degradability**Not available.

Bioaccumulation

Bioaccumulative potential

Octanol/water partition coefficient log Kow

Ethylacetate 0.73

Mobility Not available.

Ecotoxicological data

Components Species Test Results

Ethylacetate (CAS 141-78-6)

Aquatic

Fish LC50 Indian catfish (Heteropneustes fossilis) 200.32 - 225.42 mg/l, 96 hours

Material name: CD403 Series SDS INDONESIA

11291 Version #: 02 Revision date: 14-Mar-2017 Issue date: 29-Aug-2014

13. DISPOSAL CONSIDERATIONS

Disposal instructions Do not dispose of together with general office waste.

Do not allow this material to drain into sewers/water supplies.

Dispose of waste material according to Local, State, Federal, and Provincial Environmental

Ensure collection and disposal with an appropriately licensed waste contractor.

14. TRANSPORT INFORMATION

DOT

UN number NA1993

UN proper shipping name Combustible liquid n.o.s. (butyl cellosolve acetate) -Not regulated in quantities less than 119

gallons

Transport hazard class(es)

Combustible Class

Subsidiary risk Packaging group III

Special precautions for Not available.

user

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

ADR

Not regulated as dangerous goods.

15. REGULATORY INFORMATION

16. OTHER INFORMATION

Disclaimer This Safety Data Sheet document is provided without charge to customers of HP. Data is the most

current known to HP at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and may not meet regulatory requirements in other

countries.

Prepared by **HP Chemical Compliance & Toxicology Department**

Issue date 29-Aug-2014 **Revision date** 14-Mar-2017

Version #

This data sheet contains changes from the previous version in section(s):

This document has undergone significant changes and should be reviewed in its entirety.

Manufacturer information

HP Inc. 1501 Page Mill Road

Palo Alto, CA 94304-1112 US (Direct) +972 (9) 892-4628

Material name: CD403 Series

11291 Version #: 02 Revision date: 14-Mar-2017 Issue date: 29-Aug-2014

5/6

Explanation of abbreviations

ACGIH American Conference of Governmental Industrial Hygienists

CAS Chemical Abstracts Service

CERCLA Comprehensive Environmental Response Compensation and Liability Act

CFR Code of Federal Regulations

COC Cleveland Open Cup

DOT Department of Transportation

EPCRA Emergency Planning and Community Right-to-Know Act (aka SARA)

IARC International Agency for Research on Cancer

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

RCRA Resource Conservation and Recovery Act

REC Recommended

REL Recommended Exposure Limit

SARA Superfund Amendments and Reauthorization Act of 1986

STEL Short-Term Exposure Limit

TCLP Toxicity Characteristics Leaching Procedure

TLV Threshold Limit Value

TSCA Toxic Substances Control Act
VOC Volatile Organic Compounds

Material name: CD403 Series SDS INDONESIA