



SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Important information *** This Safety Data Sheet is only authorised for use by HP for HP Original products. Any unauthorised use of this Safety Data Sheet is strictly prohibited and may result in legal action being taken by HP. ***

1.1. Product identifier

Trade name or designation of the mixture CN987 Series

Registration number -

UFI

Austria: FUXD-V6J2-Y30F-1YGN
Belgium: FUXD-V6J2-Y30F-1YGN
Bulgaria: FUXD-V6J2-Y30F-1YGN
Cyprus: FUXD-V6J2-Y30F-1YGN
Czech Republic: FUXD-V6J2-Y30F-1YGN
Denmark: FUXD-V6J2-Y30F-1YGN
Estonia: FUXD-V6J2-Y30F-1YGN
Finland: FUXD-V6J2-Y30F-1YGN
France: FUXD-V6J2-Y30F-1YGN
Germany: FUXD-V6J2-Y30F-1YGN
Greece: FUXD-V6J2-Y30F-1YGN
Hungary: FUXD-V6J2-Y30F-1YGN
Iceland: FUXD-V6J2-Y30F-1YGN
Ireland: FUXD-V6J2-Y30F-1YGN
Italy: FUXD-V6J2-Y30F-1YGN
Latvia: FUXD-V6J2-Y30F-1YGN
Liechtenstein: FUXD-V6J2-Y30F-1YGN
Lithuania: FUXD-V6J2-Y30F-1YGN
Luxembourg: FUXD-V6J2-Y30F-1YGN
Malta: FUXD-V6J2-Y30F-1YGN
Netherlands: FUXD-V6J2-Y30F-1YGN
Norway: FUXD-V6J2-Y30F-1YGN
Poland: FUXD-V6J2-Y30F-1YGN
Portugal: FUXD-V6J2-Y30F-1YGN
Romania: FUXD-V6J2-Y30F-1YGN
Slovakia: FUXD-V6J2-Y30F-1YGN
Slovenia: FUXD-V6J2-Y30F-1YGN
Spain: FUXD-V6J2-Y30F-1YGN
Sweden: FUXD-V6J2-Y30F-1YGN

Synonyms HP Scitex TJ100 Flash Magenta Ink

Issue date 08-Aug-2016

Version number 10

Revision date 06-Apr-2021

Supersedes date 06-Apr-2021

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Inkjet printing.

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

HP Deutschland GmbH
Schickardstrasse 32
71034 Böblingen
Germany

Telephone

HP Inc. health effect line

(Toll-free within US) 1-800-457-4209

(Direct) 1-760-710-0048

HP Inc. Customer Care Line

(Toll-free within the US) 1-800-474-6836

(Direct) 1-208-323-2551

Email: hpcustomer.inquiries@hp.com

1.4 Emergency telephone number 1-760-710-0048

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Acute toxicity, dermal	Category 4	H312 - Harmful in contact with skin.
Acute toxicity, inhalation	Category 4	H332 - Harmful if inhaled.
Serious eye damage/eye irritation	Category 1	H318 - Causes serious eye damage.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: 2-Butoxyethyl acetate, Butyl Methacrylate, Cyclohexanone

Hazard pictograms



Signal word Danger

Hazard statements

H332	Harmful if inhaled.
H318	Causes serious eye damage.
H312	Harmful in contact with skin.

Precautionary statements

Prevention

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P271	Use only outdoors or in a well-ventilated area.

Response

P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312	Call a poison center/doctor if you feel unwell.
P362 + P364	Take off contaminated clothing and wash it before reuse.

Storage Not available.

Disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

Supplemental label information None.

2.3. Other hazards Potential routes of exposure to this product are skin and eye contact, ingestion, and inhalation.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Material name: CN987 Series

11128 Version #: 10 Revision date: 06-Apr-2021 Issue date: 08-Aug-2016

SDS LIECHTENSTEIN

2 / 20

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
2-Butoxyethyl acetate	<80	112-07-2 203-933-3	01-2119475112-47-XXXX	607-038-00-2	#
Classification:	Acute Tox. 4;H302, Acute Tox. 4;H312, Acute Tox. 4;H332				
2-methoxy-1-methylethylacetate	<20	108-65-6 203-603-9	01-2119475791-29-XXXX	607-195-00-7	#
Classification:	Flam. Liq. 3;H226, STOT SE 3;H336				
Cyclohexanone	<5	108-94-1 203-631-1	01-2119453616-35-XXXX	606-010-00-7	#
Classification:	Flam. Liq. 3;H226, Acute Tox. 4;H302, Acute Tox. 4;H312, Skin Irrit. 2;H315, Eye Dam. 1;H318, Acute Tox. 4;H332				
Butyl Methacrylate	<0.1	97-88-1 202-615-1	01-2119486394-28-XXXX	607-033-00-5	
Classification:	Flam. Liq. 3;H226, Skin Irrit. 2;H315, Skin Sens. 1;H317, Eye Irrit. 2;H319, STOT SE 3;H335				

SECTION 4: First aid measures

General information Not available.

4.1. Description of first aid measures

Inhalation	Move person to fresh air immediately. If symptoms persist, get immediate medical attention.
Skin contact	In case of contact, immediately remove contaminated clothing and flush skin with copious amounts of water. Wash clothing separately before reuse. Get medical attention, if needed.
Eye contact	In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention immediately.
Ingestion	Rinse mouth out with water. If the material is swallowed, get immediate medical attention or advice -- Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.

4.2. Most important symptoms and effects, both acute and delayed Not available.

4.3. Indication of any immediate medical attention and special treatment needed Not available.

SECTION 5: Firefighting measures

General fire hazards Not available.

5.1. Extinguishing media

Suitable extinguishing media	Suitable extinguishing media: sand, carbon dioxide (CO ₂), and dry chemical.
Unsuitable extinguishing media	Not available.

5.2. Special hazards arising from the substance or mixture Not available.

5.3. Advice for firefighters

Special protective equipment for firefighters	Firefighters should wear full protective clothing including self contained breathing apparatus. Avoid runoff into storm sewers and ditches which lead to waterways.
Special fire fighting procedures	Move containers from fire area if you can do it without risk.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	Avoid contact with skin. Avoid inhalation of vapors or mists. Do not touch or walk through spilled material. Ensure adequate ventilation. Remove all sources of ignition. Use personal protective equipment to minimize exposure to skin and eye. In the case of vapor formation use a respirator with an approved filter.
For emergency responders	Not available.

6.2. Environmental precautions Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up Not available.

6.4. Reference to other sections Not available.

SECTION 7: Handling and storage

7.1. Precautions for safe handling Avoid contact with skin, eyes and clothing. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Wear personal protective equipment.

7.2. Conditions for safe storage, including any incompatibilities Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame.

7.3. Specific end use(s) Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Austria. MAK List, OEL Ordinance (GwV), BGI. II, no. 184/2001

Components	Type	Value
2-Butoxyethyl acetate (CAS 112-07-2)	MAK	133 mg/m ³
		20 ppm
	STEL	270 mg/m ³
2-methoxy-1-methylethylacetate (CAS 108-65-6)	Ceiling	40 ppm
		550 mg/m ³
	MAK	100 ppm
Cyclohexanone (CAS 108-94-1)	MAK	275 mg/m ³
		50 ppm
	STEL	20 mg/m ³
		5 ppm
		80 mg/m ³
		20 ppm

Belgium. Exposure Limit Values

Components	Type	Value
2-Butoxyethyl acetate (CAS 112-07-2)	STEL	333 mg/m ³
		50 ppm
	TWA	133 mg/m ³
2-methoxy-1-methylethylacetate (CAS 108-65-6)		20 ppm
	STEL	550 mg/m ³
	TWA	100 ppm
Cyclohexanone (CAS 108-94-1)		275 mg/m ³
		50 ppm
	STEL	81.6 mg/m ³
		20 ppm
	TWA	40.8 mg/m ³
		10 ppm

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components	Type	Value
2-Butoxyethyl acetate (CAS 112-07-2)	STEL	333 mg/m ³
		50 ppm
	TWA	133 mg/m ³

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components	Type	Value
2-methoxy-1-methylethylacetate (CAS 108-65-6)	STEL	20 ppm 550 mg/m ³
	TWA	100 ppm 275 mg/m ³
Cyclohexanone (CAS 108-94-1)	STEL	50 ppm 81.6 mg/m ³
	TWA	20 ppm 40.8 mg/m ³ 10 ppm

Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09

Components	Type	Value
2-Butoxyethyl acetate (CAS 112-07-2)	MAC	133 mg/m ³
	STEL	20 ppm 333 mg/m ³
2-methoxy-1-methylethylacetate (CAS 108-65-6)	MAC	50 ppm 275 mg/m ³
	STEL	550 mg/m ³ 100 ppm
Cyclohexanone (CAS 108-94-1)	MAC	40.8 mg/m ³
	STEL	10 ppm 81.6 mg/m ³ 20 ppm

Czech Republic. OELs. Government Decree 361

Components	Type	Value
2-Butoxyethyl acetate (CAS 112-07-2)	Ceiling	300 mg/m ³
	TWA	130 mg/m ³
2-methoxy-1-methylethylacetate (CAS 108-65-6)	Ceiling	550 mg/m ³
	TWA	270 mg/m ³
Cyclohexanone (CAS 108-94-1)	Ceiling	80 mg/m ³
	TWA	40 mg/m ³

Denmark. Exposure Limit Values

Components	Type	Value
2-Butoxyethyl acetate (CAS 112-07-2)	TLV	134 mg/m ³
		20 ppm
2-methoxy-1-methylethylacetate (CAS 108-65-6)	TLV	275 mg/m ³
		50 ppm
Butyl Methacrylate (CAS 97-88-1)	TLV	145 mg/m ³
		25 ppm
Cyclohexanone (CAS 108-94-1)	TLV	41 mg/m ³
		10 ppm

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001)

Components	Type	Value
2-Butoxyethyl acetate (CAS 112-07-2)	STEL	333 mg/m ³
		50 ppm
	TWA	133 mg/m ³
		20 ppm
2-methoxy-1-methylethylacetate (CAS 108-65-6)	STEL	550 mg/m ³
		100 ppm
	TWA	275 mg/m ³
		50 ppm
Butyl Methacrylate (CAS 97-88-1)	STEL	450 mg/m ³
		75 ppm
	TWA	300 mg/m ³
		50 ppm
Cyclohexanone (CAS 108-94-1)	STEL	81.6 mg/m ³
		20 ppm
	TWA	40.8 mg/m ³
		10 ppm

Finland. Workplace Exposure Limits

Components	Type	Value
2-Butoxyethyl acetate (CAS 112-07-2)	STEL	330 mg/m ³
		50 ppm
	TWA	130 mg/m ³
		20 ppm
2-methoxy-1-methylethylacetate (CAS 108-65-6)	STEL	550 mg/m ³
		100 ppm
	TWA	270 mg/m ³
		50 ppm
Cyclohexanone (CAS 108-94-1)	STEL	82 mg/m ³
		20 ppm
	TWA	41 mg/m ³
		10 ppm

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Components	Type	Value
2-Butoxyethyl acetate (CAS 112-07-2)	VLE	333 mg/m ³
	Regulatory status: Regulatory binding (VRC)	50 ppm
	Regulatory status: Regulatory binding (VRC)	66.5 mg/m ³
	VME	
	Regulatory status: Regulatory binding (VRC)	10 ppm
	Regulatory status: Regulatory binding (VRC)	
2-methoxy-1-methylethylacetate (CAS 108-65-6)	VLE	550 mg/m ³
		110 ppm
	VME	275 mg/m ³

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Components	Type	Value
Cyclohexanone (CAS 108-94-1)	VLE	50 ppm 81.6 mg/m3
	VME	20 ppm 40.8 mg/m3 10 ppm

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Type	Value	Form
2-Butoxyethyl acetate (CAS 112-07-2)	TWA	66 mg/m3	Vapor and aerosol.
2-methoxy-1-methylethylacetate (CAS 108-65-6)	TWA	10 ppm	Vapor and aerosol.
		270 mg/m3 50 ppm	

Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace

Components	Type	Value	Form
2-Butoxyethyl acetate (CAS 112-07-2)	AGW	130 mg/m3	Vapor and aerosol.
2-methoxy-1-methylethylacetate (CAS 108-65-6)	AGW	20 ppm	Vapor and aerosol.
		270 mg/m3 50 ppm	
Cyclohexanone (CAS 108-94-1)	AGW	80 mg/m3 20 ppm	

Greece. OELs (Decree No. 90/1999, as amended)

Components	Type	Value
2-Butoxyethyl acetate (CAS 112-07-2)	STEL	270 mg/m3
	TWA	40 ppm 135 mg/m3 20 ppm
2-methoxy-1-methylethylacetate (CAS 108-65-6)	STEL	550 mg/m3
	TWA	100 ppm 275 mg/m3 50 ppm
Cyclohexanone (CAS 108-94-1)	STEL	400 mg/m3
	TWA	100 ppm 200 mg/m3 50 ppm

Hungary. OELs. Joint Decree on Chemical Safety of Workplaces

Components	Type	Value
2-Butoxyethyl acetate (CAS 112-07-2)	STEL	333 mg/m3
	TWA	133 mg/m3
2-methoxy-1-methylethylacetate (CAS 108-65-6)	STEL	550 mg/m3
	TWA	275 mg/m3
Cyclohexanone (CAS 108-94-1)	STEL	81.6 mg/m3
	TWA	40.8 mg/m3

Iceland. OELs. Regulation 154/1999 on occupational exposure limits

Components	Type	Value
2-Butoxyethyl acetate (CAS 112-07-2)	STEL	333 mg/m3
		50 ppm
	TWA	133 mg/m3 20 ppm
2-methoxy-1-methylethylacetate (CAS 108-65-6)	STEL	550 mg/m3
		100 ppm
	TWA	275 mg/m3 50 ppm
Butyl Methacrylate (CAS 97-88-1)	TWA	145 mg/m3
		25 ppm
Cyclohexanone (CAS 108-94-1)	STEL	81.6 mg/m3
		20 ppm
	TWA	40 mg/m3 10 ppm

Ireland. Occupational Exposure Limits

Components	Type	Value
2-Butoxyethyl acetate (CAS 112-07-2)	STEL	333 mg/m3
		50 ppm
	TWA	133 mg/m3 20 ppm
2-methoxy-1-methylethylacetate (CAS 108-65-6)	STEL	550 mg/m3
		100 ppm
	TWA	275 mg/m3 50 ppm
Cyclohexanone (CAS 108-94-1)	STEL	81.6 mg/m3
		20 ppm
	TWA	40.8 mg/m3 10 ppm

Italy. Occupational Exposure Limits

Components	Type	Value
2-Butoxyethyl acetate (CAS 112-07-2)	STEL	333 mg/m3
		50 ppm
	TWA	133 mg/m3 20 ppm
2-methoxy-1-methylethylacetate (CAS 108-65-6)	STEL	550 mg/m3
		100 ppm
	TWA	275 mg/m3 50 ppm
Cyclohexanone (CAS 108-94-1)	STEL	81.6 mg/m3
		20 ppm
	TWA	40.8 mg/m3 10 ppm

Latvia. OELs. Occupational exposure limit values of chemical substances in work environment

Components	Type	Value
2-Butoxyethyl acetate (CAS 112-07-2)	STEL	333 mg/m ³
		50 ppm
	TWA	133 mg/m ³ 20 ppm
2-methoxy-1-methylethylacetate (CAS 108-65-6)	STEL	550 mg/m ³
		100 ppm
	TWA	275 mg/m ³ 50 ppm
Butyl Methacrylate (CAS 97-88-1)	TWA	30 mg/m ³
Cyclohexanone (CAS 108-94-1)	STEL	81.6 mg/m ³
		20 ppm
	TWA	40.8 mg/m ³ 10 ppm

Lithuania. OELs. Limit Values for Chemical Substances, General Requirements

Components	Type	Value
2-Butoxyethyl acetate (CAS 112-07-2)	STEL	140 mg/m ³
		20 ppm
	TWA	70 mg/m ³ 10 ppm
2-methoxy-1-methylethylacetate (CAS 108-65-6)	STEL	400 mg/m ³
		75 ppm
	TWA	250 mg/m ³ 50 ppm
Butyl Methacrylate (CAS 97-88-1)	STEL	450 mg/m ³
		75 ppm
	TWA	300 mg/m ³ 50 ppm
Cyclohexanone (CAS 108-94-1)	STEL	81.6 mg/m ³
		20 ppm
	TWA	40.8 mg/m ³ 10 ppm

Luxembourg. Binding Occupational exposure limit values (Annex I), Memorial A

Components	Type	Value
2-Butoxyethyl acetate (CAS 112-07-2)	STEL	333 mg/m ³
		50 ppm
	TWA	133 mg/m ³ 20 ppm
2-methoxy-1-methylethylacetate (CAS 108-65-6)	STEL	550 mg/m ³
		100 ppm
	TWA	275 mg/m ³ 50 ppm
Cyclohexanone (CAS 108-94-1)	STEL	81.6 mg/m ³

Luxembourg. Binding Occupational exposure limit values (Annex I), Memorial A

Components	Type	Value
		20 ppm
	TWA	40.8 mg/m ³
		10 ppm

Malta. OELs. Occupational Exposure Limit Values (L.N. 227. of Occupational Health and Safety Authority Act (CAP. 424), Schedules I and V)

Components	Type	Value
2-Butoxyethyl acetate (CAS 112-07-2)	STEL	333 mg/m ³
		50 ppm
	TWA	133 mg/m ³
		20 ppm
2-methoxy-1-methylethylacetate (CAS 108-65-6)	STEL	550 mg/m ³
		100 ppm
	TWA	275 mg/m ³
		50 ppm
Cyclohexanone (CAS 108-94-1)	STEL	81.6 mg/m ³
		20 ppm
	TWA	40.8 mg/m ³
		10 ppm

Netherlands. OELs (binding)

Components	Type	Value
2-Butoxyethyl acetate (CAS 112-07-2)	STEL	333 mg/m ³
	TWA	135 mg/m ³
2-methoxy-1-methylethylacetate (CAS 108-65-6)	TWA	550 mg/m ³
Cyclohexanone (CAS 108-94-1)	STEL	50 mg/m ³

Norway. Administrative Norms for Contaminants in the Workplace

Components	Type	Value
2-Butoxyethyl acetate (CAS 112-07-2)	TLV	65 mg/m ³
		10 ppm
2-methoxy-1-methylethylacetate (CAS 108-65-6)	TLV	270 mg/m ³
		50 ppm
Butyl Methacrylate (CAS 97-88-1)	TLV	59 mg/m ³
		10 ppm
Cyclohexanone (CAS 108-94-1)	STEL	80 mg/m ³
		20 ppm
	TLV	40 mg/m ³
		10 ppm

Poland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817

Components	Type	Value
2-Butoxyethyl acetate (CAS 112-07-2)	STEL	300 mg/m ³
	TWA	100 mg/m ³
2-methoxy-1-methylethylacetate (CAS 108-65-6)	STEL	520 mg/m ³

Poland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817

Components	Type	Value
	TWA	260 mg/m ³
Butyl Methacrylate (CAS 97-88-1)	STEL	300 mg/m ³
	TWA	100 mg/m ³
Cyclohexanone (CAS 108-94-1)	STEL	80 mg/m ³
	TWA	40 mg/m ³

Portugal. OELs. Decree-Law n. 290/2001 (Journal of the Republic - 1 Series A, n.266)

Components	Type	Value
2-Butoxyethyl acetate (CAS 112-07-2)	STEL	333 mg/m ³
		50 ppm
	TWA	133 mg/m ³
		20 ppm
2-methoxy-1-methylethylacetate (CAS 108-65-6)	STEL	550 mg/m ³
		100 ppm
	TWA	275 mg/m ³
		50 ppm
Cyclohexanone (CAS 108-94-1)	STEL	81.6 mg/m ³
		20 ppm
	TWA	40.8 mg/m ³
		10 ppm

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)

Components	Type	Value
2-Butoxyethyl acetate (CAS 112-07-2)	TWA	20 ppm
Cyclohexanone (CAS 108-94-1)	STEL	50 ppm
	TWA	20 ppm

Romania. OELs. Protection of workers from exposure to chemical agents at the workplace

Components	Type	Value
2-Butoxyethyl acetate (CAS 112-07-2)	STEL	333 mg/m ³
		50 ppm
	TWA	133 mg/m ³
		20 ppm
2-methoxy-1-methylethylacetate (CAS 108-65-6)	STEL	550 mg/m ³
		100 ppm
	TWA	275 mg/m ³
		50 ppm
Butyl Methacrylate (CAS 97-88-1)	STEL	250 mg/m ³
		43 ppm
	TWA	150 mg/m ³
		25 ppm
Cyclohexanone (CAS 108-94-1)	STEL	81.6 mg/m ³
		20 ppm
	TWA	40.8 mg/m ³
		10 ppm

Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents

Components	Type	Value
2-Butoxyethyl acetate (CAS 112-07-2)	STEL	333 mg/m ³
		50 ppm
	TWA	133 mg/m ³ 20 ppm
2-methoxy-1-methylethylacetate (CAS 108-65-6)	STEL	550 mg/m ³
		100 ppm
	TWA	275 mg/m ³ 50 ppm
Cyclohexanone (CAS 108-94-1)	STEL	82 mg/m ³
		20 ppm
	TWA	41 mg/m ³ 10 ppm

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Components	Type	Value
2-Butoxyethyl acetate (CAS 112-07-2)	TWA	133 mg/m ³
		20 ppm
2-methoxy-1-methylethylacetate (CAS 108-65-6)	TWA	275 mg/m ³
		50 ppm
Cyclohexanone (CAS 108-94-1)	TWA	40.8 mg/m ³
		10 ppm

Spain. Occupational Exposure Limits

Components	Type	Value
2-Butoxyethyl acetate (CAS 112-07-2)	STEL	333 mg/m ³
		50 ppm
	TWA	133 mg/m ³ 20 ppm
2-methoxy-1-methylethylacetate (CAS 108-65-6)	STEL	550 mg/m ³
		100 ppm
	TWA	275 mg/m ³ 50 ppm
Cyclohexanone (CAS 108-94-1)	STEL	82 mg/m ³
		20 ppm
	TWA	41 mg/m ³ 10 ppm

Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)

Components	Type	Value
2-Butoxyethyl acetate (CAS 112-07-2)	Ceiling	333 mg/m ³
		50 ppm
	TWA	70 mg/m ³ 10 ppm
2-methoxy-1-methylethylacetate (CAS 108-65-6)	Ceiling	550 mg/m ³

Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)

Components	Type	Value
Butyl Methacrylate (CAS 97-88-1)	TWA	100 ppm 275 mg/m3
	STEL	50 ppm 450 mg/m3
	TWA	75 ppm 300 mg/m3
Cyclohexanone (CAS 108-94-1)	Ceiling	50 ppm 81 mg/m3
	TWA	20 ppm 41 mg/m3
		10 ppm

Switzerland. SUVA Grenzwerte am Arbeitsplatz

Components	Type	Value
2-Butoxyethyl acetate (CAS 112-07-2)	STEL	132 mg/m3
	TWA	20 ppm 66 mg/m3 10 ppm
2-methoxy-1-methylethylacetate (CAS 108-65-6)	STEL	275 mg/m3
	TWA	50 ppm 275 mg/m3 50 ppm
Cyclohexanone (CAS 108-94-1)	STEL	200 mg/m3
	TWA	50 ppm 100 mg/m3 25 ppm

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value
2-Butoxyethyl acetate (CAS 112-07-2)	STEL	332 mg/m3
	TWA	50 ppm 133 mg/m3
2-methoxy-1-methylethylacetate (CAS 108-65-6)	STEL	20 ppm 548 mg/m3
	TWA	100 ppm 274 mg/m3 50 ppm
Cyclohexanone (CAS 108-94-1)	STEL	82 mg/m3
	TWA	20 ppm 41 mg/m3 10 ppm

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU

Components	Type	Value
2-Butoxyethyl acetate (CAS 112-07-2)	STEL	333 mg/m3
		50 ppm

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU

Components	Type	Value
2-methoxy-1-methylethylacetate (CAS 108-65-6)	TWA	133 mg/m ³ 20 ppm
	STEL	550 mg/m ³
Cyclohexanone (CAS 108-94-1)	TWA	100 ppm 275 mg/m ³
	STEL	50 ppm 81.6 mg/m ³
	TWA	20 ppm 40.8 mg/m ³
		10 ppm

Biological limit values

Czech Republic. Limit Values for Indicators of Biological Exposure Tests in Urine and Blood, Annex 2, Tables 1 and 2, Government Decree 432/2003 Sb.

Components	Value	Determinant	Specimen	Sampling Time
2-Butoxyethyl acetate (CAS 112-07-2)		Butoxyacetic acid (with hydrolysis)	Creatinine in urine	*
	0.17 mmol/mmol	Butoxyacetic acid (with hydrolysis)	Creatinine in urine	*
Cyclohexanone (CAS 108-94-1)	50 mg/g	1,2-Cyclohexanediol (with hydrolysis)	Creatinine in urine	*
	0.049 mmol/mmol	1,2-Cyclohexanediol (with hydrolysis)	Creatinine in urine	*

* - For sampling details, please see the source document.

Germany. TRGS 903, BAT List (Biological Limit Values)

Components	Value	Determinant	Specimen	Sampling Time
2-Butoxyethyl acetate (CAS 112-07-2)		Butoxyessigsäure	Urine	*

* - For sampling details, please see the source document.

Spain. Biological Limit Values (VLBs), Occupational Exposure Limits for Chemical Agents, Table 4

Components	Value	Determinant	Specimen	Sampling Time
Cyclohexanone (CAS 108-94-1)	80 mg/l	1,2-Ciclohexanodiol, con hidrólisis	Urine	*
	8 mg/l	Ciclohexanol, con hidrólisis	Urine	*

* - For sampling details, please see the source document.

Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)

Components	Value	Determinant	Specimen	Sampling Time
2-Butoxyethyl acetate (CAS 112-07-2)		Gesamt-Butoxyessigsäure	Urine	*
	100 mg/l	Butoxyessigsäure	Urine	*
Cyclohexanone (CAS 108-94-1)	100 mg/l	Gesamt-1,2-Cyclohexandiol	Urine	*

* - For sampling details, please see the source document.

UK. EH40 Biological Monitoring Guidance Values (BMGVs)

Components	Value	Determinant	Specimen	Sampling Time
Cyclohexanone (CAS 108-94-1)	2 mmol/mol	Cyclohexanol	Creatinine in urine	*

* - For sampling details, please see the source document.

Recommended monitoring procedures Not available.

Derived no effect levels (DNELs)

Components	Type	Route	Value	Form
2-Butoxyethyl acetate (CAS 112-07-2)	Workers	Dermal	169 mg/kg	Systemic long term
		Dermal	120 mg/kg	Systemic acute short term
		Inhalation	333 mg/m3	Local acute short term
		Inhalation	133 mg/m3	Systemic long term
2-methoxy-1-methylethylacetate (CAS 108-65-6)	Workers	Dermal	796 mg/kg	Systemic long term
		Inhalation	275 mg/m3	Systemic long term
Cyclohexanone (CAS 108-94-1)	Workers	Dermal	4 mg/kg bw/d	Systemic Long Term
		Dermal	4 mg/kg bw/d	Systemic Short Term
		Inhalation	80 mg/m3	Local short term
		Inhalation	80 mg/m3	Systemic short term
		Inhalation	40 mg/m3	Local long term
		Inhalation	40 mg/m3	Systemic long term

Predicted no effect concentrations (PNECs)

Components	Type	Route	Value	Form		
2-Butoxyethyl acetate (CAS 112-07-2)	Not applicable	Freshwater	0.304 mg/l	Releases		
		Intermittent	0.56 mg/l			
		Marine water	0.0304 mg/l	Food poisoning		
		Secondary	0.06 g/kg			
		Sediment	2.03 mg/kg			
		Sediment	0.203 mg/kg			
		2-methoxy-1-methylethylacetate (CAS 108-65-6)	Not applicable	Soil	0.42 mg/kg	Sewage Treatment Plant
				STP	90 mg/l	
Freshwater	0.635 mg/l			Releases		
Intermittent	6.35 mg/l					
Marine water	0.0635 mg/l			Freshwater		
Sediment	3.29 mg/kg					
Sediment	0.329 mg/kg					
Soil	0.29 mg/kg					
Cyclohexanone (CAS 108-94-1)	Not applicable	STP	100 mg/l	Sewage Treatment Plant		
		Intermittent	0.329 mg/l			
		Marine water	0.00329 mg/l	Releases		
		Sediment	0.168 mg/kg			
		Sediment	0.0168 mg/kg			
		Soil	0.0143 mg/kg			
		STP	10 mg/l	Sewage Treatment Plant		

Exposure guidelines

EU Exposure Limit Values: Skin designation

- 2-Butoxyethyl acetate (CAS 112-07-2) Can be absorbed through the skin.
- 2-methoxy-1-methylethylacetate (CAS Proprietary) Can be absorbed through the skin.
- Cyclohexanone (CAS 108-94-1) Can be absorbed through the skin.

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

- 2-Butoxyethyl acetate (CAS 112-07-2) Can be absorbed through the skin.
- 2-methoxy-1-methylethylacetate (CAS Proprietary) Can be absorbed through the skin.
- Cyclohexanone (CAS 108-94-1) Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering controls Not available.

Individual protection measures, such as personal protective equipment

General information Not available.

Eye/face protection Wear safety glasses; chemical goggles (if splashing is possible).
Eye wash fountain and emergency showers are recommended.

Skin protection

- Hand protection Recommended gloves: Nitrile 6 mil minimum thickness.

- Other Wear appropriate chemical resistant clothing.

Respiratory protection	Provide adequate ventilation. In case of insufficient ventilation wear suitable respiratory equipment.
Thermal hazards	Not available.
Hygiene measures	Do not get this material in contact with skin. Avoid contact with skin, eyes and clothing. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Launder contaminated clothing before reuse.
Environmental exposure controls	Not available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state	Not available.
Form	Liquid.
Color	Magenta
Odor	Solvent.
Odor threshold	Not available.
pH	5.8 - 6.2 Metler Toledo pH Meter
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	>= 149.0 °F (>= 65.0 °C) Closed Cup EPA Method 1020
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	14 - 15 cP Brookfield Viscometer T 22C Spindle #18 (S18) RPM 100
Explosive properties	Not available.
Oxidizing properties	Not available.

9.2. Other information

VOC	< 907 g/L Calculated
------------	----------------------

SECTION 10: Stability and reactivity

10.1. Reactivity	Not available.
10.2. Chemical stability	Stable at normal conditions.
10.3. Possibility of hazardous reactions	None known.
10.4. Conditions to avoid	Heat, flames and sparks.
10.5. Incompatible materials	Not available.
10.6. Hazardous decomposition products	Not available.

SECTION 11: Toxicological information

General information	Not available.
Information on likely routes of exposure	
Inhalation	Harmful if inhaled.
Skin contact	Harmful in contact with skin.

Eye contact	Causes serious eye damage.
Ingestion	Ingestion is not a likely route of exposure.
Symptoms	Not available.

11.1. Information on toxicological effects

Acute toxicity Harmful if inhaled. Harmful in contact with skin.

Components	Species	Test Results
Cyclohexanone (CAS 108-94-1)		
<u>Acute</u>		
Inhalation		
<i>Vapor</i>		
LC50	Rat	> 6.2 mg/l, 4 Hours
Skin corrosion/irritation	Based on available data, the classification criteria are not met.	
Serious eye damage/eye irritation	Causes serious eye damage.	
Respiratory sensitization	Based on available data, the classification criteria are not met.	
Skin sensitization	Based on available data, the classification criteria are not met.	
Germ cell mutagenicity	Based on available data, the classification criteria are not met.	
Carcinogenicity	Based on available data, the classification criteria are not met.	
Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)		
Not listed.		
IARC Monographs. Overall Evaluation of Carcinogenicity		
Cyclohexanone (CAS 108-94-1)	3 Not classifiable as to carcinogenicity to humans.	
Reproductive toxicity	Based on available data, the classification criteria are not met.	
Specific target organ toxicity - single exposure	Based on available data, the classification criteria are not met.	
Specific target organ toxicity - repeated exposure	Based on available data, the classification criteria are not met.	
Aspiration hazard	Based on available data, the classification criteria are not met.	
Mixture versus substance information	Not available.	
Other information	Complete toxicity data are not available for this specific formulation.	

SECTION 12: Ecological information

12.1. Toxicity	No toxicity data noted for the ingredient(s).
12.2. Persistence and degradability	Not available.
12.3. Bioaccumulative potential	Not available.
Partition coefficient n-octanol/water (log Kow)	
Butyl Methacrylate	2.88
Cyclohexanone	0.81
Bioconcentration factor (BCF)	Not available.
12.4. Mobility in soil	Not available.
12.5. Results of PBT and vPvB assessment	Not a PBT or vPvB substance or mixture.
12.6. Other adverse effects	Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods	
Residual waste	Not available.
Contaminated packaging	Not available.
EU waste code	Not available.
Disposal methods/information	Do not dispose of together with general office waste. Do not allow this material to drain into sewers/water supplies. Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations. Ensure collection and disposal with an appropriately licensed waste contractor.

SECTION 14: Transport information

DOT	
UN number	NA1993
UN proper shipping name	Combustible liquid n.o.s. (2-methoxy-1-methylethyl acetate, cyclohexanone) -Not regulated in quantities less than 119 gallons
Transport hazard class(es)	
Class	Combustible
Subsidiary risk	-
Packing group	III
Special precautions for user	Not available.
DOT Supplemental Information	DOT Classification only applies to shipments within the US and Puerto Rico.
IATA	
UN number	Not available.
UN proper shipping name	Not Regulated
Transport hazard class(es)	
Class	Not available.
Subsidiary risk	-
Packing group	Not available.
Environmental hazards	No
Special precautions for user	Not available.
IMDG	
UN number	Not available.
UN proper shipping name	Not Regulated
Transport hazard class(es)	
Class	Not available.
Subsidiary risk	-
Packing group	Not available.
Transport hazard class(es)	
Marine pollutant	No
EmS	Not available.
Special precautions for user	Not available.
ADR	
UN number	Not available.
UN proper shipping name	Not Regulated
Transport hazard class(es)	
Class	Not available.
Subsidiary risk	-
Hazard No. (ADR)	Not available.
Tunnel restriction code	Not available.
Packing group	Not available.
Environmental hazards	No
Special precautions for user	Not available.
Further information	Transport in bulk according to Annex II of MARPOL73/78 and the IBC code: Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorizations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

2-methoxy-1-methylethylacetate (CAS Proprietary)

Cyclohexanone (CAS 108-94-1)

Other regulations

All chemical substances in this HP product have been notified or are exempt from notification under chemical substances notification laws in the following countries: US (TSCA), EU (EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South Korea, New Zealand, and China.

Other information

This Safety Data Sheet complies with the requirements of Regulation (EU) 2015/830. Classification according to Regulation (EC) No 1272/2008 as amended.

Specific Provisions: Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (in the amended version OJ L 396 from 29.05.2007 page 3 with further rectifications and amendments).

National regulations

Not available.

15.2. Chemical safety assessment

See attached SUMI or GEIS document, if applicable.

SECTION 16: Other information

References

Regulation (EC) No. 1907/2006 of December 18, 2006 concerning the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH) and establishing a European Chemicals Agency (REACH).

Regulation (EU) 2015/830 of May 28, 2015 amending Regulation (EC) No. 1907/2006.

Regulation (EC) No. 1272/2008 of December 16, 2008 on classification, labeling and packaging of substances and mixtures, and amendments (CLP).

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any H-statements not written out in full under Sections 2 to 15

H226 Flammable liquid and vapor.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

Revision information

None.

Training information

Follow training instructions when handling this material.

Disclaimer

This Safety Data Sheet document is provided without charge to customers of HP. Data is the most current known to HP at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and may not meet regulatory requirements in other countries.

This safety data sheet is meant to convey information about HP inks (toners) provided in HP Original ink (toner) supplies. If our Safety Data Sheet has been provided to you with a refilled, remanufactured, compatible or other non-HP Original supply please be aware that the information contained herein was not meant to convey information about such products and there could be considerable differences from information in this document and the safety information for the product you purchased. Please contact the seller of the refilled, remanufactured or compatible supplies for applicable information, including information on personal protective equipment, exposure risks and safe handling guidance. HP does not accept refilled, remanufactured or compatible supplies in our recycling programs.

Explanation of abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS	Chemical Abstracts Service
CERCLA	Comprehensive Environmental Response Compensation and Liability Act
CFR	Code of Federal Regulations
COC	Cleveland Open Cup
DOT	Department of Transportation
EPCRA	Emergency Planning and Community Right-to-Know Act (aka SARA)
IARC	International Agency for Research on Cancer
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
RCRA	Resource Conservation and Recovery Act
REC	Recommended
REL	Recommended Exposure Limit
SARA	Superfund Amendments and Reauthorization Act of 1986
STEL	Short-Term Exposure Limit
TCLP	Toxicity Characteristics Leaching Procedure
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
VOC	Volatile Organic Compounds

Safe Use of Mixture Information (SUMI)

--

Solvent based inks: SB01 *English*

Disclaimer


This SUMI is a generic document for communicating conditions of safe use of a product in response to the REACH obligation. This document relates only to conditions of safe use and is not specific to a product. By adding this SUMI to a specific product SDS, the importer/formulator declares that the mixture can safely be used following the instructions below. Following occupational health legislation, the employer of workers remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product. Derived No Effect Levels (DNEL) and Predicted No Effect Concentration (PNEC) values of substances derived from the Chemical Safety Assessment (CSA) will be given in section 8 of the SDS.

The REACH registration number(s), where applicable, completes an extended product SDS.

Operational conditions


Maximum duration	Up to 8 hours per day
Frequency of exposure	< 240 days per year
Process conditions	<p>Covers use at ambient temperatures.</p> <p>Use of an integrated local exhaust ventilation is required in drying zone.</p> <p>Adequate ventilation should be provide for the areas where printing is performed. ANSI/ASHRAE Standard 62.1-2013 provides guidelines to ensure acceptable air quality in the workspace.</p> <p>Use explosion proof electrical equipment.</p> <p>Keep emissions below the occupational exposure limits of the ingredients specified in section 8 of the SDS.</p> <p>Avoid direct contact.</p> <p>Regular cleaning of equipment and work area.</p> <p>Supervision in place to check that Risk Management Measures are in place are being correctly used and Operational Conditions followed.</p>

Risk management measures

<p>Conditions and measures related to Personal Protection Equipment, hygiene and health evaluation</p>	<p>Wear safety glasses with side shields (or goggles), if splashing is possible.</p> <p>Wear appropriate chemical resistant gloves: see section 8 of the SDS.</p> <p>Wear appropriate chemical resistant clothing.</p> <p>In case of inadequate ventilation wear respiratory protection.</p> <p>Eye wash fountain and emergency showers are recommended.</p> <p>Avoid breathing mist/vapours.</p> <p>Avoid contact with skin, eyes and clothing.</p> <p>Training of workers in relation to proper use and maintenance of all Personal protection equipment (PPE) must be ensured.</p>
	

Good practice advice

Use personal protective equipment as required.
 Wash hands before breaks and after work.
 Keep good industrial hygiene and safety practice.
 Use only with adequate ventilation.
 Do no eat, drink or smoke when using this product.
 Wash contaminated clothing before reuse.
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
 Store in a well-ventilated place.
 Keep container tightly closed.
 Store at room temperature.



Environmental measures

Do not allow this material to drain into sewers/water supplies.
 Dispose of waste material according to Local, State, Federal and Provincial Environmental Regulations.
 Ensure collection and disposal with appropriately licenced waste contractor.

Use descriptors

- IS-Use at industrial sites
- PW-Widespread use by professional workers
- SU7-Printing and reproduction media
- PC18-Inks and Toners
- PROC1-Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.
- PROC2-Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
- PROC3- Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
- PROC8a-Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
- PROC8b-Transfer of substance or mixture (charging and discharging) at dedicated facilities
- ERC5-Use at industrial site leading to inclusion into/onto article
- ERC8c-Widespread use leading to inclusion into/onto article (indoor)

Additional information on product composition

In section 2 of the SDS as well as on the label, the classification of the mixture is provided.
 The classification of the mixture is based on the individual ingredients and their concentration within the mixture.
 All ingredients contributing to the classification are stated in Section 3 of the SDS.
 Relevant limit values of ingredients on which the exposure assessment is based, are listed in section 8 of the SDS.
 The product may contain sensitizing ingredients that may cause allergic reaction to certain people.
 Section 2 of the SDS states these ingredients where applicable.