



SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture CP780B
 Registration number -
 Synonyms HP HDR240 Black Scitex Ink
 Issue date 24-Jun-2016
 Version number 01

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Inkjet printing
 Uses advised against None known.

Company identification HP Deutschland GmbH
 Schickardstrasse 32, Geb. Businesspark, Boeblingen B01 (SUO07) - 1st Floor Eingang A
 Boeblingen
 Germany 71034

HP Inc. health effect line
 (Toll-free within US) 1-800-457-4209
 (Direct) 1-760-710-0048
 HP Inc. Customer Care Line
 (Toll-free within the US) 1-800-474-6836
 (Direct) 1-208-323-2551
 Email: hpcustomer.inquiries@hp.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Serious eye damage/eye irritation	Category 1	H318 - Causes serious eye damage.
Skin sensitization	Category 1	H317 - May cause an allergic skin reaction.
Reproductive toxicity (fertility)	Category 2	H361f - Suspected of damaging fertility.
Specific target organ toxicity - single exposure	Category 3 respiratory tract irritation	H335 - May cause respiratory irritation.
Specific target organ toxicity - repeated exposure	Category 1 (liver, respiratory system)	H372 - Causes damage to organs (liver, respiratory system) through prolonged or repeated exposure.

Environmental hazards

Hazardous to the aquatic environment, long-term aquatic hazard	Category 2	H411 - Toxic to aquatic life with long lasting effects.
--	------------	---

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: 1-vinylhexahydro-2H-azepin-2-one, 2-phenoxyethyl acrylate, Acrylated oligoamine resin, Carbon black, Diphenyl (2,4,6-trimethylbenzoyl) phosphine oxide, Isobornyl acrylate, Propoxylated glycerol triacrylate, Reaction mass of Decyl acrylate and Octyl acrylate, Urethane acrylate oligomer A, Urethane acrylate oligomer B

Hazard pictograms



Signal word Danger

Hazard statements

H315	Causes skin irritation.
H318	Causes serious eye damage.
H317	May cause an allergic skin reaction.
H361f	Suspected of damaging fertility.
H335	May cause respiratory irritation.
H372	Causes damage to organs (liver, respiratory system) through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P271 - Use only outdoors or in a well-ventilated area.
P202 - Do not handle until all safety precautions have been read and understood.
P201 - Obtain special instructions before use.
P270 - Do not eat, drink or smoke when using this product.
P264 - Wash hands thoroughly after handling.
P273 - Avoid release to the environment.

Response

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTER or doctor/physician.
P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.
P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention.
P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P308 + P313 - IF exposed or concerned: Get medical attention/advice.
P312 - Call a POISON CENTER/doctor/physician if you feel unwell.
P391 - Collect spillage.
P362 - Take off contaminated clothing and wash before reuse.

Storage

P405 - Store locked up.
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

Disposal

P501

Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information

None.

2.3. Other hazards

Potential routes of exposure to this product are skin and eye contact, ingestion, and inhalation.

Carbon black is classified by the IARC as a Group 2B carcinogen (the substance is possibly carcinogenic to humans). Carbon black in this preparation, due to its bound form, does not present this carcinogenic risk. None of the components present in this formulation at concentrations equal to or greater than 0.1% are listed by EU, MAK, IARC, NTP or OSHA.

Diphenyl (2,4,6-trimethylbenzoyl) phosphineoxide - In animal testing, risk of impaired fertility was shown only after repeated ingestion of very high doses of this substance.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
2-phenoxyethyl acrylate	<30	48145-04-6 256-360-6	-	-	
Classification:	Skin Sens. 1A;H317, Aquatic Chronic 2;H411				
Isobornyl acrylate	<25	5888-33-5 227-561-6	01-2119957862-25-XXXX	-	
Classification:	Skin Irrit. 2;H315, Skin Sens. 1B;H317, Eye Irrit. 2;H319, STOT SE 3;H335, Aquatic Acute 1;H400, Aquatic Chronic 1;H410				

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
1-vinylhexahydro-2H-azepin-2-one	<20	2235-00-9 218-787-6	-	-	
Classification:	Acute Tox. 4;H302, Acute Tox. 4;H312, Skin Sens. 1B;H317, Eye Irrit. 2;H319, STOT RE 1;H372				
Carbon black	<5	1333-86-4 215-609-9	01-2119384822-32-XXXX	-	
Classification:	-				
Diphenyl (2,4,6-trimethylbenzoyl) phosphine oxide	<5	75980-60-8 278-355-8	-	015-203-00-X	
Classification:	Skin Sens. 1B;H317, Repr. 2;H361f, Aquatic Chronic 2;H411				
Reaction mass of Decyl acrylate and Octyl acrylate	<5	Not available 911-295-9	-	-	
Classification:	Skin Irrit. 2;H315, Skin Sens. 1;H317, Eye Irrit. 2;H319, STOT SE 3;H335, Aquatic Chronic 2;H411				
Urethane acrylate oligomer A	<5	Proprietary -	-	-	
Classification:	Skin Irrit. 2;H315, Eye Irrit. 2;H319				
Urethane acrylate oligomer B	<5	Proprietary -	-	-	
Classification:	Acute Tox. 4;H302, Skin Irrit. 2;H315, Skin Sens. 1;H317, Eye Dam. 1;H318, Aquatic Chronic 2;H411				
Acrylated oligoamine resin	<2.5	Proprietary -	-	-	
Classification:	Skin Irrit. 2;H315, Eye Irrit. 2;H319				
Propoxylated glycerol triacrylate	<1	52408-84-1 500-114-5	-	-	
Classification:	Skin Sens. 1;H317, Eye Irrit. 2;H319				

Composition comments Carbon black is present only in a bound form in this preparation.

SECTION 4: First aid measures

General information Not available.

4.1. Description of first aid measures

Inhalation Move to fresh air. If symptoms persist, get medical attention.

Skin contact Wash affected areas thoroughly with mild soap and water. If irritation persists get medical attention.

Eye contact Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure) for at least 15 minutes or until particles are removed. If irritation persists get medical attention.

Ingestion If the material is swallowed, get immediate medical attention or advice -- Do not induce vomiting. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed Not available.

4.3. Indication of any immediate medical attention and special treatment needed Not available.

SECTION 5: Firefighting measures

General fire hazards	Not available.
5.1. Extinguishing media	
Suitable extinguishing media	Dry powder. Carbon dioxide (CO ₂). Water may be ineffective.
Unsuitable extinguishing media	Water may be ineffective. Do not use a solid water stream as it may scatter and spread fire.
5.2. Special hazards arising from the substance or mixture	Not available.
5.3. Advice for firefighters	
Special protective equipment for firefighters	Not available.
Special fire fighting procedures	Avoid runoff into storm sewers and ditches which lead to waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Wear appropriate personal protective equipment. Do not touch or walk through spilled material.
For emergency responders	Not available.
6.2. Environmental precautions	Do not let product enter drains. Do not flush into surface water or sanitary sewer system. See also section 13 Disposal considerations.
6.3. Methods and material for containment and cleaning up	Not available.
6.4. Reference to other sections	Not available.

SECTION 7: Handling and storage

7.1. Precautions for safe handling	Avoid contact with skin, eyes and clothing.
7.2. Conditions for safe storage, including any incompatibilities	Keep away from excessive heat or cold. Do not store in direct sunlight. Do not handle or store near an open flame, heat or other sources of ignition. Opaque, high density polyethylene (HDPE) containers are recommended for shipping and storage.
7.3. Specific end use(s)	Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Belgium. Exposure Limit Values. Components

	Type	Value
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m ³

Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09

Components	Type	Value
Carbon black (CAS 1333-86-4)	MAC	3.5 mg/m ³
	STEL	7 mg/m ³

Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, as amended.

Components	Type	Value
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m ³

Czech Republic. OELs. Government Decree 361 Components

	Type	Value	Form
Carbon black (CAS 1333-86-4)	TWA	2 mg/m ³	Dust.

Denmark. Exposure Limit Values Components

Type	Value
Carbon black (CAS 1333-86-4)	TLV 3.5 mg/m ³

Finland. Workplace Exposure Limits Components

Type	Value
Carbon black (CAS 1333-86-4)	STEL 7 mg/m ³
	TWA 3.5 mg/m ³

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Components

Type	Value
Carbon black (CAS 1333-86-4)	VME 3.5 mg/m ³

Iceland. OELs. Regulation 154/1999 on occupational exposure limits Components

Type	Value
Carbon black (CAS 1333-86-4)	TWA 3.5 mg/m ³

Ireland. Occupational Exposure Limits Components

Type	Value
Carbon black (CAS 1333-86-4)	STEL 7 mg/m ³
	TWA 3.5 mg/m ³

Italy. Occupational Exposure Limits Components

Type	Value	Form
Carbon black (CAS 1333-86-4)	TWA 3 mg/m ³	Inhalable fraction.

Norway. Administrative Norms for Contaminants in the Workplace Components

Type	Value
Carbon black (CAS 1333-86-4)	TLV 3.5 mg/m ³

Poland. MACs. Minister of Labour and Social Policy Regarding Maximum Allowable Concentrations and Intensities in Working Environment Components

Type	Value	Form
Carbon black (CAS 1333-86-4)	TWA 4 mg/m ³	Total dust.

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Components

Type	Value	Form
Carbon black (CAS 1333-86-4)	TWA 3.5 mg/m ³	Fume.

Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents Components

Type	Value
Carbon black (CAS 1333-86-4)	TWA 2 mg/m ³

Spain. Occupational Exposure Limits Components

Type	Value
Carbon black (CAS 1333-86-4)	TWA 3.5 mg/m ³

UK. EH40 Workplace Exposure Limits (WELs) Components

Type	Value
Carbon black (CAS 1333-86-4)	STEL 7 mg/m ³
	TWA 3.5 mg/m ³

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures Not available.

Derived no-effect level (DNEL)

Components	Type	Route	Value	Form
1-vinylhexahydro-2H-azepin-2-one (CAS 2235-00-9)	Workers	Dermal	0.7 mg/kg	Systemic long term
		Inhalation	4.9 mg/m ³	Systemic long term
		Inhalation	0.17 mg/m ³	Local long term
2-phenoxyethyl acrylate (CAS 48145-04-6)	Industry	Dermal	1.5 mg/kg/day	
		Inhalation	10 mg/m ³	
	Workers	Dermal	1.5 mg/kg	Systemic long term
		Inhalation	77 mg/m ³	Local long term
		Inhalation	10 mg/m ³	Systemic long term
Carbon black (CAS 1333-86-4)	Consumers	Inhalation	1.75 mg/m ³	Local long term
		Inhalation	0.06 mg/m ³	Systemic long term
	Workers	Inhalation	2 mg/m ³	Local long term
Isobornyl acrylate (CAS 5888-33-5)	Workers	Inhalation	1 mg/m ³	Systemic long term
		Dermal	1.39 mg/kg bw/d	Systemic long term
		Dermal	1.92 mg/kg	Systemic long term
Propoxylated glycerol triacrylate (CAS 52408-84-1)	Workers	Inhalation	16.22 mg/m ³	Systemic long term

Predicted no effect concentrations (PNECs)

Components	Type	Route	Value	Form
1-vinylhexahydro-2H-azepin-2-one (CAS 2235-00-9)	Not applicable	Freshwater	0.1 mg/l	
		Intermittant	1 mg/l	Releases
		Marine water	0.01 mg/l	
		Sediment	0.829 mg/kg	Freshwater
		Sediment	0.0829 mg/kg	Marine water
		Soil	0.107 mg/kg	
		STP	262 mg/l	Sewage Treatment Plant
		STP	262 mg/l	Sewage Treatment Plant
2-phenoxyethyl acrylate (CAS 48145-04-6)	Not applicable	Freshwater	0.002 mg/l	
		Intermittant	0.0121 mg/l	Releases
		Marine water	0.0002 mg/l	
		Sediment	0.02 mg/kg	Freshwater
		Sediment	0.002 mg/kg	Marine water
		Soil	0.006 mg/kg	
		STP	1.77 mg/l	Sewage Treatment Plant
		STP	1.77 mg/l	Sewage Treatment Plant
Carbon black (CAS 1333-86-4)	Not applicable	Freshwater	5 mg/l	
		Marine water	5 mg/l	
Isobornyl acrylate (CAS 5888-33-5)	Not applicable	Freshwater	0.00092 mg/l	
		Intermittant	0.00704 mg/l	Releases
		Marine water	0.000092 mg/l	
		Sediment	0.145 mg/kg	Freshwater
		Sediment	0.0145 mg/kg	Marine water
		Soil	0.0285 mg/kg	
		STP	2 mg/l	Sewage Treatment Plant
		STP	2 mg/l	Sewage Treatment Plant
Propoxylated glycerol triacrylate (CAS 52408-84-1)	Not applicable	Freshwater	0.00574 mg/l	
		Intermittant	0.0574 mg/l	Releases
		Marine water	0.01697 mg/kg	
		Sediment	0.001697 mg/kg	Marine water
		Soil	0.00111 mg/kg	
		STP	10 mg/l	Sewage Treatment Plant
		STP	10 mg/l	Sewage Treatment Plant
		STP	10 mg/l	Sewage Treatment Plant

Exposure guidelines

Exposure limits have not been established for this product.

8.2. Exposure controls**Appropriate engineering controls**

Not available.

Individual protection measures, such as personal protective equipment**General information**

Not available.

Eye/face protection	Wear safety glasses; chemical goggles (if splashing is possible). Eye wash fountain and emergency showers are recommended.
Skin protection	
- Hand protection	Wear appropriate chemical resistant gloves. Recommended gloves: Nitrile 6 mil minimum thickness.
- Other	Wear appropriate chemical resistant clothing.
Respiratory protection	Provide adequate ventilation. In case of insufficient ventilation wear suitable respiratory equipment.
Thermal hazards	Not available.
Hygiene measures	Handle in accordance with good industrial hygiene and safety practice. Do not get this material in your eyes, on your skin, or on your clothing. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Launder contaminated clothing before reuse. Keep away from food and drink.
Environmental exposure controls	Not available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state	Liquid.
Form	Liquid.
Color	Black.
Odor	Characteristic.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	240.8 °F (116.0 °C) Closed Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Solubility (other)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidizing properties	Not available.

9.2. Other information

VOC (Weight %)	19 g/L Method 24/ASTM D5403-93
-----------------------	--------------------------------

SECTION 10: Stability and reactivity

10.1. Reactivity	Not available.
10.2. Chemical stability	Stable under normal storage conditions.
10.3. Possibility of hazardous reactions	Hazardous polymerization can occur with decreased inhibitor content.
10.4. Conditions to avoid	Exposure to sunlight.
10.5. Incompatible materials	Incompatible with strong bases and oxidizing agents. alkaline metals

10.6. Hazardous decomposition products

Upon decomposition, this product may yield gaseous nitrogen oxides, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

SECTION 11: Toxicological information

General information Not available.

11.1. Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

Components	Species	Test Results
-------------------	----------------	---------------------

Carbon black (CAS 1333-86-4)

Acute*Oral*

LD50

Rat

> 8000 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye damage.

Respiratory sensitization Based on available data, the classification criteria are not met.

Skin sensitization May cause sensitization by skin contact.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Carbon black is classified as a carcinogen by the IARC (possibly carcinogenic to humans, Group 2B) and by the State of California under Proposition 65. In their evaluations of carbon black, both organizations indicate that exposure to carbon black, per se, does not occur when it remains bound within a product matrix, specifically, rubber, ink, or paint. Carbon black is present only in a bound form in this preparation.

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon black (CAS 1333-86-4)

2B Possibly carcinogenic to humans.

Reproductive toxicity Suspected of damaging fertility.

Specific target organ toxicity - single exposure May cause irritation to the respiratory system.

Specific target organ toxicity - repeated exposure Causes damage to organs (liver, respiratory system) through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

Other information Complete toxicity data are not available for this specific formulation

SECTION 12: Ecological information

12.1. Toxicity No toxicity data noted for the ingredient(s).

Aquatic toxicity Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. This product has not been tested for ecological effects.

12.2. Persistence and degradability Not available.

12.3. Bioaccumulative potential Not available.

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil Not available.

12.5. Results of PBT and vPvB assessment Not a PBT or vPvB substance or mixture.

12.6. Other adverse effects Not available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Residual waste Not available.

Contaminated packaging Not available.

EU waste code Not available.

Disposal methods/information

Do not dispose of together with general office waste.
Do not allow this material to drain into sewers/water supplies.
Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.
Ensure collection and disposal with an appropriately licensed waste contractor.

SECTION 14: Transport information

DOT

UN number UN3082
UN proper shipping name Environmentally Hazardous Substance, Liquid, N.O.S. (Acrylates)
Transport hazard class(es)
Class 9
Subsidiary risk -
Packaging group III
Environmental hazards
Marine pollutant Yes
Special precautions for user Not available.

DOT supplemental information DOT Classification only applies to shipments within the US and Puerto Rico.

IATA

UN number UN3082
UN proper shipping name Environmentally Hazardous Substance, Liquid, N.O.S. (Acrylates)
Transport hazard class(es)
Class 9
Subsidiary risk -
Packing group III
Environmental hazards Yes
Special precautions for user Not available.

IMDG

UN number UN3082
UN proper shipping name Environmentally Hazardous Substance, Liquid, N.O.S. (Acrylates), MARINE POLLUTANT
Transport hazard class(es)
Class 9
Subsidiary risk -
Packing group III
Environmental hazards
Marine pollutant Yes
EmS F-A, S-F
Special precautions for user Not available.

ADR

Proper shipping name Environmentally Hazardous Substance, Liquid, N.O.S. (Acrylates)
Hazard class 9
UN number 3082
Packing group III
Marine pollutant Yes


DOT; IATA; IMDG





ADR

Marine pollutant



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I

Not listed.

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex II

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 1 as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 2 as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 3 as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(1) Candidate List as currently published by ECHA

Not listed.

Authorizations

Regulation (EC) No. 143/2011 Annex XIV Substances Subject to Authorization

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work

Not regulated.

Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding

Not regulated.

Other EU regulations

Directive 96/82/EC (Seveso II) on the control of major-accident hazards involving dangerous substances

Not regulated.

Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Diphenyl (2,4,6-trimethylbenzoyl) phosphine oxide (CAS 75980-60-8)

Directive 94/33/EC on the protection of young people at work

Not regulated.

Other regulations

All chemical substances in this HP product have been notified or are exempt from notification under chemical substances notification laws in the following countries: US (TSCA), EU (EINECS/ELINCS), Switzerland, Canada (DSL/NDL), Australia, Japan, Philippines, South Korea, New Zealand, and China.

Other information

This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

Specific Provisions: Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (in the amended version OJ L 396 from 29.05.2007 page 3 with further rectifications and amendments).

National regulations

Not available.

15.2. Chemical safety assessment

See attached SUMI or GEIS document, if applicable.

SECTION 16: Other information

References

Not available.

Information on evaluation method leading to the classification of mixture

Not available.

Issue date

24-Jun-2016

Revision information

1. Product and Company Identification: Business Units
3. Composition / Information on Ingredients: Ingredients
9. Physical & Chemical Properties: Multiple Properties
14. Transport Information: Material Transportation Information
15. Regulatory Information: United States
GHS: Qualifiers

Training information

Not available.

Disclaimer

This Safety Data Sheet document is provided without charge to customers of HP. Data is the most current known to HP at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and may not meet regulatory requirements in other countries.

Manufacturer information

HP Inc.
1501 Page Mill Road
Palo Alto, CA 94304-1112 US
(Direct) +972 (9) 892-4628

Explanation of abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS	Chemical Abstracts Service
CERCLA	Comprehensive Environmental Response Compensation and Liability Act
CFR	Code of Federal Regulations
COC	Cleveland Open Cup
DOT	Department of Transportation
EPCRA	Emergency Planning and Community Right-to-Know Act (aka SARA)
IARC	International Agency for Research on Cancer
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
RCRA	Resource Conservation and Recovery Act
REC	Recommended
REL	Recommended Exposure Limit
SARA	Superfund Amendments and Reauthorization Act of 1986
STEL	Short-Term Exposure Limit
TCLP	Toxicity Characteristics Leaching Procedure
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
VOC	Volatile Organic Compounds
List of abbreviations	Not available.

Safe Use of Mixture Information (SUMI)

--

UV digital printing inks: UV01 *English*

Disclaimer

*This SUMI is a generic document for communicating conditions of safe use of a product in response to the REACH obligation. This document relates only to conditions of safe use and is not specific to a product. By adding this SUMI to a specific product SDS, the importer/formulator declares that the mixture can safely be used following the instructions below. Following occupational health legislation, the employer of workers remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product. Derived No Effect Levels (DNEL) and Predicted No Effect Concentration (PNEC) values of substances derived from the Chemical Safety Assessment (CSA) will be given in section 8 of the SDS.
The REACH registration number(s), where applicable, completes an extended product SDS.*

Operational conditions

Maximum duration	Up to 8 hours per day
Frequency of exposure	< 240 days per year
Process conditions	Covers use at ambient temperatures. Adequate ventilation should be provide for the areas where printing is performed. ANSI/ASHRAE Standard 62.1-2013 provides guidelines to ensure acceptable air quality in the workspace. Keep emissions below the occupational exposure limits of the ingredients specified in section 8 of the SDS. Avoid direct contact. Regular cleaning of equipment and work area. Supervision in place to check that Risk Management Measures are in place are being correctly used and Operational Conditions foll

Risk management measures

Conditions and measures related to Personal Protection Equipment, hygiene and health evaluation

Wear safety glasses with side shields (or goggles), if splashing is possible.
Wear appropriate chemical resistant gloves: see section 8 of the SDS.
Wear appropriate chemical resistant clothing.
Eye wash fountain and emergency showers are recommended.
Avoid breathing mist/vapours.
Avoid contact with skin, eyes and clothing.
Training of workers in relation to proper use and maintenance of all Personal protection equipment (PPE) must be ensured.



Good practice advice

Use personal protective equipment as required.
Wash hands before breaks and after work.
Keep good industrial hygiene and safety practice.
Use only with adequate ventilation.
Do no eat, drink or smoke when using this product.
Wash contaminated clothing before reuse.
Store in a well-ventilated place.
Keep container tightly closed.
Store at room temperature.



Environmental measures

Do not allow this material to drain into sewers/water supplies.
Dispose of waste material according to Local, State, Federal and Provincial Environmental Regulations.
Ensure collection and disposal with appropriately licenced waste contractor.

Use descriptors

IS-Use at industrial sites

PW-Widespread use by professional workers

SU7-Printing and reproduction media

PC18-Inks and Toners

PROC1-Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2-Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC3- Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition

PROC8a-Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC8b-Transfer of substance or mixture (charging and discharging) at dedicated facilities

ERC5-Use at industrial site leading to inclusion into/onto article

ERC8c-Widespread use leading to inclusion into/onto article (indoor)

Additional information on product composition

In section 2 of the SDS as well as on the label, the classification of the mixture is provided.

The classification of the mixture is based on the individual ingredients and their concentration within the mixture.

All ingredients contributing to the classification are stated in Section 3 of the SDS.

Relevant limit values of ingredients on which the exposure assessment is based, are listed in section 8 of the SDS.

The product may contain sensitizing ingredients that may cause allergic reaction to certain people.

Section 2 of the SDS states these ingredients where applicable.

The product is classified as toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.