



SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Important information *** This Safety Data Sheet is only authorised for use by HP for HP Original products. Any unauthorised use of this Safety Data Sheet is strictly prohibited and may result in legal action being taken by HP. ***

1.1. Product identifier

Trade name or designation of the mixture CH663 Series
Registration number -
UFI Q7QD-H7GH-9304-VYP3
Synonyms HP XP222 Magenta Scitex Ink
Issue date 06-Sep-2013
Version number 14
Revision date 22-Apr-2021
Supersedes date 31-Mar-2021

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Inkjet printing
Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

HP Finland Oy
Piispankalliontie 17, Pt. Ground Floor
Espoo
Finland FI-02200

Telephone +358-102-77-4000

HP Inc. health effects line

(Toll-free within the US) 1-800-457-4209
(Direct) 1-760-710-0048

HP Inc. Customer Care Line

(Toll-free within the US) 1-800-474-6836
(Direct) 1-208-323-2551

Email: hpcustomer.inquiries@hp.com

1.4 Emergency telephone number +358 (0)9 471977

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Serious eye damage/eye irritation	Category 2	H319 - Causes serious eye irritation.
Skin sensitization	Category 1	H317 - May cause an allergic skin reaction.
Reproductive toxicity (fertility, the unborn child)	Category 1B	H360FD - May damage fertility. May damage the unborn child.
Specific target organ toxicity - single exposure	Category 3 respiratory tract irritation	H335 - May cause respiratory irritation.
Specific target organ toxicity - repeated exposure	Category 1 (liver, respiratory system)	H372 - Causes damage to organs (liver, respiratory system) through prolonged or repeated exposure.

Environmental hazards

Hazardous to the aquatic environment, long-term aquatic hazard	Category 2	H411 - Toxic to aquatic life with long lasting effects.
--	------------	---

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: 1-vinylhexahydro-2H-azepin-2-one, 2-methyl-1-(4-methylthiophenyl)- 2-morpholinopropan-1-one, 2-phenoxyethyl acrylate, Dodecyl acrylate

Hazard pictograms



Signal word

Danger

Hazard statements

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H360FD	May damage fertility. May damage the unborn child.
H335	May cause respiratory irritation.
H372	Causes damage to organs (liver, respiratory system) through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P270	Do not eat, drink or smoke when using this product.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.

Response

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P308 + P313	IF exposed or concerned: Get medical attention/advice.
P314	Get medical attention/advice if you feel unwell.
P391	Collect spillage.
P362	Take off contaminated clothing and wash before reuse.

Storage

P405	Store locked up.
------	------------------

Disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

Supplemental label information None.

2.3. Other hazards Potential routes of exposure to this product are skin and eye contact, ingestion, and inhalation.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
2-phenoxyethyl acrylate	<25	48145-04-6 256-360-6	01-2119980532-35-XXXX	-	
Classification:	Skin Sens. 1A;H317, Repr. 2;H361d, Aquatic Chronic 2;H411				
Dodecyl acrylate	<25	2156-97-0 218-463-4	01-2119976296-23-XXXX	-	
Classification:	Skin Irrit. 2;H315, Skin Sens. 1;H317, Eye Irrit. 2;H319, STOT SE 3;H335, Aquatic Chronic 2;H411				
1-vinylhexahydro-2H-azepin-2-one	<20	2235-00-9 218-787-6	01-2119977109-27-XXXX	-	
Classification:	Acute Tox. 4;H302, Acute Tox. 4;H312, Skin Sens. 1B;H317, Eye Irrit. 2;H319, STOT RE 1;H372				

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Neopentylglycol, propoxylated esters with acrylic acid	<10	84170-74-1	01-2119970213-43-XXXX	-	
Classification:	Skin Sens. 1B;H317, Aquatic Chronic 2;H411				
2-[[[3-hydroxy-2,2-bis[[[(1-oxoallyl)oxy]methyl]propoxy]methyl]-2-[[[(1-oxoallyl)oxy]methyl]-1,3-propandiyldiacrylat	<5	1384855-91-7 800-838-4	01-2119980666-22-XXXX	-	
Classification:	Skin Sens. 1A;H317, Eye Irrit. 2;H319, Aquatic Chronic 3;H412				
Diphenyl (2,4,6-trimethylbenzoyl) phosphine oxide	<5	75980-60-8 278-355-8	01-2119972295-29-XXXX	015-203-00-X	
Classification:	Skin Sens. 1B;H317, Repr. 2;H361fd, Aquatic Chronic 2;H411				
2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one	<2.5	71868-10-5 400-600-6	-	606-041-00-6	
Classification:	Acute Tox. 4;H302, Repr. 1B;H360FD, Aquatic Chronic 2;H411				

SECTION 4: First aid measures

General information

Risk of skin burn caused by hot melt.
Do not leave the victim unattended.
Remove victim immediately from source of exposure.
Victim to lie down in the recovery position, cover and keep him warm.

4.1. Description of first aid measures

Inhalation

If dust from the material is inhaled, remove the affected person immediately to fresh air.

Move to fresh air in case of accidental inhalation of vapors or decomposition products. If breathing is difficult, give oxygen. Oxygen or artificial respiration if needed. Consult a physician for specific advice.

Skin contact

Wash the skin immediately with soap and water. In case of contact with molten product, cool rapidly with water and seek immediate medical attention. Do not attempt to remove molten product from skin because skin will tear easily.

Eye contact

Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure) for at least 15 minutes or until particles are removed. If irritation persists get medical attention.

Ingestion

If swallowed, do NOT induce vomiting. Get medical attention. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

No experiences of acute or chronic damages in humans have been made yet.

4.3. Indication of any immediate medical attention and special treatment needed

Not available.

SECTION 5: Firefighting measures

General fire hazards

Not available.

5.1. Extinguishing media

Suitable extinguishing media

Dry powder. Carbon dioxide (CO₂). Water may be ineffective.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Not available.

5.3. Advice for firefighters

Special protective equipment for firefighters

Avoid runoff into storm sewers and ditches which lead to waterways.

Special fire fighting procedures

Avoid runoff into storm sewers and ditches which lead to waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Wear appropriate personal protective equipment. Do not touch or walk through spilled material.

For emergency responders

Not available.

6.2. Environmental precautions

Do not let product enter drains. Do not flush into surface water or sanitary sewer system. See also section 13 Disposal considerations.

6.3. Methods and material for containment and cleaning up Not available.

6.4. Reference to other sections Not available.

SECTION 7: Handling and storage

7.1. Precautions for safe handling Avoid contact with skin, eyes and clothing.

7.2. Conditions for safe storage, including any incompatibilities Keep away from excessive heat or cold. Do not store in direct sunlight. Do not handle or store near an open flame, heat or other sources of ignition. Opaque, high density polyethylene (HDPE) containers are recommended for shipping and storage.

7.3. Specific end use(s) Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits No exposure limits noted for ingredient(s).

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures Not available.

Derived no effect levels (DNELs)

Components	Type	Route	Value	Form
1-vinylhexahydro-2H-azepin-2-one (CAS 2235-00-9)	Workers	Dermal	0.7 mg/kg	Systemic long term
		Inhalation	4.9 mg/m3	Systemic long term
		Inhalation	0.17 mg/m3	Local long term
2-[[[3-hydroxy-2,2-bis[[[(1-oxoallyl)oxy]methyl]propoxy]methyl]-2-[[[(1-oxoallyl)oxy]methyl]-1,3-propandiyldiacrylat (CAS 1384855-91-7)	Industry	Dermal	0.5 mg/kg/day	
		Inhalation	1.76 mg/m3	
2-phenoxyethyl acrylate (CAS 48145-04-6)	Workers	Dermal	1.5 mg/kg	Systemic long term
		Inhalation	77 mg/m3	Local long term
		Inhalation	10 mg/m3	Systemic long term
Diphenyl (2,4,6-trimethylbenzoyl) phosphine oxide (CAS 75980-60-8)	Workers	Dermal	0.233 mg/kg	Systemic long term
		Inhalation	0.822 mg/m3	Systemic long term
Dodecyl acrylate (CAS 2156-97-0)	Workers	Dermal	138.9 mg/kg	Systemic long term
		Inhalation	97.9 mg/m3	Systemic long term
Neopentylglycol, propoxylated esters with acrylic acid (CAS 84170-74-1)	Workers	Dermal	3.33 mg/kg	Systemic long term
		Inhalation	11.75 mg/m3	Systemic long term

Predicted no effect concentrations (PNECs)

Components	Type	Route	Value	Form
1-vinylhexahydro-2H-azepin-2-one (CAS 2235-00-9)	Not applicable	Freshwater	0.1 mg/l	
		Intermittent	1 mg/l	Releases
		Marine water	0.01 mg/l	
		Sediment	0.829 mg/kg	Freshwater
		Sediment	0.0829 mg/kg	Marine water
		Soil	0.107 mg/kg	
		STP	262 mg/l	Sewage Treatment Plant
2-phenoxyethyl acrylate (CAS 48145-04-6)	Not applicable	Freshwater	0.002 mg/l	
		Intermittent	0.0121 mg/l	Releases
		Marine water	0.0002 mg/l	
		Sediment	0.02 mg/kg	Freshwater
		Sediment	0.002 mg/kg	Marine water
		Soil	0.006 mg/kg	
		STP	1.77 mg/l	Sewage Treatment Plant
Diphenyl (2,4,6-trimethylbenzoyl) phosphine oxide (CAS 75980-60-8)	Not applicable	Freshwater	0.00353 mg/l	
		Intermittent	0.0353 mg/l	Releases
		Marine water	0.0005353 mg/l	
		Sediment	0.29 mg/kg	Freshwater

Components	Type	Route	Value	Form		
Dodecyl acrylate (CAS 2156-97-0)	Not applicable	Sediment	0.029 mg/kg	Marine water		
		Soil	0.0557 mg/kg			
		Freshwater	0.495 mg/l	Releases		
		Intermittent	0.52 mg/l			
		Marine water	0.05 mg/l			
		Sediment	1245.42 mg/kg		Freshwater	
		Neopentylglycol, propoxylated esters with acrylic acid (CAS 84170-74-1)	Not applicable	Sediment	124.54 mg/kg	Marine water
				Soil	248.09 mg/kg	Sewage Treatment Plant
STP	1000 mg/l					
Freshwater	0.0027 mg/l			Releases		
Intermittent	0.027 mg/l					
Marine water	0.00027 mg/l					
Sediment	0.188 mg/kg				Freshwater	
Sediment	0.018 mg/kg				Marine water	
Soil	0.036 mg/kg	Sewage Treatment Plant				
STP	0.2 mg/l					

Exposure guidelines Exposure limits have not been established for this product.

8.2. Exposure controls

Appropriate engineering controls Not available.

Individual protection measures, such as personal protective equipment

General information Not available.

Eye/face protection Wear safety glasses; chemical goggles (if splashing is possible). Eye wash fountain and emergency showers are recommended.

Skin protection

- Hand protection Wear appropriate chemical resistant gloves. Recommended gloves: Nitrile 6 mil minimum thickness.

- Other

Wear appropriate chemical resistant gloves.
Wear appropriate chemical resistant clothing.

Respiratory protection Provide adequate ventilation. In case of insufficient ventilation wear suitable respiratory equipment.

Thermal hazards Not available.

Hygiene measures Handle in accordance with good industrial hygiene and safety practice. Do not get this material in your eyes, on your skin, or on your clothing. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Launder contaminated clothing before reuse. Keep away from food and drink.

Environmental exposure controls Not available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state Liquid.

Form Liquid.

Color Magenta

Odor Characteristic.

Odor threshold Not available.

pH 6.8 - 7.2 Metler Toledo pH Meter. Temperature 25°C

Melting point/freezing point Not available.

Initial boiling point and boiling range Not available.

Flash point > 200.0 °F (> 93.3 °C) Closed Cup EPA Method 1020

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not available.

Flammability limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	13.5 - 14.5 cP Brookfield Viscometer (± 0.5) Temperature 45°C. Spindle # 18 (S18) RPM 100. Wait approx 10 min to take the reading.
Explosive properties	Not available.
Oxidizing properties	Not available.
9.2. Other information	
VOC	27.72 g/L Method 24/ASTM D403-93

SECTION 10: Stability and reactivity

10.1. Reactivity	Not available.
10.2. Chemical stability	Stable under normal storage conditions.
10.3. Possibility of hazardous reactions	Hazardous polymerization can occur with decreased inhibitor content.
10.4. Conditions to avoid	Exposure to sunlight.
10.5. Incompatible materials	Incompatible with strong bases and oxidizing agents. alkaline metals
10.6. Hazardous decomposition products	Upon decomposition, this product may yield gaseous nitrogen oxides, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

SECTION 11: Toxicological information

General information	Not available.
Information on likely routes of exposure	
Inhalation	Inhalation may result in mild irritation to the respiratory system.
Skin contact	Causes skin irritation. May cause sensitization by skin contact.
Eye contact	Causes serious eye irritation.
Ingestion	Ingestion is not a likely route of exposure.
Symptoms	Not available.

11.1. Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

Components	Species	Test Results
1-vinylhexahydro-2H-azepin-2-one (CAS 2235-00-9)		
Acute		
Dermal		
LD50	Rabbit	1700 mg/kg
Inhalation		
LC50	Rat	> 1.6 mg/l
Oral		
LD50	Rat	1114 mg/kg

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory sensitization	Based on available data, the classification criteria are not met.
Skin sensitization	May cause sensitization by skin contact.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Based on available data, the classification criteria are not met.
Reproductive toxicity	May damage fertility. May damage the unborn child.
Specific target organ toxicity - single exposure	May cause irritation to the respiratory system.

Specific target organ toxicity - repeated exposure	Causes damage to organs (liver, respiratory system) through prolonged or repeated exposure.
Aspiration hazard	Based on available data, the classification criteria are not met.
Mixture versus substance information	Not available.
Other information	Complete toxicity data are not available for this specific formulation

SECTION 12: Ecological information

12.1. Toxicity

Aquatic toxicity Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. This product has not been tested for ecological effects.

Components		Species	Test Results
2-phenoxyethyl acrylate (CAS 48145-04-6)			
<i>Acute</i>			
	EC10	Desmodesmus subcapitatus	0.71 mg/l, 72 h (DIN 38412 L9)
	EC50	Desmodesmus subcapitatus	4.44 mg/l, 72 h (DIN 38412 L9)
	LC50	Leuciscus idus	10 mg/l, 96 h (DIN 38 412)
	NOEC	Desmodesmus subcapitatus	0.71 mg/l, 72 h (DIN 38412 L9)
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Daphnia magna	1.21 mg/l, 48 h (Directive CE 79/831/CEE, Annex V, Part C)
Diphenyl (2,4,6-trimethylbenzoyl) phosphine oxide (CAS 75980-60-8)			
<i>Acute</i>			
	EC10	Pseudokirchneriella subcapitata	1.56 mg/l, 72 h (OECD 201)
	EC50	Pseudokirchneriella subcapitata	> 2.01 mg/l, 72 h (OECD 201)
	LC50	Cyprinus carpio	1.4 mg/l, 96 h (OECD 203)
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Daphnia magna	3.53 mg/l, 48 h (OECD 202)
Dodecyl acrylate (CAS 2156-97-0)			
<i>Acute</i>			
	ErC50	Pseudokirchneriella subcapitata	> 0.274 µg/l, 72 h (OECD 201)
	LC50	Leuciscus idus	460 mg/l, 96 h (DIN 38 412, part L 15, 1982)
	NOEC	Leuciscus idus	215 mg/l, 96 h (DIN 38 412, part L 15, 1982)
<i>Chronic</i>			
	LOEC	Daphnia magna	> 0.25 µg/l, 21 d (OECD 211)
Aquatic			
<i>Chronic</i>			
Crustacea	NOEC	Daphnia magna	0.25 µg/l, 21 d (OECD 211)
Fish	LOEC	Danio rerio	> 1 µg/l, 36 d (OECD 210)
Neopentylglycol, propoxylated esters with acrylic acid (CAS 84170-74-1)			
<i>Acute</i>			
	EC10	Pseudokirchneriella subcapitata	2.3 mg/l, 72 h (OECD 201)
	EC50	Pseudokirchneriella subcapitata	11 mg/l, 72 h (OECD 201)
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Daphnia Magna	37 mg/l, 48 h (OECD 202)
Fish	LC50	Danio rerio	2.7 mg/l, 96 h (OECD 203)

12.2. Persistence and degradability Not available.

12.3. Bioaccumulative potential Not available.

Partition coefficient n-octanol/water (log Kow) Not available.

Bioconcentration factor (BCF)

Diphenyl (2,4,6-trimethylbenzoyl) phosphine oxide

72, (JIS K 0102-1986, 71 - Kanpogyo No .S, Yakuhatsu No . 615, 4
MITI/MHW Chemical Substance Control Law, Japan)
2.34, (EPA Epiwin (v.4.11))

Dodecyl acrylate

12.4. Mobility in soil Not available.**12.5. Results of PBT and vPvB assessment** Not a PBT or vPvB substance or mixture.**12.6. Other adverse effects** Not available.


SECTION 13: Disposal considerations**13.1. Waste treatment methods****Residual waste** Not available.**Contaminated packaging** Not available.**EU waste code** Not available.**Disposal methods/information** Do not dispose of together with general office waste.
Do not allow this material to drain into sewers/water supplies.
Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.
Ensure collection and disposal with an appropriately licensed waste contractor.

SECTION 14: Transport information**DOT**


Not regulated as dangerous goods.

DOT Supplemental Information DOT Classification only applies to shipments within the US and Puerto Rico.**IATA****UN number** UN3082**UN proper shipping name** Environmentally Hazardous Substance, Liquid, N.O.S. (Acrylates, Propiophenone derivative)**Transport hazard class(es)****Class** 9**Subsidiary risk** -**Packing group** III**Environmental hazards** Yes**Special precautions for user** Not available.**IATA Supplemental Information** When shipping ≤ 5L inner packaging, Special Provision A197 may apply.**IMDG****UN number** UN3082**UN proper shipping name** Environmentally Hazardous Substance, Liquid, N.O.S. (Acrylates, Propiophenone derivative),
MARINE POLLUTANT**Transport hazard class(es)****Class** 9**Subsidiary risk** -**Packing group** III**Transport hazard class(es)****Marine pollutant** Yes**EmS** F-A, S-F**Special precautions for user** Not available.**IMDG Supplemental Information** When shipping ≤ 5L containers, IMDG 2.10.2.7 may apply.**ADR****UN number** UN3082**UN proper shipping name** Environmentally Hazardous Substance, Liquid, N.O.S. (Acrylates, Propiophenone derivative)**Transport hazard class(es)****Class** 9**Subsidiary risk** -**Hazard No. (ADR)** Not available.**Tunnel restriction code** Not available.**Packing group** III**Environmental hazards** Yes**Special precautions for user** Not available.**ADR Supplemental Information** When shipping ≤ 5L containers, ADR 375 may apply.

ADR; IATA; IMDG



Marine pollutant



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

2-methyl-1-(4-methylthiophenyl)- 2-morpholinopropan-1-one (CAS 71868-10-5)

Authorizations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

2-methyl-1-(4-methylthiophenyl)- 2-morpholinopropan-1-one (CAS 71868-10-5)

Other regulations

All chemical substances in this HP product have been notified or are exempt from notification under chemical substances notification laws in the following countries: US (TSCA), EU (EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South Korea, New Zealand, and China.

Other information

This Safety Data Sheet complies with the requirements of Regulation (EU) 2015/830. Classification according to Regulation (EC) No 1272/2008 as amended.

Specific Provisions: Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (in the amended version OJ L 396 from 29.05.2007 page 3 with further rectifications and amendments).

National regulations

Not available.

15.2. Chemical safety assessment

See attached SUMI or GEIS document, if applicable.

SECTION 16: Other information**References**

Regulation (EC) No. 1907/2006 of December 18, 2006 concerning the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH) and establishing a European Chemicals Agency (REACH).

Regulation (EU) 2015/830 of May 28, 2015 amending Regulation (EC) No. 1907/2006.

Regulation (EC) No. 1272/2008 of December 16, 2008 on classification, labeling and packaging of substances and mixtures, and amendments (CLP).

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any H-statements not written out in full under Sections 2 to 15

H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H360FD May damage fertility. May damage the unborn child.
H361d Suspected of damaging the unborn child.
H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Revision information

3. Composition / Information on Ingredients: Disclosure Overrides

Training information

Follow training instructions when handling this material.

Disclaimer

This Safety Data Sheet document is provided without charge to customers of HP. Data is the most current known to HP at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and may not meet regulatory requirements in other countries.

This safety data sheet is meant to convey information about HP inks (toners) provided in HP Original ink (toner) supplies. If our Safety Data Sheet has been provided to you with a refilled, remanufactured, compatible or other non-HP Original supply please be aware that the information contained herein was not meant to convey information about such products and there could be considerable differences from information in this document and the safety information for the product you purchased. Please contact the seller of the refilled, remanufactured or compatible supplies for applicable information, including information on personal protective equipment, exposure risks and safe handling guidance. HP does not accept refilled, remanufactured or compatible supplies in our recycling programs.

Explanation of abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS	Chemical Abstracts Service
CERCLA	Comprehensive Environmental Response Compensation and Liability Act
CFR	Code of Federal Regulations
COC	Cleveland Open Cup
DOT	Department of Transportation
EPCRA	Emergency Planning and Community Right-to-Know Act (aka SARA)
IARC	International Agency for Research on Cancer
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
RCRA	Resource Conservation and Recovery Act
REC	Recommended
REL	Recommended Exposure Limit
SARA	Superfund Amendments and Reauthorization Act of 1986
STEL	Short-Term Exposure Limit
TCLP	Toxicity Characteristics Leaching Procedure
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
VOC	Volatile Organic Compounds

Safe Use of Mixture Information (SUMI)

--

UV digital printing inks: UV01 *English*





Disclaimer

*This SUMI is a generic document for communicating conditions of safe use of a product in response to the REACH obligation. This document relates only to conditions of safe use and is not specific to a product. By adding this SUMI to a specific product SDS, the importer/formulator declares that the mixture can safely be used following the instructions below. Following occupational health legislation, the employer of workers remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product. Derived No Effect Levels (DNEL) and Predicted No Effect Concentration (PNEC) values of substances derived from the Chemical Safety Assessment (CSA) will be given in section 8 of the SDS.
The REACH registration number(s), where applicable, completes an extended product SDS.*

Operational conditions

Maximum duration	Up to 8 hours per day
Frequency of exposure	< 240 days per year
Process conditions	Covers use at ambient temperatures. Adequate ventilation should be provide for the areas where printing is performed. ANSI/ASHRAE Standard 62.1-2013 provides guidelines to ensure acceptable air quality in the workspace. Keep emissions below the occupational exposure limits of the ingredients specified in section 8 of the SDS. Avoid direct contact. Regular cleaning of equipment and work area. Supervision in place to check that Risk Management Measures are in place are being correctly used and Operational Conditions foll

Risk management measures

Conditions and measures related to Personal Protection Equipment, hygiene and health evaluation	<p>Wear safety glasses with side shields (or goggles), if splashing is possible. Wear appropriate chemical resistant gloves: see section 8 of the SDS. Wear appropriate chemical resistant clothing. Eye wash fountain and emergency showers are recommended. Avoid breathing mist/vapours. Avoid contact with skin, eyes and clothing. Training of workers in relation to proper use and maintenance of all Personal protection equipment (PPE) must be ensured.</p> <div style="display: flex; justify-content: space-around; align-items: center;">     </div>
--	--

Good practice advice

<p>Use personal protective equipment as required. Wash hands before breaks and after work. Keep good industrial hygiene and safety practice. Use only with adequate ventilation. Do no eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Store in a well-ventilated place. Keep container tightly closed. Store at room temperature.</p>	 
--	---

Environmental measures

Do not allow this material to drain into sewers/water supplies.
Dispose of waste material according to Local, State, Federal and Provincial Environmental Regulations.
Ensure collection and disposal with appropriately licenced waste contractor.

Use descriptors

IS-Use at industrial sites
PW-Widespread use by professional workers
SU7-Printing and reproduction media
PC18-Inks and Toners
PROC1-Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.
PROC2-Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
PROC3- Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
PROC8a-Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
PROC8b-Transfer of substance or mixture (charging and discharging) at dedicated facilities
ERC5-Use at industrial site leading to inclusion into/onto article
ERC8c-Widespread use leading to inclusion into/onto article (indoor)

Additional information on product composition

In section 2 of the SDS as well as on the label, the classification of the mixture is provided.
The classification of the mixture is based on the individual ingredients and their concentration within the mixture.
All ingredients contributing to the classification are stated in Section 3 of the SDS.
Relevant limit values of ingredients on which the exposure assessment is based, are listed in section 8 of the SDS.
The product may contain sensitizing ingredients that may cause allergic reaction to certain people.
Section 2 of the SDS states these ingredients where applicable.
The product is classified as toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.