

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

*** This Safety Data Sheet is only authorised for use by HP for HP Original products. Any Important information

unauthorised use of this Safety Data Sheet is strictly prohibited and may result in legal action

being taken by HP. ***

1.1. Product identifier

Trade name or designation

CN872Series

of the mixture

Registration number

UFI 46E4-47XY-830F-DVYX

Synonyms HP XP231 Specialty Billboard Black Scitex Ink

Issue date 27-Nov-2013

Version number 11

Revision date 20-Apr-2021 03-Sep-2019 Supersedes date

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Inkjet printing Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

HP Finland Oy

Piispankalliontie 17, Pt. Ground Floor

Espoo

Finland FI-02200 +358-102-77-4000

HP Inc. health effects line

(Toll-free within the US) 1-800-457-4209 1-760-710-0048 (Direct)

HP Inc. Customer Care

Telephone

1-800-474-6836 (Toll-free within the US) (Direct) 1-208-323-2551

Email: hpcustomer.inquiries@hp.com

1.4 Emergency telephone

number

+358 (0)9 471977

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Skin corrosion/irritation Category 2 H315 - Causes skin irritation. Serious eye damage/eye irritation H318 - Causes serious eye Category 1

damage.

Skin sensitization Category 1 H317 - May cause an allergic skin

Reproductive toxicity (fertility, the unborn

child)

Category 1B

H360FD - May damage fertility. May damage the unborn child. H335 - May cause respiratory

Specific target organ toxicity - single

exposure

Category 3 respiratory tract irritation

irritation. H372 - Causes damage to organs

Specific target organ toxicity - repeated Category 1 (liver, respiratory system) exposure

(liver, respiratory system) through

prolonged or repeated exposure.

Environmental hazards

Hazardous to the aquatic environment, H411 - Toxic to aquatic life with Category 2 long-term aquatic hazard long lasting effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

1-vinylhexahydro-2H-azepin-2-one, Ethyl 4-dimethylaminobenzoate, Contains:

exo-1,7,7-trimethylbicyclo[2.2,1]hept-2-yl acrylate, Oxybis(methyl-2,1-ethanediyl) diacrylate

Hazard pictograms



Signal word Danger

Hazard statements

Causes skin irritation. H315

May cause an allergic skin reaction. H317 Causes serious eve damage. H318 May cause respiratory irritation. H335

May damage fertility. May damage the unborn child. H360FD

Causes damage to organs (liver, respiratory system) through prolonged or repeated exposure. H372

Toxic to aquatic life with long lasting effects. H411

Precautionary statements

Prevention

Wear protective gloves/protective clothing/eye protection/face protection. P280

Do not breathe dust/fume/gas/mist/vapors/spray. P260 Use only outdoors or in a well-ventilated area. P271 Obtain special instructions before use. P201 Wash hands thoroughly after handling. P264 Avoid release to the environment. P273

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present P305 + P351 + P338

and easy to do. Continue rinsing

Immediately call a POISON CENTER or doctor/physician. P310

IF ON SKIN: Wash with plenty of soap and water. P302 + P352

If skin irritation or rash occurs: Get medical advice/attention. P333 + P313

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P304 + P340

P314 Get medical attention/advice if you feel unwell.

P391 Collect spillage.

Take off contaminated clothing and wash before reuse. P362

Storage

Store locked up. P405

Store in a well-ventilated place. Keep container tightly closed. P403 + P233

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations. P501

Supplemental label information None.

2.3. Other hazards Carbon black is classified by the IARC as a Group 2B carcinogen (the substance is possibly

carcinogenic to humans). Carbon black in this preparation, due to its bound form, does not present

this carcinogenic risk. None of the other ingredients in this preparation are classified as

carcinogens according to ACGIH, EU, IARC, MAK, NTP or OSHA.

Potential routes of exposure to this product are skin and eye contact, ingestion, and inhalation.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name		%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
exo-1,7,7-trimethylbicyclo	o[2.2,1]hept-	<20	5888-33-5	01-2119957862-25-XXXX	-	
2-yl acrylate			227-561-6			
Classification:	Skin Irrit. 2;H3	315, Skin	Sens. 1B;H317, Eye	Irrit. 2;H319, STOT SE 3;H33	35, Aquatic	

Chronic 1;H410

(octahydro-4.7-methano-1H-indenediy 42594-17-2

I)bis(methylene) diacrylate

Classification: Skin Sens. 1;H317, Aquatic Chronic 2;H411

Material name: CN872Series SDS LITHUANIA

11209 Version #: 11 Revision date: 20-Apr-2021 Issue date: 27-Nov-2013

Chemical name		%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
1-vinylhexahydro-2H-aze	pin-2-one	<15	2235-00-9 218-787-6	01-2119977109-27-XXXX	-	
Classification:	Acute Tox. 4; RE 1;H372	;H302, Ac	ute Tox. 4;H312, Ski	n Sens. 1B;H317, Eye Irrit. 2;	H319, STOT	
2-[[3-hydroxy-2,2-bis[[(1-c methyl]propoxy]methyl]-2 oxy]methyl]-1,3-propandiy	-[[(1-oxoallyl)	<15	1384855-91-7 800-838-4	01-2119980666-22-XXXX	-	
Classification:	Skin Sens. 1.	A;H317, E	ye Irrit. 2;H319, Aqu	atic Chronic 3;H412		
Propylidynetrimethanol, e esters with acrylic acid	thoxylated,	<15	Proprietary -	-	-	
Classification:	Skin Sens. 1	;H317				
Dodecyl acrylate		<10	2156-97-0 218-463-4	01-2119976296-23-XXXX	-	
Classification:	Skin Irrit. 2;H Chronic 2;H4		Sens. 1;H317, Eye I	rrit. 2;H319, STOT SE 3;H335	5, Aquatic	
Phenyl, Bis(2,4,6-trimethylbenzoy oxide	ا)-phosphine	<7.5	162881-26-7 423-340-5	01-2119489401-38-XXXX	015-189-00-5	
UXIUE						
Classification:	Skin Sens. 1	A;H317, A	quatic Chronic 4;H4	13		
Classification:		A;H317, A <7.5	quatic Chronic 4;H4 2399-48-6 219-268-7	13 01-2120738396-46-XXXX	-	
Classification:	e Acute Tox. 4	<7.5 ;H302, Ski	2399-48-6 219-268-7	01-2120738396-46-XXXX xin Sens. 1;H317, Eye Dam. 1		
Classification: Tetrahydrofurfuryl acrylate Classification: Oxybis(methyl-2,1-ethane	e Acute Tox. 4; 1B;H360, Re	<7.5 ;H302, Ski	2399-48-6 219-268-7 in Corr. 1B;H314, Sk	01-2120738396-46-XXXX xin Sens. 1;H317, Eye Dam. 1		
Classification: Tetrahydrofurfuryl acrylate Classification: Oxybis(methyl-2,1-ethane	e Acute Tox. 4: 1B;H360, Re ediyl)	<7.5 ;H302, Ski pr. 1B;H36 <5	2399-48-6 219-268-7 in Corr. 1B;H314, Sk 60FD, Aquatic Chror 57472-68-1	01-2120738396-46-XXXX sin Sens. 1;H317, Eye Dam. 1 nic 2;H411 01-2119484629-21-XXXX		
Classification: Tetrahydrofurfuryl acrylate Classification: Oxybis(methyl-2,1-ethanediacrylate	e Acute Tox. 4, 1B;H360, Re ediyl) Skin Irrit. 2;H	<7.5 ;H302, Ski pr. 1B;H36 <5	2399-48-6 219-268-7 in Corr. 1B;H314, Sk 60FD, Aquatic Chror 57472-68-1 260-754-3	01-2120738396-46-XXXX sin Sens. 1;H317, Eye Dam. 1 nic 2;H411 01-2119484629-21-XXXX		
Classification: Tetrahydrofurfuryl acrylate Classification: Oxybis(methyl-2,1-ethanediacrylate Classification:	e Acute Tox. 4, 1B;H360, Re ediyl) Skin Irrit. 2;H	<7.5 ;H302, Ski pr. 1B;H36 <5	2399-48-6 219-268-7 in Corr. 1B;H314, Sk 60FD, Aquatic Chror 57472-68-1 260-754-3 Sens. 1;H317, Eye I	01-2120738396-46-XXXX xin Sens. 1;H317, Eye Dam. 1; nic 2;H411 01-2119484629-21-XXXX Dam. 1;H318		
Classification: Tetrahydrofurfuryl acrylate Classification: Oxybis(methyl-2,1-ethanediacrylate Classification: 2-isopropyl-9H-thioxanthe	Acute Tox. 4; 1B;H360, Re ediyl) Skin Irrit. 2;H en-9-one	<7.5 ;H302, Ski pr. 1B;H36 <5	2399-48-6 219-268-7 in Corr. 1B;H314, Sk 60FD, Aquatic Chror 57472-68-1 260-754-3 Sens. 1;H317, Eye I	01-2120738396-46-XXXX xin Sens. 1;H317, Eye Dam. 1; nic 2;H411 01-2119484629-21-XXXX Dam. 1;H318		

SECTION 4: First aid measures

General information Not available.

4.1. Description of first aid measures

Move to fresh air. If symptoms persist, get medical attention. Inhalation

Skin contact Wash affected areas thoroughly with mild soap and water. If irritation persists get medical

attention.

Not available.

Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure) for at Eye contact

least 15 minutes or until particles are removed. If irritation persists get medical attention.

If the material is swallowed, get immediate medical attention or advice -- Do not induce vomiting. Ingestion

Never give anything by mouth to an unconscious person.

4.2. Most important symptoms

and effects, both acute and

delayed

4.3. Indication of any Not available.

immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

General fire hazards Not available.

5.1. Extinguishing media

Suitable extinguishing Dry powder. Carbon dioxide (CO2). Water may be ineffective.

media

Unsuitable extinguishing Water may be ineffective. Do not use a solid water stream as it may scatter and spread fire.

media

5.2. Special hazards arising from the substance or mixture

Not available.

5.3. Advice for firefighters

Special protective equipment for firefighters

Not available.

Special fire fighting

procedures

Avoid runoff into storm sewers and ditches which lead to waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

Wear appropriate personal protective equipment. Do not touch or walk through spilled material.

For emergency responders

Not available.

6.2. Environmental precautions

Do not let product enter drains. Do not flush into surface water or sanitary sewer system. See also

section 13 Disposal considerations.

6.3. Methods and material for containment and cleaning up

Not available.

6.4. Reference to other

Not available.

sections

SECTION 7: Handling and storage

7.1. Precautions for safe

handling

Avoid contact with skin, eyes and clothing.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from excessive heat or cold. Do not store in direct sunlight. Do not handle or store near an open flame, heat or other sources of ignition. Opaque, high density polyethylene (HDPE)

containers are recommended for shipping and storage.

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

No exposure limits noted for ingredient(s).

Biological limit values

No biological exposure limits noted for the ingredient(s).

Recommended monitoring

procedures

Not available.

Derived no effect levels (DNELs)

Components	Туре	Route	Value	Form
1-vinylhexahydro-2H-azepin-2-one (CAS 2235-00-9)	Workers	Dermal	0.7 mg/kg	Systemic long term
		Inhalation	4.9 mg/m3	Systemic long term
		Inhalation	0.17 mg/m3	Local long term
2-[[3-hydroxy-2,2-bis[[(1-oxoallyl)oxy]methyl]propoxy]methyl]-2-[[(1-oxoallyl)oxy]methyl]-1 3-propandiyldiacrylat (CAS 1384855-91-7)		Dermal	0.5 mg/kg/day	
		Inhalation	1.76 mg/m3	
Dodecyl acrylate (CAS 2156-97-0)	Workers	Dermal	138.9 mg/kg	Systemic long term
		Inhalation	97.9 mg/m3	Systemic long term
exo-1,7,7-trimethylbicyclo[2.2,1]hept-2-yl acrylate (CAS 5888-33-5)	Workers	Dermal	1.39 mg/kg	Systemic long term
Oxybis(methyl-2,1-ethanediyl) diacrylate (CAS 57472-68-1)	Workers	Dermal	2.77 mg/kg	Systemic long term
		Inhalation	24.48 mg/m3	Systemic short term
Phenyl, Bis(2,4,6-trimethylbenzoyl)-phosphine oxide (CAS 162881-26-7)	Workers	Dermal	3.3 mg/kg	Systemic long term
		Dermal	3.3 mg/kg	Systemic short term
		Inhalation	7.8 mg/m3	Systemic long term
		Inhalation	7.8 mg/m3	Systemic short term
Tetrahydrofurfuryl acrylate (CAS 2399-48-6)	Consumers	Dermal	1.75 mg/kg bw/d	Systemic long term
		Inhalation	0.3 mg/m3	Systemic long term
		Oral	0.18 mg/kg bw/d	Systemic long term
	Workers	Dermal	4.9 mg/kg bw/d	Systemic long term
		Inhalation	1.73 mg/m3	Systemic long term

Predicted no effect concentrations (PNECs)

Components	Туре	Route	Value	Form
1-vinylhexahydro-2H-azepin-2-one (CAS 2235-00-9)	Not applicable	Freshwater	0.1 mg/l	
		Intermittent	1 mg/l	Releases
		Marine water	0.01 mg/l	
		Sediment	0.829 mg/kg	Freshwater
		Sediment	0.0829 mg/kg	Marine water
		Soil	0.107 mg/kg	
		STP	262 mg/l	Sewage Treatment Plant
Dodecyl acrylate (CAS 2156-97-0)	Not applicable	Freshwater	0.495 mg/l	
		Intermittent	0.52 mg/l	Releases
		Marine water	0.05 mg/l	
		Sediment	1245.42 mg/kg	Freshwater
		Sediment	124.54 mg/kg	Marine water
		Soil	248.09 mg/kg	
		STP	1000 mg/l	Sewage Treatment Plant
exo-1,7,7-trimethylbicyclo[2.2,1]hept-2-yl acrylate (CAS 5888-33-5)	Not applicable	Freshwater	0.00092 mg/l	J
		Intermittent	0.00704 mg/l	Releases
		Marine water	0.000092 mg/l	
		Sediment	0.145 mg/kg	Freshwater
		Sediment	0.0145 mg/kg	Marine water
		Soil	0.0285 mg/kg	
		STP	2 mg/l	Sewage Treatment Plant
Oxybis(methyl-2,1-ethanediyl) diacrylate (CAS 57472-68-1)	Not applicable	Freshwater	0.0034 mg/l	J
		Intermittent	0.034 mg/l	Releases
		Marine water	0.00034 mg/l	
		Sediment	0.00884 mg/kg	Freshwater
		Soil	0.0013 mg/kg	
		STP	100 mg/l	Sewage Treatment Plant
Phenyl,	Not applicable	Freshwater	0.8 mg/l	G
Bis(2,4,6-trimethylbenzoyl)-phosphine oxide (CAS 162881-26-7)			J	
		Intermittent	0.8 mg/l	Releases
		Marine water	0.8 mg/l	
		STP	1 mg/l	Sewage Treatment Plant
Tetrahydrofurfuryl acrylate (CAS 2399-48-	Not applicable	Freshwater	3.92 µg/l	
		Intermittent	39.2 µg/l	Releases
		Marine water	0.392 µg/l	
		Sediment	0.0206 mg/kg	Freshwater
		Sediment	0.0021 mg/kg	Marine water
		Soil	0.0018 mg/kg	
		STP	2.637 mg/l	Sewage Treatment Plant
			•	~

8.2. Exposure controls

Appropriate engineering Not available.

controls

Individual protection measures, such as personal protective equipment

General information Not available.

Wear safety glasses; chemical goggles (if splashing is possible). Eye wash fountain and Eye/face protection

emergency showers are recommended.

Skin protection

Wear appropriate chemical resistant gloves. Recommended gloves: Nitrile 6 mil minimum - Hand protection

thickness.

- Other Wear appropriate chemical resistant clothing.

Respiratory protection Provide adequate ventilation. In case of insufficient ventilation wear suitable respiratory equipment.

Thermal hazards Not available.

Handle in accordance with good industrial hygiene and safety practice. Do not get this material in Hygiene measures

your eyes, on your skin, or on your clothing. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Launder contaminated clothing before

reuse. Keep away from food and drink.

Environmental exposure

controls

Not available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Liquid. **Physical state Form** Liquid. Color Black.

Odor Characteristic. Not available. Odor threshold

6.8 - 7.2 Metler Toledo pH Meter. Temperature 25°C pН

Melting point/freezing point Not available. Initial boiling point and boiling Not available.

range

Flash point > 212.0 °F (> 100.0 °C) Closed Cup EPA Method 1020

Evaporation rate Not available Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

Flammability limit - upper

Not available.

(%)

Not available. Vapor pressure Not available. Vapor density

Solubility(ies)

Not available. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available. **Decomposition temperature** Not available.

14.5 - 15.5 cP Brookfield Viscometer (± 0.5) Temperature 55°C. Spindle # 18 (S18) RPM 100. Wait Viscosity

approx 10 min to take the reading.

Explosive properties Not available. Not available. Oxidizing properties

9.2. Other information

9.04 g/L Method 24/ASTM D403-93 VOC

SECTION 10: Stability and reactivity

10.1. Reactivity Not available.

10.2. Chemical stability Stable under normal storage conditions.

10.3. Possibility of hazardous

reactions

Hazardous polymerization can occur with decreased inhibitor content.

10.4. Conditions to avoid Exposure to sunlight.

10.5. Incompatible materials Incompatible with strong bases and oxidizing agents. alkaline metals

10.6. Hazardous Upon decomposition, this product may yield gaseous nitrogen oxides, carbon monoxide, carbon

dioxide and/or low molecular weight hydrocarbons. decomposition products

SECTION 11: Toxicological information

Not available General information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system.

Skin contact Causes skin irritation. May cause sensitization by skin contact.

Eye contact Causes serious eye damage.

Ingestion Ingestion is not a likely route of exposure.

Symptoms Not available.

11.1. Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

Components Species Test Results

1-vinylhexahydro-2H-azepin-2-one (CAS 2235-00-9)

<u>Acute</u>

Dermal

LD50 Rabbit 1700 mg/kg

Inhalation

LC50 Rat > 1.6 mg/l

Oral

LD50 Rat 1114 mg/kg

Skin corrosion/irritation Non-corrosive (OECD 431)

Causes skin irritation.

Serious eye damage/eye

irritation
Respiratory sensitization

Based on available data, the classification criteria are not met.

Skin sensitization May cause sensitization by skin contact.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Causes serious eye damage.

Carbon black is classified as a carcinogen by the IARC (possibly carcinogenic to humans, Group 2B) and by the State of California under Proposition 65. In their evaluations of carbon black, both organizations indicate that exposure to carbon black, per se, does not occur when it remains bound within a product matrix, specifically, rubber, ink, or paint. Carbon black is present only in a

bound form in this preparation.

Reproductive toxicity May damage fertility. May damage the unborn child.

Specific target organ toxicity -

single exposure

May cause irritation to the respiratory system.

Specific target organ toxicity -

repeated exposure

Causes damage to organs (liver, respiratory system) through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

Mixture versus substance

information

Not available.

Other information Complete toxicity data are not available for this specific formulation

SECTION 12: Ecological information

12.1. Toxicity

Aquatic toxicityToxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Components		Species	Test Results
Dodecyl acrylate (CAS 215	56-97-0)		
Acute			
	ErC50	Pseudokirchneriella subcapitata	> 0.274 µg/l, 72 h (OECD 201)
	LC50	Leuciscus idus	460 mg/l, 96 h (DIN 38 412, part L 15, 1982)
	NOEC	Leuciscus idus	215 mg/l, 96 h (DIN 38 412, part L 15, 1982)
Chronic			
	LOEC	Daphina magna	> 0.25 µg/l, 21 d (OECD 211)
Aquatic			
Chronic			
Crustacea	NOEC	Daphnia magna	0.25 μg/l, 21 d (OECD 211)
Fish	LOEC	Danio rerio	> 1 μg/l, 36 d (OECD 210)
Phenyl, Bis(2,4,6-trimethyl	benzoyl)-phosphine	e oxide (CAS 162881-26-7)	
Acute	- , - •	,	
	EC50	Desmodesmus subspicatus	> 260 μg/l, 72 h (OECD 201)

Material name: CN872Series SDS LITHUANIA

11209 Version #: 11 Revision date: 20-Apr-2021 Issue date: 27-Nov-2013

Components **Species Test Results** LC50 Danio rerio > 90 µg/l, 96 h (OECD 203) **NOEC** Desmodesmus subspicatus > 260 µg/l, 72 h (OECD 201) Aquatic Acute Crustacea EC50 > 1175 µg/l, 48 h (OECD 202) Daphnia magna Chronic Crustacea **NOEC** Daphnia magna $>= 8.1 \mu g/l, 21 d (OECD 211)$

12.2. Persistence and

degradability

Not available.

12.3. Bioaccumulative potential Not available. **Partition coefficient** Not available.

n-octanol/water (log Kow)

Bioconcentration factor (BCF)

Dodecyl acrylate 2.34, (EPA Epiwin (v.4.11)) Phenyl, Bis(2,4,6-trimethylbenzoyl)-phosphine oxide 5, (similar to OECD 305 C)

12.4. Mobility in soil Not available.

12.5. Results of PBT and vPvB Not a PBT or vPvB substance or mixture.

assessment

12.6. Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Not available.

Contaminated packaging Not available.

EU waste code Not available.

Disposal methods/information Do not dispose of together with general office waste.

Do not allow this material to drain into sewers/water supplies.

Dispose of waste material according to Local, State, Federal, and Provincial Environmental

Regulations.

Ensure collection and disposal with an appropriately licensed waste contractor.

SECTION 14: Transport information

DOT

UN number Not available.
UN proper shipping name Not Regulated

Transport hazard class(es)

Class Not available.

Subsidiary risk -

Packing group Not available.

Environmental hazards

Marine pollutant No

Special precautions for user Not available.

DOT Supplemental Information DOT Classification only applies to shipments within the US and Puerto Rico.

IATA

UN number UN3082

UN proper shipping name Environmentally Hazardous Substance, Liquid, N.O.S. (Acrylates)

Transport hazard class(es)

Class 9
Subsidiary risk Packing group III
Environmental hazards Yes

Special precautions for user Not available.

IATA Supplemental Information When shipping ≤ 5L inner packaging, Special Provision A197 may apply.

IMDG

UN number UN3082

UN proper shipping name Transport hazard class(es)

Environmentally Hazardous Substance, Liquid, N.O.S. (Acrylates), MARINE POLLUTANT

Class 9
Subsidiary risk Packing group III

Transport hazard class(es)

Marine pollutant Yes
EmS F-A, S-F
Special precautions for user Not available.

IMDG Supplemental Information When shipping ≤ 5L containers, IMDG 2.10.2.7 may apply.

ADR

UN number UN3082

UN proper shipping name Environmentally Hazardous Substance, Liquid, N.O.S. (Acrylates)

Transport hazard class(es)

Class 9 Subsidiary risk -

Hazard No. (ADR) Not available.


Tunnel restriction code Not available.

Packing group III
Environmental hazards Yes

Special precautions for user Not available.

ADR Supplemental Information When shipping ≤ 5L containers, ADR 375 may apply.

ADR; IATA; IMDG



Marine pollutant



Further information

Transport in bulk according to Annex II of MARPOL73/78 and the IBC code: Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorizations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

Other regulations All chemical substances in this HP product have been notified or are exempt from notification

under chemical substances notification laws in the following countries: US (TSCA), EU

(EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South Korea, New Zealand, and China. European Union, Canada, Ontario, Japan, Philippines, Korea, New

Zealand and China.

Other information This Safety Data Sheet complies with the requirements of Regulation (EU) 2015/830.

Classification according to Regulation (EC) No 1272/2008 as amended.

Specific Provisions: Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (in the amended version OJ L 396 from 29.05.2007 page 3 with further

rectifications and amendments).

National regulations

15.2. Chemical safety

assessment

Not available.

See attached SUMI or GEIS document, if applicable.

SECTION 16: Other information

References

Regulation (EC) No. 1907/2006 of December 18, 2006 concerning the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH) and establishing a European Chemicals Agency (REACH).

Regulation (EU) 2015/830 of May 28, 2015 amending Regulation (EC) No. 1907/2006.

Regulation (EC) No. 1272/2008 of December 16, 2008 on classification, labeling and packaging of substances and mixtures, and amendments (CLP).

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any H-statements not written out in full under Sections 2 to 15

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H360 May damage fertility or the unborn child.

H360D May damage the unborn child.

H360F May damage fertility.

H360FD May damage fertility. May damage the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
H413 May cause long lasting harmful effects to aquatic life.

A.B. I. () C. () C. () FILE : ...

Revision information 1. Product and Company Identification: EU Poison Center

Composition / Information on Ingredients: Ingredients
9. Physical & Chemical Properties: Multiple Properties
14. Transport Information: Material Transportation Information

HazReg Data: Europe - EU

Training information Follow training instructions when handling this material.

Material name: CN872Series sps_Lithuania

Disclaimer

This Safety Data Sheet document is provided without charge to customers of HP. Data is the most current known to HP at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and may not meet regulatory requirements in other countries.

This safety data sheet is meant to convey information about HP inks (toners) provided in HP Original ink (toner) supplies. If our Safety Data Sheet has been provided to you with a refilled, remanufactured, compatible or other non-HP Original supply please be aware that the information contained herein was not meant to convey information about such products and there could be considerable differences from information in this document and the safety information for the product you purchased. Please contact the seller of the refilled, remanufactured or compatible supplies for applicable information, including information on personal protective equipment, exposure risks and safe handling guidance. HP does not accept refilled, remanufactured or compatible supplies in our recycling programs.

Explanation of abbreviations

ACGIH American Conference of Governmental Industrial Hygienists

CAS Chemical Abstracts Service

CERCLA Comprehensive Environmental Response Compensation and Liability Act

CFR Code of Federal Regulations

COC Cleveland Open Cup

DOT Department of Transportation

EPCRA Emergency Planning and Community Right-to-Know Act (aka SARA)

IARC International Agency for Research on Cancer

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

RCRA Resource Conservation and Recovery Act

REC Recommended

REL Recommended Exposure Limit

SARA Superfund Amendments and Reauthorization Act of 1986

STEL Short-Term Exposure Limit

TCLP Toxicity Characteristics Leaching Procedure

TLV Threshold Limit Value

TSCA Toxic Substances Control Act
VOC Volatile Organic Compounds

Safe Use of Mixture Information (SUMI)

--

UV digital printing inks: UV01 *English*

Disclaimer

This SUMI is a generic document for communicating conditions of safe use of a product in response to the REACH obligation. This document relates only to conditions of safe use and is not specific to a product. By adding this SUMI to a specific product SDS, the importer/formulator declares that the mixture can safely be used following the instructions below. Following occupational health legislation, the employer of workers remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product. Derived No Effect Levels (DNEL) and Predicted No Effect Concentration (PNEC) values of substances derived from the Chemical Safety Assessment (CSA) will be given in section 8 of the SDS.

The REACH registration number(s), where applicable, completes an extended product SDS.

Operational conditions	
Maximum duration	Up to 8 hours per day
Frequency of exposure	< 240 days per year
Process conditions	Covers use at ambient temperatures.
	Adequate ventilation should be provide for the areas where printing is performed. ANSI/ASHRAE Standard 62.1-2013 provides
	guidelines to ensure acceptable air quality in the workspace.
	Keep emissions below the occupational exposure limits of the ingredients specified in section 8 of the SDS.
	Avoid direct contact.
	Regular cleaning of equipment and work area.
	Supervision in place to check that Risk Management Measures are in place are being correctly used and Operational Conditions foll
Diek managament magazura	

Risk management measures

Conditions and measures related to Personal Protection Equipment, hygiene and health evaluation Wear safety glasses with side shields (or goggles), if splashing is possible.

Wear appropriate chemical resistent gloves: see section 8 of the SDS.

Wear appropriate chemical resistent clothing.

Eye wash fountain and emergency showers are recommended.

Avoid breathing mist/vapours.

Avoid contact with skin, eyes and clothing.

Training of workers in relation to proper use and maintenance of all Personal protection equipment (PPE) must be ensured.









Good practice advice

Use personal protective equipment as required.

Wash hands before breaks and after work.

Keep good industrial hygiene and safety practice.

Use only with adequate ventilation.

Do no eat, drink or smoke when using this product.

Wash contaminated clothing before reuse.

Store in a well-ventilated place.

Keep container tightly closed.

Store at room temperature.





Environmental measures

Do not allow this material to drain into sewers/water supplies.

Dispose of waste material according to Local, State, Federal and Provincial Environmental Regulations.

Ensure collection and disposal with appropriately licenced waste contractor.

Use descriptors

IS-Use at industrial sites

PW-Widespread use by professional workers

SU7-Printing and reproduction media

PC18-Inks and Toners

PROC1-Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2-Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC3- Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition

PROC8a-Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC8b-Transfer of substance or mixture (charging and discharging) at dedicated facilities

ERC5-Use at industrial site leading to inclusion into/onto article

ERC8c-Widespread use leading to inclusion into/onto article (indoor)

Additional information on product composition

In section 2 of the SDS as well as on the label, the classification of the mixture is provided.

The classification of the mixture is based on the individuel ingredients and their concentration within the mixture.

All ingredients contributing to the classification are stated in Section 3 of the SDS.

Relevant limit values of ingredients on which the exposure assessment is based, are listed in section 8 of the SDS.

The product may contain sensitizing ingredients that may cause allergic reaction to certain people.

Section 2 of the SDS states these ingredients where applicable.

The product is classified as toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.