



# SAFETY DATA SHEET

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

**Important information** \*\*\* This Safety Data Sheet is only authorised for use by HP for HP Original products. Any unauthorised use of this Safety Data Sheet is strictly prohibited and may result in legal action being taken by HP. \*\*\*

### 1.1. Product identifier

**Trade name or designation of the mixture** G0Y96Series  
**Registration number** -  
**UFI** JAJ2-3XEK-330V-PJWT  
**Synonyms** HP FB794 Black Scitex Ink Cartridge  
**Issue date** 15-Aug-2016  
**Version number** 11  
**Revision date** 27-Apr-2021  
**Supersedes date** 16-Apr-2021

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Inkjet printing  
**Uses advised against** None known.

### 1.3. Details of the supplier of the safety data sheet

HP Europe B.V.  
PO Box 667  
1180 XR Amstelveen  
The Netherlands

**Telephone** +31 20 721 3400

### HP Inc. health effects line

**(Toll-free within the US)** 1-800-457-4209  
**(Direct)** 1-760-710-0048

### HP Inc. Customer Care Line

**(Toll-free within the US)** 1-800-474-6836  
**(Direct)** 1-208-323-2551

**Email:** hpcustomer.inquiries@hp.com

**1.4 Emergency telephone number** +37167032027

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended

#### Health hazards

Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Serious eye damage/eye irritation	Category 2	H319 - Causes serious eye irritation.
Skin sensitization	Category 1	H317 - May cause an allergic skin reaction.
Reproductive toxicity	Category 1B	H360 - May damage fertility or the unborn child.
Specific target organ toxicity - single exposure	Category 3 respiratory tract irritation	H335 - May cause respiratory irritation.
Specific target organ toxicity - repeated exposure	Category 1	H372 - Causes damage to organs (liver, respiratory system) through prolonged or repeated exposure.

#### Environmental hazards

Hazardous to the aquatic environment, long-term aquatic hazard	Category 2	H411 - Toxic to aquatic life with long lasting effects.
--	------------	---

## 2.2. Label elements

### Label according to Regulation (EC) No. 1272/2008 as amended

**Contains:** 1-vinylhexahydro-2H-azepin-2-one, 2,6-di-tert-butyl-.alpha.-dimethylamino-p-cresol, 2-[[[3-hydroxy-2,2-bis[[[(1-oxoallyl)oxy]methyl]propoxy]methyl]-2-[[[(1-oxoallyl)oxy]methyl]-1,3-propandiyl]diacrylat, 2-phenoxyethyl acrylate, Benzophenone, Butylhydroxytoluene, Diphenyl (2,4,6-trimethylbenzoyl) phosphine oxide, Neopentylglycol, propoxylated esters with acrylic acid, Poly (ethylene glycol) diacrylate, Tridecyl acrylate

### Hazard pictograms



### Signal word

Danger

### Hazard statements

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H360	May damage fertility or the unborn child.
H335	May cause respiratory irritation.
H372	Causes damage to organs (liver, respiratory system) through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

### Precautionary statements

#### Prevention

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P202	Do not handle until all safety precautions have been read and understood.
P201	Obtain special instructions before use.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P271	Use only outdoors or in a well-ventilated area.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.

#### Response

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P308 + P313	IF exposed or concerned: Get medical attention/advice.
P312	Call a poison center/doctor if you feel unwell.
P362	Take off contaminated clothing and wash before reuse.
P391	Collect spillage.

#### Storage

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

#### Disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

**Supplemental label information** None.

### 2.3. Other hazards

Potential routes of exposure to this product are skin and eye contact, ingestion, and inhalation.

Benzophenone is classified by the IARC as a Group 2B carcinogen (the substance is possibly carcinogenic to humans).

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
2-phenoxyethyl acrylate	<30	48145-04-6 256-360-6	01-2119980532-35-XXXX	-	
<b>Classification:</b>	Skin Sens. 1A;H317, Repr. 2;H361d, Aquatic Chronic 2;H411				
1-vinylhexahydro-2H-azepin-2-one	<25	2235-00-9 218-787-6	01-2119977109-27-XXXX	-	
<b>Classification:</b>	Acute Tox. 4;H302, Acute Tox. 4;H312, Skin Sens. 1B;H317, Eye Irrit. 2;H319, STOT RE 1;H372				

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Tridecyl acrylate	<15	3076-04-8 221-351-8	-	-	
<b>Classification:</b>	Skin Irrit. 2;H315, Eye Irrit. 2;H319, STOT SE 3;H335, Aquatic Chronic 2;H411				
Neopentylglycol, propoxylated esters with acrylic acid	<10	84170-74-1 -	01-2119970213-43-XXXX	-	
<b>Classification:</b>	Skin Sens. 1B;H317, Aquatic Chronic 2;H411				
2-[[[3-hydroxy-2,2-bis[[[(1-oxoallyl)oxy]methyl]propoxy]methyl]-2-[[[(1-oxoallyl)oxy]methyl]-1,3-propanediyl]diacrylat	<5	1384855-91-7 800-838-4	01-2119980666-22-XXXX	-	
<b>Classification:</b>	Skin Sens. 1A;H317, Eye Irrit. 2;H319, Aquatic Chronic 3;H412				
Diphenyl (2,4,6-trimethylbenzoyl) phosphine oxide	<5	75980-60-8 278-355-8	01-2119972295-29-XXXX	015-203-00-X	
<b>Classification:</b>	Skin Sens. 1B;H317, Repr. 2;H361fd, Aquatic Chronic 2;H411				
Poly (ethylene glycol) diacrylate	<5	26570-48-9 -	-	-	
<b>Classification:</b>	Skin Irrit. 2;H315, Skin Sens. 1;H317, Eye Dam. 1;H318, STOT SE 3;H335, Aquatic Chronic 2;H411				
2,6-di-tert-butyl-.alpha.-dimethylamino -p-cresol	<1	88-27-7 201-816-1	-	-	
<b>Classification:</b>	Acute Tox. 4;H302, Skin Sens. 1;H317, Eye Irrit. 2;H319, Aquatic Acute 1;H400, Aquatic Chronic 1;H410				
Benzophenone	<1	119-61-9 204-337-6	-	-	
<b>Classification:</b>	STOT RE 2;H373, Aquatic Chronic 3;H412				
Butylhydroxytoluene	<1	128-37-0 -	01-2119565113-46-XXXX	-	
<b>Classification:</b>	Aquatic Chronic 1;H410				

**Composition comments** Carbon black is present only in a bound form in this preparation.

## SECTION 4: First aid measures

**General information** Not available.

### 4.1. Description of first aid measures

<b>Inhalation</b>	Move to fresh air. If symptoms persist, get medical attention.
<b>Skin contact</b>	Wash affected areas thoroughly with mild soap and water. If irritation persists get medical attention.
<b>Eye contact</b>	Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure) for at least 15 minutes or until particles are removed. If irritation persists get medical attention.
<b>Ingestion</b>	If the material is swallowed, get immediate medical attention or advice -- Do not induce vomiting. Never give anything by mouth to an unconscious person.

**4.2. Most important symptoms and effects, both acute and delayed** Not available.

**4.3. Indication of any immediate medical attention and special treatment needed** Not available.

## SECTION 5: Firefighting measures

**General fire hazards** Not available.

### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Dry powder. Carbon dioxide (CO <sub>2</sub> ). Water may be ineffective.
<b>Unsuitable extinguishing media</b>	Water may be ineffective. Do not use a solid water stream as it may scatter and spread fire.

**5.2. Special hazards arising from the substance or mixture** Not available.

### 5.3. Advice for firefighters

<b>Special protective equipment for firefighters</b>	Not available.
--	----------------

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

**For non-emergency personnel** Wear appropriate personal protective equipment. Do not touch or walk through spilled material.

**For emergency responders** Not available.

**6.2. Environmental precautions** Do not let product enter drains. Do not flush into surface water or sanitary sewer system. See also section 13 Disposal considerations.**6.3. Methods and material for containment and cleaning up** Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.**6.4. Reference to other sections** Not available.**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling** Avoid contact with skin, eyes and clothing.

**7.2. Conditions for safe storage, including any incompatibilities** Keep away from excessive heat or cold. Do not store in direct sunlight. Do not handle or store near an open flame, heat or other sources of ignition. Opaque, high density polyethylene (HDPE) containers are recommended for shipping and storage.

**7.3. Specific end use(s)** Not available.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters**

**Occupational exposure limits** No exposure limits noted for ingredient(s).

**Biological limit values** No biological exposure limits noted for the ingredient(s).

**Recommended monitoring procedures** Not available.

**Derived no effect levels (DNELs)**

Components	Type	Route	Value	Form
1-vinylhexahydro-2H-azepin-2-one (CAS 2235-00-9)	Workers	Dermal	0.7 mg/kg	Systemic long term
		Inhalation	4.9 mg/m <sup>3</sup>	Systemic long term
		Inhalation	0.17 mg/m <sup>3</sup>	Local long term
2-[[[3-hydroxy-2,2-bis[[[(1-oxoallyl)oxy]methyl]propoxy]methyl]-2-[[[(1-oxoallyl)oxy]methyl]-1,3-propandiyldiacrylat (CAS 1384855-91-7)	Industry	Dermal	0.5 mg/kg/day	
		Inhalation	1.76 mg/m <sup>3</sup>	
2-phenoxyethyl acrylate (CAS 48145-04-6)	Workers	Dermal	1.5 mg/kg	Systemic long term
		Inhalation	77 mg/m <sup>3</sup>	Local long term
		Inhalation	10 mg/m <sup>3</sup>	Systemic long term
Butylhydroxytoluene (CAS 128-37-0)	Workers	Dermal	166 mg/kg	Systemic short term
		Dermal	0.3 mg/kg	Systemic long term
		Inhalation	3.5 mg/m <sup>3</sup>	Systemic long term
		Inhalation	2 mg/m <sup>3</sup>	Systemic short term
Diphenyl (2,4,6-trimethylbenzoyl) phosphine oxide (CAS 75980-60-8)	Workers	Dermal	0.233 mg/kg	Systemic long term
		Inhalation	0.822 mg/m <sup>3</sup>	Systemic long term
Neopentylglycol, propoxylated esters with acrylic acid (CAS 84170-74-1)	Workers	Dermal	3.33 mg/kg	Systemic long term
		Inhalation	11.75 mg/m <sup>3</sup>	Systemic long term

**Predicted no effect concentrations (PNECs)**

Components	Type	Route	Value	Form
1-vinylhexahydro-2H-azepin-2-one (CAS 2235-00-9)	Not applicable	Freshwater	0.1 mg/l	
		Intermittent	1 mg/l	Releases
		Marine water	0.01 mg/l	
		Sediment	0.829 mg/kg	Freshwater
		Sediment	0.0829 mg/kg	Marine water
		Soil	0.107 mg/kg	
		STP	262 mg/l	Sewage Treatment Plant

Components	Type	Route	Value	Form
2-phenoxyethyl acrylate (CAS 48145-04-6)	Not applicable	Freshwater	0.002 mg/l	
		Intermittent	0.0121 mg/l	Releases
		Marine water	0.0002 mg/l	
		Sediment	0.02 mg/kg	Freshwater
		Sediment	0.002 mg/kg	Marine water
		Soil	0.006 mg/kg	
		STP	1.77 mg/l	Sewage Treatment Plant
Butylhydroxytoluene (CAS 128-37-0)	Not applicable	Freshwater	0.0041 mg/l	
		Intermittent	0.00199 mg/l	Releases
		Marine water	0.0041 mg/l	
		Sediment	0.731 mg/kg	Freshwater
		Sediment	0.731 mg/kg	Marine water
		Soil	0.0477 mg/kg	
		STP	0.17 mg/l	Sewage Treatment Plant
Diphenyl (2,4,6-trimethylbenzoyl) phosphine oxide (CAS 75980-60-8)	Not applicable	Freshwater	0.00353 mg/l	
		Intermittent	0.0353 mg/l	Releases
		Marine water	0.0005353 mg/l	
		Sediment	0.29 mg/kg	Freshwater
		Sediment	0.029 mg/kg	Marine water
		Soil	0.0557 mg/kg	
		STP	0.17 mg/l	Sewage Treatment Plant
Neopentylglycol, propoxylated esters with acrylic acid (CAS 84170-74-1)	Not applicable	Freshwater	0.0027 mg/l	
		Intermittent	0.027 mg/l	Releases
		Marine water	0.00027 mg/l	
		Sediment	0.188 mg/kg	Freshwater
		Sediment	0.018 mg/kg	Marine water
		Soil	0.036 mg/kg	
		STP	0.2 mg/l	Sewage Treatment Plant

**Exposure guidelines** Exposure limits have not been established for this product.

## 8.2. Exposure controls

**Appropriate engineering controls** Not available.

### Individual protection measures, such as personal protective equipment

**General information** Not available.

**Eye/face protection** Wear safety glasses; chemical goggles (if splashing is possible). Eye wash fountain and emergency showers are recommended.

#### Skin protection

**- Hand protection** Wear appropriate chemical resistant gloves. Recommended gloves: Nitrile 6 mil minimum thickness.

**- Other** Wear appropriate chemical resistant clothing.

**Respiratory protection** Provide adequate ventilation. In case of insufficient ventilation wear suitable respiratory equipment.

**Thermal hazards** Not available.

**Hygiene measures** Handle in accordance with good industrial hygiene and safety practice. Do not get this material in your eyes, on your skin, or on your clothing. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Launder contaminated clothing before reuse. Keep away from food and drink.

**Environmental exposure controls** Not available.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

**Physical state** Liquid.

**Form** Liquid.

**Color** Black.

**Odor** Characteristic.

**Odor threshold** Not available.

**pH** 7.4 - 7.8 Metler Toledo pH Meter. Temperature 25°C

<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	Not available.
<b>Flash point</b>	> 199.9 °F (> 93.3 °C) Calculated
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	Not available.
<b>Flammability limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	Not available.
<b>Vapor density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	9.3 - 10.6 cP Brookfield Viscometer Temperature 50°C
<b>Explosive properties</b>	Not available.
<b>Oxidizing properties</b>	Not available.
<b>9.2. Other information</b>	
<b>Chemical family</b>	Acrylate/Polymer/Pigment Blend
<b>VOC</b>	0.2 g/L Calculated

---

## SECTION 10: Stability and reactivity

<b>10.1. Reactivity</b>	Not available.
<b>10.2. Chemical stability</b>	Stable under normal storage conditions.
<b>10.3. Possibility of hazardous reactions</b>	Hazardous polymerization can occur with decreased inhibitor content.
<b>10.4. Conditions to avoid</b>	Exposure to sunlight.
<b>10.5. Incompatible materials</b>	Incompatible with strong bases and oxidizing agents. alkaline metals
<b>10.6. Hazardous decomposition products</b>	Upon decomposition, this product may yield gaseous nitrogen oxides, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

---

## SECTION 11: Toxicological information

<b>General information</b>	Not available.
<b>Information on likely routes of exposure</b>	
<b>Inhalation</b>	Inhalation may result in mild irritation to the respiratory system.
<b>Skin contact</b>	Causes skin irritation. May cause sensitization by skin contact.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	Ingestion is not a likely route of exposure.
<b>Symptoms</b>	Not available.

### 11.1. Information on toxicological effects

**Acute toxicity** Based on available data, the classification criteria are not met.

<b>Components</b>	<b>Species</b>	<b>Test Results</b>
1-vinylhexahydro-2H-azepin-2-one (CAS 2235-00-9)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	1700 mg/kg
<b>Inhalation</b>		
LC50	Rat	> 1.6 mg/l
<b>Oral</b>		
LD50	Rat	1114 mg/kg

<b>Skin corrosion/irritation</b>	Causes skin irritation.
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.
<b>Respiratory sensitization</b>	Based on available data, the classification criteria are not met.
<b>Skin sensitization</b>	May cause sensitization by skin contact.
<b>Germ cell mutagenicity</b>	Based on available data, the classification criteria are not met.
<b>Carcinogenicity</b>	Based on available data, the classification criteria are not met.

Carbon black is classified as a carcinogen by the IARC (possibly carcinogenic to humans, Group 2B) and by the State of California under Proposition 65. In their evaluations of carbon black, both organizations indicate that exposure to carbon black, per se, does not occur when it remains bound within a product matrix, specifically, rubber, ink, or paint. Carbon black is present only in a bound form in this preparation.

#### IARC Monographs. Overall Evaluation of Carcinogenicity

Benzophenone (CAS 119-61-9)	2B Possibly carcinogenic to humans.
Butylhydroxytoluene (CAS 128-37-0)	3 Not classifiable as to carcinogenicity to humans.

<b>Reproductive toxicity</b>	Suspected of damaging the unborn child.
<b>Specific target organ toxicity - single exposure</b>	May cause irritation to the respiratory system.
<b>Specific target organ toxicity - repeated exposure</b>	Causes damage to organs (liver, respiratory system) through prolonged or repeated exposure.
<b>Aspiration hazard</b>	Based on available data, the classification criteria are not met.
<b>Mixture versus substance information</b>	Not available.
<b>Other information</b>	Complete toxicity data are not available for this specific formulation

## SECTION 12: Ecological information

### 12.1. Toxicity

**Aquatic toxicity** Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. This product has not been tested for ecological effects.

Components	Species	Test Results
2-phenoxyethyl acrylate (CAS 48145-04-6)		
<i>Acute</i>		
	EC10	Desmodesmus subcapitatus 0.71 mg/l, 72 h (DIN 38412 L9)
	EC50	Desmodesmus subcapitatus 4.44 mg/l, 72 h (DIN 38412 L9)
	LC50	Leuciscus idus 10 mg/l, 96 h (DIN 38 412)
	NOEC	Desmodesmus subcapitatus 0.71 mg/l, 72 h (DIN 38412 L9)
<b>Aquatic</b>		
<i>Acute</i>		
Crustacea	EC50	Daphnia magna 1.21 mg/l, 48 h (Directive CE 79/831/CEE, Annex V, Part C)
Diphenyl (2,4,6-trimethylbenzoyl) phosphine oxide (CAS 75980-60-8)		
<i>Acute</i>		
	EC10	Pseudokirchneriella subcapitata 1.56 mg/l, 72 h (OECD 201)
	EC50	Pseudokirchneriella subcapitata > 2.01 mg/l, 72 h (OECD 201)
	LC50	Cyprinus carpio 1.4 mg/l, 96 h (OECD 203)
<b>Aquatic</b>		
<i>Acute</i>		
Crustacea	EC50	Daphnia magna 3.53 mg/l, 48 h (OECD 202)
Neopentylglycol, propoxylated esters with acrylic acid (CAS 84170-74-1)		
<i>Acute</i>		
	EC10	Pseudokirchneriella subcapitata 2.3 mg/l, 72 h (OECD 201)
	EC50	Pseudokirchneriella subcapitata 11 mg/l, 72 h (OECD 201)
<b>Aquatic</b>		
<i>Acute</i>		
Crustacea	EC50	Daphnia Magna 37 mg/l, 48 h (OECD 202)
Fish	LC50	Danio rerio 2.7 mg/l, 96 h (OECD 203)

<b>12.2. Persistence and degradability</b>	Not available.
<b>12.3. Bioaccumulative potential</b>	Not available.
<b>Partition coefficient n-octanol/water (log Kow)</b>	Not available.
<b>Bioconcentration factor (BCF)</b>	
Diphenyl (2,4,6-trimethylbenzoyl) phosphine oxide	72, (JIS K 0102-1986, 71 - Kanpogyo No .S, Yakuhatsu No . 615, 4 MITI/MHW Chemical Substance Control Law, Japan)
<b>12.4. Mobility in soil</b>	Not available.
<b>12.5. Results of PBT and vPvB assessment</b>	Not a PBT or vPvB substance or mixture.
<b>12.6. Other adverse effects</b>	Not available.

---

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>Residual waste</b>	Not available.
<b>Contaminated packaging</b>	Not available.
<b>EU waste code</b>	Not available.
<b>Disposal methods/information</b>	Do not dispose of together with general office waste. Do not allow this material to drain into sewers/water supplies. Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations. Ensure collection and disposal with an appropriately licensed waste contractor.

---

## SECTION 14: Transport information

### DOT

<b>UN number</b>	Not available.
<b>UN proper shipping name</b>	Not Regulated
<b>Transport hazard class(es)</b>	
<b>Class</b>	Not available.
<b>Subsidiary risk</b>	-
<b>Packing group</b>	Not available.
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	No
<b>Special precautions for user</b>	Not available.
<b>DOT Supplemental Information</b>	DOT Classification only applies to shipments within the US and Puerto Rico.

### IATA

<b>UN number</b>	UN3082
<b>UN proper shipping name</b>	Environmentally Hazardous Substance, Liquid, N.O.S. (Acrylates)
<b>Transport hazard class(es)</b>	
<b>Class</b>	9
<b>Subsidiary risk</b>	-
<b>Packing group</b>	III
<b>Environmental hazards</b>	Yes
<b>Special precautions for user</b>	Not available.
<b>IATA Supplemental Information</b>	When shipping ≤ 5L inner packaging, Special Provision A197 may apply.

### IMDG

<b>UN number</b>	UN3082
<b>UN proper shipping name</b>	Environmentally Hazardous Substance, Liquid, N.O.S. (Acrylates), MARINE POLLUTANT
<b>Transport hazard class(es)</b>	
<b>Class</b>	9
<b>Subsidiary risk</b>	-
<b>Packing group</b>	III
<b>Transport hazard class(es)</b>	
<b>Marine pollutant</b>	Yes
<b>EmS</b>	F-A, S-F
<b>Special precautions for user</b>	Not available.
<b>IMDG Supplemental Information</b>	When shipping ≤ 5L containers, IMDG 2.10.2.7 may apply.


### ADR

<b>UN number</b>	UN3082
<b>UN proper shipping name</b>	Environmentally Hazardous Substance, Liquid, N.O.S. (Acrylates)
<b>Transport hazard class(es)</b>	
<b>Class</b>	9




<b>Subsidiary risk</b>	-
<b>Hazard No. (ADR)</b>	Not available.
<b>Tunnel restriction code</b>	Not available.
<b>Packing group</b>	III
<b>Environmental hazards</b>	Yes
<b>Special precautions for user</b>	Not available.
<b>ADR Supplemental Information</b>	When shipping ≤ 5L containers, ADR 375 may apply.

**ADR; IATA; IMDG**



**Marine pollutant**



**Further information**

Transport in bulk according to Annex II of MARPOL73/78 and the IBC code: Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulations

**Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended**

Not listed.

**Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended**

Not listed.

**Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended**

Not listed.

**Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA**

Not listed.

#### Authorizations

**Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended**

Not listed.

#### Restrictions on use

**Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended**

Not listed.

**Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended**

Not listed.

## Other EU regulations

### Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

## Other regulations

The components of this product are reported in the following inventories: USA, European Union, Canada, Japan, China, Australia, Korea.

## Other information

This Safety Data Sheet complies with the requirements of Regulation (EU) 2015/830. Classification according to Regulation (EC) No 1272/2008 as amended.

Specific Provisions: Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (in the amended version OJ L 396 from 29.05.2007 page 3 with further rectifications and amendments).

## National regulations

Not available.

### 15.2. Chemical safety assessment

See attached SUMI or GEIS document, if applicable.

---

## SECTION 16: Other information

### References

Regulation (EC) No. 1907/2006 of December 18, 2006 concerning the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH) and establishing a European Chemicals Agency (REACH).

Regulation (EU) 2015/830 of May 28, 2015 amending Regulation (EC) No. 1907/2006.

Regulation (EC) No. 1272/2008 of December 16, 2008 on classification, labeling and packaging of substances and mixtures, and amendments (CLP).

### Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

### Full text of any H-statements not written out in full under Sections 2 to 15

H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H361d Suspected of damaging the unborn child.  
H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.  
H372 Causes damage to organs through prolonged or repeated exposure.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

### Revision information

3. Composition / Information on Ingredients: Disclosure Overrides

### Training information

Follow training instructions when handling this material.

### Disclaimer

This Safety Data Sheet document is provided without charge to customers of HP. Data is the most current known to HP at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and may not meet regulatory requirements in other countries.

This safety data sheet is meant to convey information about HP inks (toners) provided in HP Original ink (toner) supplies. If our Safety Data Sheet has been provided to you with a refilled, remanufactured, compatible or other non-HP Original supply please be aware that the information contained herein was not meant to convey information about such products and there could be considerable differences from information in this document and the safety information for the product you purchased. Please contact the seller of the refilled, remanufactured or compatible supplies for applicable information, including information on personal protective equipment, exposure risks and safe handling guidance. HP does not accept refilled, remanufactured or compatible supplies in our recycling programs.

## Explanation of abbreviations

<b>ACGIH</b>	American Conference of Governmental Industrial Hygienists
<b>CAS</b>	Chemical Abstracts Service
<b>CERCLA</b>	Comprehensive Environmental Response Compensation and Liability Act
<b>CFR</b>	Code of Federal Regulations
<b>COC</b>	Cleveland Open Cup
<b>DOT</b>	Department of Transportation
<b>EPCRA</b>	Emergency Planning and Community Right-to-Know Act (aka SARA)
<b>IARC</b>	International Agency for Research on Cancer
<b>NIOSH</b>	National Institute for Occupational Safety and Health
<b>NTP</b>	National Toxicology Program
<b>OSHA</b>	Occupational Safety and Health Administration
<b>PEL</b>	Permissible Exposure Limit
<b>RCRA</b>	Resource Conservation and Recovery Act
<b>REC</b>	Recommended
<b>REL</b>	Recommended Exposure Limit
<b>SARA</b>	Superfund Amendments and Reauthorization Act of 1986
<b>STEL</b>	Short-Term Exposure Limit
<b>TCLP</b>	Toxicity Characteristics Leaching Procedure
<b>TLV</b>	Threshold Limit Value
<b>TSCA</b>	Toxic Substances Control Act
<b>VOC</b>	Volatile Organic Compounds

# Safe Use of Mixture Information (SUMI)

--

## UV digital printing inks: UV01 \*English\*

### Disclaimer





*This SUMI is a generic document for communicating conditions of safe use of a product in response to the REACH obligation. This document relates only to conditions of safe use and is not specific to a product. By adding this SUMI to a specific product SDS, the importer/formulator declares that the mixture can safely be used following the instructions below. Following occupational health legislation, the employer of workers remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product. Derived No Effect Levels (DNEL) and Predicted No Effect Concentration (PNEC) values of substances derived from the Chemical Safety Assessment (CSA) will be given in section 8 of the SDS.*

*The REACH registration number(s), where applicable, completes an extended product SDS.*



### Operational conditions

<b>Maximum duration</b>	Up to 8 hours per day
<b>Frequency of exposure</b>	< 240 days per year
<b>Process conditions</b>	Covers use at ambient temperatures. Adequate ventilation should be provide for the areas where printing is performed. ANSI/ASHRAE Standard 62.1-2013 provides guidelines to ensure acceptable air quality in the workspace. Keep emissions below the occupational exposure limits of the ingredients specified in section 8 of the SDS. Avoid direct contact. Regular cleaning of equipment and work area. Supervision in place to check that Risk Management Measures are in place are being correctly used and Operational Conditions foll

### Risk management measures

<b>Conditions and measures related to Personal Protection Equipment, hygiene and health evaluation</b>	<p>Wear safety glasses with side shields (or goggles), if splashing is possible. Wear appropriate chemical resistant gloves: see section 8 of the SDS. Wear appropriate chemical resistant clothing. Eye wash fountain and emergency showers are recommended. Avoid breathing mist/vapours. Avoid contact with skin, eyes and clothing. Training of workers in relation to proper use and maintenance of all Personal protection equipment (PPE) must be ensured.</p> <div style="display: flex; justify-content: space-around; align-items: center;">     </div>
--	--

### Good practice advice

<p>Use personal protective equipment as required. Wash hands before breaks and after work. Keep good industrial hygiene and safety practice. Use only with adequate ventilation. Do no eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Store in a well-ventilated place. Keep container tightly closed. Store at room temperature.</p>	 
--	---

### Environmental measures

Do not allow this material to drain into sewers/water supplies.  
Dispose of waste material according to Local, State, Federal and Provincial Environmental Regulations.  
Ensure collection and disposal with appropriately licenced waste contractor.

### Use descriptors

- IS-Use at industrial sites
- PW-Widespread use by professional workers
- SU7-Printing and reproduction media
- PC18-Inks and Toners
- PROC1-Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.
- PROC2-Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
- PROC3- Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
- PROC8a-Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
- PROC8b-Transfer of substance or mixture (charging and discharging) at dedicated facilities
- ERC5-Use at industrial site leading to inclusion into/onto article
- ERC8c-Widespread use leading to inclusion into/onto article (indoor)

### Additional information on product composition

In section 2 of the SDS as well as on the label, the classification of the mixture is provided.  
The classification of the mixture is based on the individual ingredients and their concentration within the mixture.  
All ingredients contributing to the classification are stated in Section 3 of the SDS.  
Relevant limit values of ingredients on which the exposure assessment is based, are listed in section 8 of the SDS.  
The product may contain sensitizing ingredients that may cause allergic reaction to certain people.  
Section 2 of the SDS states these ingredients where applicable.  
The product is classified as toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.